

Cooling Incubator



Name : Cooling Incubator (catalog P3)

Type: LRH-100CL, LRH-100CA, LRH-100CB,
LRH-150CL, LRH-150CA, LRH-150CB,
LRH-250CL, LRH-250CA, LRH-250CB

Microprocessor Controller

Summary:

Serve for preserve culture medium, serum, medicine as well as microorganism training and environmental testing etc.

Features:

- Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable.
- Latest PID controller
- R134a refrigerant, imported compressor
- Independent temperature-limiting alarm system ensures experiments run safely. (option)
- Printer connector and RS485 connector are options which can connect printer and computer to record the parameters and the variations of temperature. (option)
- There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement.

Specifications

Model	LRH-100CL LRH-100CA LRH-100CB	LRH-150CL LRH-150CA LRH-150CB	LRH-250CL LRH-250CA LRH-250CB
Temperature Range	L:-10~65°C A:-20~65°C B:-40~65°C		
Display Resolution	0.1°C		
Temperature Stability	over room temp:±0.5°C, below room temp:±1°C		
Electrical Requirement	220V 50HZ	220V 50HZ	220V 50HZ 220V 50HZ 380V 50HZ
Ambient Temperature	220V 50HZ		
Power Consumption	+5~35°C		
Interior Dimension (W×D×H) mm	500×400×600	550×405×670	600×500×830
Exterior Dimension (W×D×H) mm	650×770×1320	690×800×1430	740×900×1580
(W×D×H) mm	2(pcs)	3(pcs)	3(pcs)
Timing Range	1~9999min		

Options:

- Intelligent programmable temperature & Humidity controller
- Printer
- Independent temperature-limiting Alarm system
- Test hole on the left (Φ50mm)
- BOD socket
- RS485 connector
- UV Sterilizer