

Product Catalog-2020



Product Catalog

1	Introduction to Cameras	13
2	Camera & Microscope Configuration	18
3.1	Trinocular Digital Microscope (1/2).....	18
3.2	Trinocular Digital Microscope (2/2).....	18
3.3	Binocular Digital Microscope	19
3.4	Size Description of the Connection Parts	20
3	Microscope Auto Focus HDMI CMOS Camera.....	21
4.1	XFCAM1080PHB/PHD Auto Focus HDMI's Characteristic	21
4.2	XFCAM1080PHB/PHD Datasheet(2).....	23
4.3	XFCAM1080PHB/PHD and Microscope	24
4.4	Dimension of XFCAM1080PHB/PHD	25
4.5	Packing Information for XFCAM1080PHB/PHD	26
4.6	Extension of XFCAM1080PHB/PHD with Microscope or Telescope Adapter	27
5	Microscope HDMI CMOS Camera.....	28

Product Catalog

5.1 XCAM4K Series HDMI/GE/WiFi Multi-outputs C-mount CMOS Camera (2)	28
5.1.1 <i>XCAM4K Series' Basic Characteristic</i>	28
5.1.2 <i>XCAM4K Series' Datasheet(2)</i>	29
5.1.3 <i>Dimension of XCAM4K Series</i>	30
5.1.4 <i>Packing Information of XCAM4K Series</i>	31
5.1.5 <i>Extension of XCAM4K Series with Microscope or Telescope Adapter</i>	32
5.1.6 <i>Application of XCAM4K Series Camera</i>	33
5.1.7 <i>Images Captured by XCAM4K8MPA</i>	34
5.1.8 <i>XCAM4K Camera and Microscope</i>	37
5.2 XCAM0720PHA C-mount HDMI CMOS Camera(1) <small>(Stopped)</small>	73
5.2.1 <i>XCAM0720PHA's Basic Characteristic</i>	73
5.2.2 <i>XCAM0720PHA Datasheet</i>	74
5.2.3 <i>Function Key Description</i>	75
5.2.4 <i>Dimension of XCAM0720PHA</i>	77
5.2.5 <i>Packing Information for XCAM720PHA</i>	78
5.2.6 <i>Extension of XCAM0720PHA Camera with Microscope or Telescope Adapter</i>	79
5.3 XCAM0720PHB/PHC C-mount HDMI CMOS Camera (2)	55
5.3.1 <i>XCAM0720PHB/PHC's Basic Characteristic</i>	67
5.3.2 <i>XCAM0720PHB/PHC Datasheet(2)</i>	68
5.3.3 <i>Hardware Interface and XCamView UI Description</i>	69
5.3.4 <i>Dimension of XCAM0720PHB/PHC</i>	70
5.3.5 <i>Packing Information for XCAM0720PHB/PHC</i>	71
5.3.6 <i>Extension of XCAM0720PHB/PHC with Microscope or Telescope Adapter</i>	72
5.4 ALPHA1080 Series HDMI+USB Outputs C-mount CMOS Camera(2)	55
5.4.1 <i>ALPHA1080 Series' Basic Characteristics</i>	55
5.4.2 <i>ALPHA1080 Series Datasheet(2)</i>	57
5.4.3 <i>ALPHA1080 Series and Microscope</i>	58
5.4.4 <i>Dimension of ALPHA1080 Series</i>	60
5.4.5 <i>Packing Information for ALPHA1080 Series</i>	61
5.4.6 <i>Extension of ALPHA1080 with Microscope or Telescope Adapter</i>	62
5.4.7 <i>Sample Photos Captured with ALPHA1080A</i>	63
5.5 XCAM1080PHA C-mount HDMI+USB Output CMOS Camera(1)	39
5.5.1 <i>XCAM1080PHA's Basic Characteristic</i>	39
5.5.2 <i>XCAM1080PHA Datasheet(1)</i>	41
5.5.3 <i>XCAM1080PHA and Microscope</i>	42
5.5.4 <i>Dimension of XCAM1080PHA</i>	44
5.5.5 <i>Packing Information for XCAM1080PHA</i>	45
5.5.6 <i>Extension of XCAM1080PHA with Microscope or Telescope Adapter</i>	46
5.6 XCAM1080PHB/PHD/PHE C-mount HDMI+WiFi Output CMOS Camera.....	47
5.6.1 <i>XCAM1080PHB/PHD/PHE's Basic Characteristic</i>	47
5.6.2 <i>XCAM1080PHB/PHD/PHE Datasheet(3)</i>	49
5.6.3 <i>XCAM1080PHB/PHD/PHE and Microscope</i>	50
5.6.4 <i>Dimension of XCAM1080PHB/PHD/PHE</i>	52
5.6.5 <i>Packing Information for XCAM1080PHB/PHD/PHE</i>	53
5.6.6 <i>Extension of XCAM1080PHB/PHD/PHE with Microscope or Telescope Adapter</i>	54
6 Microscope TE-Cooling USB2.0 and 3.0 CCD Camera.....	55
6.1 MTR3CCD Series TE-Cooling C-mount USB3.0 CCD Camera	80
6.1.1 <i>The Basic Characteristic of MTR3CCD</i>	80
6.1.2 <i>MTR3CCD Datasheet(12)</i>	81
6.1.3 <i>MTR3CCD Dimension</i>	82
6.1.4 <i>Packing Information for MTR3CCD Camera</i>	83
6.2 SCCCD Series TE Cooling C-mount USB2.0 CCD Camera <small>suspended</small>	84
6.2.1 <i>The Basic Characteristic of SCCCD</i>	84
6.2.2 <i>SCCCD Datasheet(5)</i>	85
6.2.3 <i>Dimension of SCCCD</i>	86
6.2.4 <i>Packing Information for SCCCD</i>	87
7 Microscope USB3.0 CCD Camera.....	88

7.1	U3CCD Series C-mount USB3.0 CCD Camera	88
7.1.1	<i>U3CCD Basic Characteristic</i>	88
7.1.2	<i>U3CCD Datasheet (10)</i>	89
7.1.3	<i>Dimension of U3CCD</i>	90
7.1.4	<i>Packing Information for U3CCD Series Camera</i>	91
7.1.5	<i>Extension of U3CCD with Microscope or Telescope Adapter</i>	92
8	Microscope USB2.0 CCD Camera	93
8.1	EXCCD Series C-mount USB2.0 CCD Camera	93
8.1.1	<i>EXCCD Basic Characteristic</i>	93
8.1.2	<i>EXCCD Datasheet(4)</i>	94
8.1.3	<i>Dimension of EXCCD</i>	95
8.1.4	<i>Packing Information of EXCCD</i>	96
8.1.5	<i>Extension of EXCCD with Microscope or Telescope Adapter</i>	97
8.2	UHCCD Series C-mount USB2.0 CCD Camera	98
8.2.1	<i>UHCCD Basic Characteristic</i>	98
8.2.2	<i>UHCCD Datasheet(9)</i>	99
8.2.3	<i>Dimension of UHCCD</i>	100
8.2.4	<i>Packing Information of UHCCD</i>	101
8.2.5	<i>Extension of UHCCD with Microscope or Telescope Adapter</i>	102
9	Microscope USB3.0 CMOS Camera	103
9.1	MTR3CMOS Series TE-Cooling C-mount USB3.0 CMOS Camera	103
9.1.1	<i>The Basic Characteristic of MTR3CMOS</i>	103
9.1.2	<i>MTR3CMOS Datasheet(10)</i>	104
9.1.3	<i>MTR3CMOS Dimension</i>	105
9.1.4	<i>Packing Information for MTR3CMOS Camera</i>	106
9.1.5	<i>Extension of MTR3CMOS with Microscope Adapter</i>	107
9.1.6	<i>Sample Photos Captured with MTR3CMOS Camera</i>	108
9.2	BigEye Series M42 and M42 to C or F Mount USB3.0 CMOS Camera	109
9.2.1	<i>Characteristic</i>	115
9.2.2	<i>BigEye Datasheet (3)</i>	117
9.2.3	<i>Dimension of BigEye</i>	119
9.2.4	<i>Packing Information for BigEye</i>	120
9.3	I3 Series C-mount USB3.0 CMOS Camera with Hardware ISP	121
9.3.1	<i>I3 Basic Characteristic</i>	121
9.3.2	<i>I3CMOS Datasheet (6)</i>	122
9.3.3	<i>I3ISPM Datasheet (6)</i>	122
9.3.4	<i>Dimension of I3</i>	124
9.3.5	<i>Packing Information for I3</i>	125
9.3.6	<i>Extension of I3 with Microscope or Telescope Adapter</i>	126
9.4	E3ISPM Series C-mount USB3.0 CMOS Camera with Hardware ISP and Video Pipeline.....	127
9.4.1	<i>E3ISPM Basic Characteristic</i>	127
9.4.2	<i>E3ISPM Datasheet (16)</i>	128
9.4.3	<i>Dimension of E3ISPM</i>	130
9.4.4	<i>Packing Information for E3ISPM</i>	131
9.4.5	<i>Extension of E3ISPM with Microscope or Telescope Adapter</i>	132
9.5	E3CMOS Series C-mount USB3.0 CMOS Camera	133
9.5.1	<i>E3CMOS Basic Characteristic</i>	133
9.5.2	<i>E3CMOS Datasheet(19)</i>	134
9.5.3	<i>Dimension of E3CMOS</i>	136
9.5.4	<i>Packing Information for E3CMOS</i>	137
9.5.5	<i>Extension of E3CMOS with Microscope or Telescope Adapter</i>	138
9.6	U3ISPM Series C-mount USB3.0 CMOS Camera with Hardware ISP and Video Pipeline Inside	139
9.6.1	<i>U3ISPM Basic Characteristic</i>	139
9.6.2	<i>U3ISPM Datasheet(3)</i>	140
9.6.3	<i>Dimension of U3ISPM</i>	141
9.6.4	<i>Packing Information for U3ISPM</i>	142

Product Catalog

9.6.5	<i>Extension of U3ISPM with Microscope or Telescope Adapter</i>	143
9.7	L3CMOS Series C-mount USB3.0 CMOS Camera.....	144
9.7.1	<i>L3CMOS Basic Characteristic</i>	144
9.7.2	<i>L3CMOS Datasheet(5)</i>	145
9.7.3	<i>Dimension of L3CMOS</i>	146
9.7.4	<i>Packing Information of L3CMOS</i>	147
9.7.5	<i>Extension of L3CMOS with Microscope or Telescope Adapter</i>	148
9.8	U3CMOS Series C-mount USB3.0 CMOS Camera	149
9.8.1	<i>U3CMOS Basic Characteristic</i>	149
9.8.2	<i>U3CMOS Datasheet(10)</i>	150
9.8.3	<i>Dimension of U3CMOS</i>	151
9.8.4	<i>Packing Information for U3CMOS</i>	152
9.8.5	<i>Extension of U3CMOS with Microscope or Telescope Adapter</i>	153
9.9	C3CMOS Series C-mount USB3.0 CMOS Camera	154
9.9.1	<i>C3CMOS Basic Characteristic</i>	154
9.9.2	<i>C3CMOS Datasheet(2)</i>	155
9.9.3	<i>Dimension of C3CMOS</i>	156
9.9.4	<i>Packing Information for C3CMOS</i>	157
9.9.5	<i>Extension of C3CMOS with Microscope or Telescope Adapter</i>	158
9.10	S3CMOS Series USB3.0 Eyepiece Camera	159
9.10.1	<i>S3CMOS Characteristic</i>	159
9.10.2	<i>S3CMOS Datasheet(2)</i>	160
9.10.3	<i>Dimension of S3CMOS</i>	161
9.10.4	<i>Packing Information for S3CMOS</i>	162
10	Microscope USB2.0 CMOS Camera	163
10.1	ECMOS Series C-mount USB2.0 CMOS Camera.....	163
10.1.1	<i>ECMOS Basic Characteristic</i>	163
10.1.2	<i>ECMOS Datasheet (7)</i>	164
10.1.3	<i>Dimension of ECMOS</i>	165
10.1.4	<i>Packing Information for ECMOS</i>	166
10.1.5	<i>Extension of ECMOS with Microscope or Telescope Adapter</i>	167
10.2	LCMOS Series C-mount USB2.0 CMOS Camera	168
10.2.1	<i>LCMOS Characteristic</i>	168
10.2.2	<i>LCMOS Datasheet (10)</i>	169
10.2.3	<i>Dimension of LCMOS</i>	170
10.2.4	<i>Packing Information of LCMOS</i>	171
10.2.5	<i>Extension of LCMOS with Microscope or Telescope Adapter</i>	172
10.3	UA Series C-mount USB2.0 CMOS Camera	173
10.3.1	<i>UA's Basic Characteristic</i>	173
10.3.2	<i>UA Datasheet(5)</i>	174
10.3.3	<i>Dimension of UA</i>	175
10.3.4	<i>Packing Information for UA</i>	176
10.3.5	<i>Extension of UA with Microscope or Telescope Adapter</i>	177
10.4	UCMOS Series C-mount USB2.0 CMOS Camera	178
10.4.1	<i>UCMOS Basic Characteristic</i>	183
10.4.2	<i>UCMOS Datasheet(10)</i>	184
10.4.3	<i>Dimension of UCMOS</i>	185
10.4.4	<i>Packing Information for UCMOS</i>	186
10.4.5	<i>Extension of UCMOS with Microscope or Telescope Adapter</i>	187
10.5	SPCMOS Series USB2.0 CMOS Eyepiece Camera with Reduction Lens	188
10.5.1	<i>SPCMOS Basic Characteristic</i>	188
10.5.2	<i>SPCMOS Datasheet(5)</i>	189
10.5.3	<i>Dimension of SPCMOS</i>	190
10.5.4	<i>Packing Information for SPCMOS</i>	191
10.6	SCMOS Series USB2.0 CMOS Eyepiece Camera	192
10.6.1	<i>SCMOS Characteristic</i>	192
10.6.2	<i>SCMOS Datasheet (9)</i>	193

10.6.3	<i>Dimension of SCMOS</i>	195
10.6.4	<i>Packing Information for SCMOS</i>	196
11	Microscope WiFi CMOS Camera	197
11.1	WCAM Series C-mount WiFi CMOS Camera.....	197
11.1.1	<i>WCAM Basic Characteristic</i>	197
11.1.2	<i>WCAM Datasheet (4)</i>	198
11.1.3	<i>Dimension of WCAM</i>	199
11.1.4	<i>Packing Information of WCAM</i>	200
11.1.5	<i>Extension of WCAM with Microscope or Telescope Adapter</i>	201
12	Microscope WiFi+USB CMOS Camera	202
12.1	WUCAM Series C-mount WiFi+USB CMOS Camera.....	202
12.1.1	<i>WUCAM's Basic Characteristic</i>	202
12.1.2	<i>WUCAM Datasheet (1)</i>	203
12.1.3	<i>Dimension of WUCAM</i>	204
12.1.4	<i>Packing Information of WUCAM</i>	205
12.1.5	<i>Extension of WUCAM with Microscope or Telescope Adapter</i>	206
13	Industrial USB2.0 CMOS Camera	207
13.1	ICMOS Series C-mount USB2.0 CMOS Camera.....	207
13.1.1	<i>ICMOS Basic Characteristic</i>	207
13.1.2	<i>ICMOS Datasheet(4)</i>	208
13.1.3	<i>Dimension of ICMOS</i>	209
13.1.4	<i>Packing Information for ICMOS Camera</i>	210
13.1.5	<i>Extension of ICMOS with Microscope or Telescope Adapter</i>	211
14	ZOPE Series Continuous Zoom Digital Microscope	212
14.1	Basic Characteristic of ZOPE	212
14.2	ZOPE Series Digital Microscope Module List	213
14.3	Zoom Lens for ZOPE Series Digital Microscope	214
14.4	Camera Modules for ZOPE Series Digital Microscope	215
14.5	Dimension of ZOPE	216
14.6	Packing Information for ZOPE Series Digital Microscope	217
15	TSCOPE Series Portable Microscope	218
15.1	TSCOPE Portable USB Microscope.....	218
15.1.1	<i>PUM's Basic Characteristics</i>	218
15.1.2	<i>PUM's Hardware Specification</i>	220
15.1.3	<i>Accessory for PUM</i>	220
16	HCAM Series Potable USB2.0 Microscope	221
16.1	HCAM's Basic Characteristic	221
16.2	Specification of HCAM Series Portable USB Microscope	223
16.2.1	<i>HCAM KPA Series</i>	223
16.2.2	<i>HCAM KPB Series</i>	223
16.2.3	<i>Accessory for HCAM Series Portable USB Microscope</i>	224
17	Stands for the Potable Microscope	225
17.1	M-SD-HM1 Potable Microscope Stand	225
17.2	M-SD-HM2 Potable Microscope Stand	226
17.3	M-SD-HM3 Potable Microscope Stand	227
17.4	M-SD-HM4 Potable Microscope Stand	228
17.5	M-SD-HM5 Potable Microscope Stand	229
18	HINOTEK HDMI Display for XCAM Series Camera.....	230
18.1	TPHD1080PA HDMI Displayer.....	230
18.1.1	<i>TPHD1080PA's basic characteristic</i>	230

18.1.2	<i>TPHD1080PA Datasheet</i>	230
18.1.3	<i>TPHD1080PA and XCAM0720PHB/PHC Camera</i>	232
18.1.4	<i>TPHD1080PA and XCAM1080PHA,XCAM1080PHB/PHD Camera</i>	236
18.1.5	<i>Dimension of TPHD1080PA</i>	240
19	Eyepiece Tube to C-Mount Adapter	241
19.1	23.2mm Eyepiece to C-mount Adjustable Microscope Eyepiece Adapter	241
19.2	23.2mm Eyepiece to C-mount Fixed Microscope Eyepiece Adapter	242
19.3	31.75mm Eyepiece to C-mount Adjustable Telescope Eyepiece Adapter	243
19.4	31.75mm Eyepiece to C-mount Fixed Telescope Eyepiece Adapter	244
20	Olympus,Leica,Nikon, Zeiss Phototube to C-Mount Adapter	245
20.1	Olympus TV Adapter.....	245
20.1.1	<i>Characteristic</i>	245
20.1.2	<i>Specifications</i>	245
20.2	Zeiss TV Adapter	247
20.2.1	<i>P95 Series Zeiss Characteristic</i>	247
20.2.2	<i>Specifications for the P95 series adapter</i>	247
20.2.3	<i>60N-C, 60N-T2 Series TV Adapter Characteristic for Zeiss Microscope</i>	249
20.2.4	<i>Specifications for the 60N-C or 60N-T2 series adapter</i>	249
20.3	LEICA TV Adapter.....	251
20.3.1	<i>Characteristic</i>	251
20.3.2	<i>Specifications</i>	251
20.4	NIKON TV Adapter	252
20.4.1	<i>Characteristic</i>	252
20.4.2	<i>Specification</i>	252
20.5	HUVITZ TV Adapter.....	254
20.5.1	<i>Characteristic</i>	254
20.5.2	<i>Specifications</i>	254
20.6	Labomed TV Adapter.....	256
20.6.1	<i>Characteristic</i>	256
20.6.2	<i>Specifications</i>	256
21	Microscope 23.2 to 30, 30.5, 30.75 Eyepiece Converter	258
21.1	The Basic Characteristic of the Eyepiece Converter	258
21.2	Specification of the Eyepiece Converter.....	258
22	Lens for Machine Vision	259
22.1	TP-1632ZL5M (16mm~32mm, 1" Format).....	259
22.1.1	<i>Specification</i>	259
22.1.2	<i>Drawing and Optical Performance</i>	259
22.2	TPWA Series Lens with CS-mount.....	261
22.3	TP3MP Series Lens with CS-mount.....	262
22.4	TP2MP Series Lens with CS-mount.....	263
22.5	TP1MP Series Lens with CS-mount.....	264
22.6	FA-A Series Machine Vision Lens (1/1.9" 6M Resolution)	265
22.6.1	<i>Characteristic</i>	265
22.6.2	<i>Specifications (7)</i>	265
22.6.3	<i>Lens Layout</i>	265
22.7	FA-B Series Machine Vision lens (2/3" 6M Resolution)	266
22.7.1	<i>Lens Characteristic</i>	266
22.7.2	<i>Specifications (6)</i>	266
22.7.3	<i>Lens Layout</i>	266
22.8	FA-C Series Machine Vision Lens(1" 10M Resolution)	267
22.8.1	<i>Lens Characteristic</i>	267
22.8.2	<i>Specifications(5)</i>	267
22.8.3	<i>Lens Layout</i>	267
22.9	FA-D and FA-E Series Telecentric Lens	268

Product Catalog

22.9.1	<i>Lens Characteristic</i>	268
22.9.2	<i>Specifications (18)</i>	268
22.9.3	<i>Lens Layout</i>	269
23	LHCCD Series Linear CCD Camera	270
23.1	Basic Characteristic.....	270
23.2	Datasheet	270
24	ToupVi for Cameras	271
24.1	User-friendly UI design	271
24.2	Professional Camera Control Panel	271
24.3	Practical functions with good results.....	271
24.4	Powerful compatibility	273
24.5	Hardware Requirement	273

2.4 Product Nomenclature

	UHCCD	05100K	P	A	-U	-ET	-S	-C	-SQ	-NA
	1	2	3	4	5	6	7	8	9	10
1	Series Name: SCCCD, U3CCD, U3CMOS, EXCCD, UHCCD , UCMOS or SCOMS, HCAM, XCAM, L3CMOS, LCMOS, WCAM, E3CMOS, GCMOS, MG3CMOS , MTR3CCD									
2	Pixel Number: eg. 05100K : 5.1 Mega pixels									
3	Color Mode, M: Monochromatic; P : Polychromatic									
4	Sensor Distinguishing Code, such as A , B, C or D...									
5	Data Output Interface Model, U : USB; D: DVI; V: VGA; A: Analog									
6	Trigger Type, ET : External Trigger; NA: Not Available									
7	Cooled Type, S : Semiconductor Cooled; F: Fan Cooled; N: Natural Cooled									
8	Optical-Mechanical Interface Type, C : C-mount; M: Microscope; T: Telescope; S: Sporting Scope									
9	Mechanical Shape , CY: Cylinder; SQ : Square; CP: Compact									
10	TV System (Analog Cameras Only), PA: PAL; NT: NTSC; NA : Not Available									

2.5 Comparison of Camera


Model	Interface	Characteristic
MTR3CCD	USB3.0	<ul style="list-style-type: none"> Temperature-regulated USB3.0 CCD camera with Sony Super HAD/ExView CCD sensor. Controllable fan is used to achieve high performance heat radiation. Up to 50 degrees temperature drop ensures high quality video or image with lower noise;
SCCCD	USB2.0	<ul style="list-style-type: none"> TE-Cooling USB2.0 CCD camera with Sony Super HAD/ExView CCD sensor. Heat pipe is used to achieve high performance heat radiation to eliminate the vibration. Up to 20 degrees temperature drop ensures high quality video or image with lower noise;
U3CCD	USB3.0	<ul style="list-style-type: none"> USB3.0 CCD camera with Sony Super HAD/ExView CCD sensor. USB3.0 ensures high speed data transfer rate.
EXCCD	USB2.0	<ul style="list-style-type: none"> High Speed CCD camera with Sony ExView HAD CCD sensor. It could be used for dark field applications due to its high sensitivity, such as fluorescence applications;
UHCCD	USB2.0	<ul style="list-style-type: none"> High Speed CCD camera with Sony Super HAD CCD sensor;
MG3CMOS	USB3.0	<ul style="list-style-type: none"> With Sony Exmor, Exmor R and Exmor RS CMOS sensor as the image-picking device and USB3.0 is used as the data transfer interface. High quality fan is used to dissipate the sensor heat and increase the image signal to noise ratio. This technique could lower the sensor noise and upgrade the CMOS sensor to the CCD sensor image quality
E3CMOS	USB3.0	<ul style="list-style-type: none"> Super speed USB3.0 camera with Sony Exmor or Exmor R CMOS Sensor The most cost-effective USB3.0 imaging solution;
L3CMOS	USB3.0	<ul style="list-style-type: none"> Super speed USB3.0 camera with on-board memory for Aptina and Sony CMOS Sensor; High performance cooling structure ensures low image noise;
U3CMOS	USB3.0	<ul style="list-style-type: none"> Super speed USB3.0 camera with Aptina CMOS Sensor The most cost-effective USB3.0 imaging solution;
S3CMOS	USb3.0	<ul style="list-style-type: none"> Compact microscope eyepiece camera with 23.2 diameter and Aptina CMOS sensor and USB3.0 interface;
LCMOS	USB2.0	<ul style="list-style-type: none"> High speed USB2.0 camera with on-board memory for Aptina and Sony CMOS Sensor; On-board memory helps the camera to achieve the bandwidth limitation of USB2.0 and make the camera work stable for different computers with different configuration. High performance cooling structure ensures low image noise;
UCMOS	USB2.0	<ul style="list-style-type: none"> High speed USB2.0 camera with Aptina CMOS sensor; The most cost-effective USB2.0 imaging solution;
SCMOS	USB2.0	<ul style="list-style-type: none"> Microscope economic eyepiece camera with 23.2mm diameter. Aptina sensor is used as the image pickup device;
SPCMOS	USB2.0	<ul style="list-style-type: none"> Microscope economic eyepiece camera with embedded reduction lens to enlarge the FOV. The 23.2mm diameter ensures it can be directly insert into the eyepiece tube
XCAM	HDMI/VGA	<ul style="list-style-type: none"> HDMI & VGA output camera; DSP inside ensuring high image quality and versatile functions; Including automatic white balance and exposure on/off (AEWB), saving images to SD card (SAVE), video stream and freeze on/off (FREEZE), multiple groups of cross lines and remote image snapshot controller to reduce the vibration blur (REMOTE);
WCAM	WiFi	<ul style="list-style-type: none"> WiFi cameras. H.264 or MJPEG compression ensures high quality video; WiFi-enabled devices could be used to receive the video, such as smartphones, computers, and tablets with iOS, Android, and Windows operating systems; Multiple users could have access to one camera simultaneously(up to 10); Born with our imaging software for quantifying, measuring, and annotating images which is downloadable from app store viewing, capturing, and editing images(Windows OS Only);
WUCAM	WiFi+USB	<ul style="list-style-type: none"> Multiple data output method(USB+WiFi) with switch on the cover;
HDMI720P	HDMI	<ul style="list-style-type: none"> HDMI camera with720P hardware resolution
XCAM	HDMI+USB; HDMI+WiFi	<ul style="list-style-type: none"> With HDMI+USB+SD card output interface. GUI is supported to make the adjustment at ease With HDMI+WiFi+SD card output interface. GUI is supported to make the adjustment

		at ease
ICMOS	USB2.0	<ul style="list-style-type: none"> ● USB2.0 industrial camera with on-board memory for perfect synchronization and stable performance; ● 8-pin Hirose HR25-7TR-8PA GPIO connector for optical coupler isolation trigger, strobe (Optional); ● Compact industrial standard size (29x29x29 mm)for easy integration;
HCAM	USB2.0	<ul style="list-style-type: none"> ● Handheld USB2.0 microscope with 10X to 1300X magnification;

3 Camera & Microscope Configuration


3.1 Trinocular Digital Microscope (1/2)

Attach the C-mount camera and Adapter to the straight photo tube




3.2 Trinocular Digital Microscope (2/2)

Attach the C-Mount camera and adapter to the 3rd ocular tube or the other 2 eyepiece tubes




3.3 Binocular Digital Microscope


STEP 1: Remove the eyepiece from the ocular tube or the eyepiece tube




STEP 2: Attach (Screw) the camera Adapter to the C-mount camera



STEP 3: Attach (Insert) the eyepiece camera into the ocular tube or eyepiece tube



3.4 Size Description of the Connection Parts



- ① Standard C-Mount: Dia.1 inch (25.4mm) female thread
- ② Standard C-Mount: Dia.1 inch (25.4mm) male thread
- ③ Camera Adapter connector: size varies between microscope brands
- ④ Straight photo tube: size varies between microscope brands
- ⑤ Relay lens: standard eyepiece connector size, Dia.23.2mm (male)
- ⑥ 3rd ocular tube: standard eyepiece connector size, Dia.23.2mm (female)
- ⑦ Ocular tube: standard eyepiece connector size, Dia.23.2mm (female)

4 Microscope Auto Focus HDMI CMOS Camera

4.1 XFCAM1080PHB/PHD Auto Focus HDMI's Characteristic

XFCAM1080PHB/PHD is a multiple interfaces (HDMI+WiFi+SD card, so **X** here means multiple interfaces) CMOS camera with autofocus function (**F** means autofocus) and it adopts ultra-high performance Sony CMOS sensor as the image-picking device. HDMI+WiFi are used as the data transfer interface to HDMI display or computer.

For HDMI output, The XCamView will be loaded and a camera control panel and toolbar are overlaid on the HDMI screen, in this case, the USB mouse can be used to set the camera, browse and compare the captured image, play the video etc.

For WiFi output, unplug the mouse and plug in the USB WiFi adapter, connect the computer WiFi to the camera, then the video stream can be transferred to computer with the advanced software ToupVi. With ToupVi, you can control the camera, process the image as other USB series camera.

In HDMI and WiFi outputs, the camera embedded Auto/Manual focus function can obtain the clear image at ease. No hand rotation of the microscope Coarse/Fine knob is needed.



The XFCAM1080PHD's basic characteristic is as follows:

- All in 1(HDMI+WiFi) C-mount camera with Sony high sensitivity CMOS sensor;
- 1920 × 1080 (1080P) video resolution;
- Record 1080P video(ASF format) into SD card;
- 5~2M resolution captured image(XFCAM1080PHB/PHD);
- HDMI/WiFi output simultaneously;
- **Auto/Manual focus with the movement of the sensor;**
- For HDMI output, XCamView is used to control the camera;
- For WiFi output, ToupVi/ToupLite is used to control the camera;
- Ultra-Fine Color Engine with perfect color reproduction capability(WiFi);
- With advanced video & image processing application ToupVi/ToupLite;
- Windows/Linux/macOS/Android multi-platform SDK;
- CNC Camera housing;

The possible applications of **XFCAM1080PHB/PHD** are as follows:

- Scientific research, education (teaching, demonstration and academic exchanges);
- Digital laboratory, medical research;
- Industrial visual (PCB examination, IC quality control);
- Medical treatment (pathological observation);
- Food (microbial colony observation and counting);
- Aerospace, military (high sophisticated weapons);

4.2 XFCAM1080PHB/PHD Datasheet(2)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Sensitivity Dark Signal	FPS/Resolution	Binning	Exposure
XFCAM1080PHB XF1080B	1080P/5M/Sony IMX178(C) 1/1.8"(6.22x4.67)	2.4x2.4	425mv with 1/30s 0.15mv with 1/30s	30@1920*1080(HDMI) 25@1920*1080(WiFi)	1x1	0.03ms~918ms
XFCAM1080PHD XF1080D	1080P/2M/Sony IMX185(C) 1/1.9"(7.20x4.05)	3.75x3.75	1120mv with 1/30s 0.15mv with 1/30s	60@1920*1080(HDMI) 25@1920*1080(WiFi)	1x1	0.06ms~918ms

C: Color; M: Monochrome;

Interface & Button Functions

	USB	USB Mouse/USB WiFi Adapter
	HDMI	HDMI Output
	DC12V	12V/1A Power in
	SD	SD Card Slot
	LED	Power Indicator Power
	ON/OFF	On/off Switch

Other Specification for HDMI Output

UI Operation	With USB Mouse to operate on the embedded XCamView
Image Capture	JPEG Format with 5M or 2M Resolution in SD Card (XFCAM1080PHB/PHD)
Video Record	ASF Format 1080P 30fps in SD Card(8G)
Camera Control Panel	Including Exposure, Gain, White Balance, Color Adjustment, Sharpness and Denoising Control
Auto-focus Control Panel	Including Auto-focus, Manual Focus, One Push AF and Conjugate Correction Functions
Toolbar	Including Zoom, Mirror, Comparison, Freeze, Cross, WDR, Auto-focus, Browser Function, Setting, Multi-language and XCamView Version Information

Other Specification for WiFi Output

UI Operation	TouVi or TouPLite on Windows/Linux/OSX/Android Platform
WiFi Performance	802.11n 150Mbps; RF Power 20dBm(Maximum)
Maximum Connected Devices	3~6(According to the Environment and Connection Distance)
White Balance	Auto White Balance
Color Technique	Ultra-FineTM Color Engine (WiFi)
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)(WiFi)
Recording System	Still Picture or Movie (WiFi)
Software Environment (for USB2.0 Connection)	
Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 8.1/10(32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory:4GB or More
	USB Port:USB2.0 High-speed Port(As Power Only, not as the USB Data Transfer)
	Display:19" or Larger
	CD-ROM

Operating Environment

Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 12V/1A Adapter

4.3 XFCAM1080PHB/PHD and Microscope



XFCAM1080PHB/PHD and Its Back Panel




Different Views of XFCAM1080PHB/PHD



XFCAM1080PHB/PHD and Microscope

4.4 Dimension of XFCAM1080PHB/PHD



Dimension of XFCAM1080PHB/PHD

4.5 Packing Information for XFCAM1080PHB/PHD



Figure 4-1 Packing Information of XFCAM1080PHB/PHD

Standard Packing List

A	Gift box : L:25.5cm W:17.0cm H:9.0cm (1pcs, 1.43Kg/ box)
B	XFCAM1080PHB/PHD Power Adapter: Input: AC 100~240V 50Hz/60Hz, Output: DC 12V 1A American standard: Model: GS12U12-P1I 12W/12V/1A; UL/CUL/BSMI/CB/FCC EMI Standard:EN55022,EN61204-3, EN61000-3-2,-3, FCC Part 152 class B, BSMI CNS14338
C	EMS Standard:EN61000-4-2,3,4,5,6,8,11,EN61204-3,Class A Light Industry Standard European standard:Model:GS12E12-PII 12W/12V/1A; TUV(GS)/CB/CE/ROHS EMI Standard:EN55022,EN61204-3, EN61000-3-2,-3, FCC Part 152 class B, BSMI CNS14338 EMS Standard:EN61000-4-2,3,4,5,6,8,11,EN61204-3,Class A Light Industry Standard
D	HDMI Cable
E	USB Mouse
F	Wireless network adapter with USB interface
G	CD (Driver & utilities software, Ø12cm)

Optional Accessory

H	Adjustable lens adapter	C-Mount to Dia.23.2mm Eyepiece Tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075
		C-Mount to Dia.31.75mm Eyepiece Tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075
I	Fixed lens Adapter	C-Mount to Dia.23.2mm Eyepiece Tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075
		C-Mount to Dia.31.75mm Eyepiece Tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075
Note: For H and I optional items, please specify your camera type(C mount, microscope camera or telescope camera), T engineer will help you to determine the right microscope or telescope camera adapter for your application;			
J	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube		
K	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube		
L	Calibration kit	106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)	
M	SD Card(4G or 8G)		

4.6 Extension of XFCAM1080PHB/PHD with Microscope or Telescope Adapter

Extension	Picture	
C-mount Camera		Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;
Microscope Camera	 	XFCAM1080PHD+AMAXXX(23.2mm Adapter) XFCAM1080PHD+FMAXXX(23.2mm Adapter)
Telescope Camera:	 	XFCAM1080PHD+ATAXXX(31.75mm Adapter) XFCAM1080PHD+FTAXXX(31.75mm Adapter)

5 Microscope HDMI CMOS Camera

5.1 XCAM4K Series HDMI/GE/WiFi Multi-outputs C-mount CMOS Camera (2)

5.1.1 XCAM4K Series' Basic Characteristic

The **XCAM4K** series is the next-generation live-view imaging-system with 4K resolution at 60/30 FPS.

XCAM4K series comes with Sony Exmor CMOS sensor with high sensitivity, low dark current and no smear achieved through the adoption of R, G and B primary color mosaic filters.

The camera uses a standard C-mount interface for maximum compatibility with various microscopy-systems. It can be used as a stand-alone recorder when used with an HDMI monitor or television, or live-streamed to a PC via Gigabit Ethernet (GE) for image-capture and video-recording.

Hardware 3D denoising, sharpness and local tone mapping control functions greatly improve the image and video quality.

The included Windows software offers image-development and measurement tools, as well as advanced compositing features such as image-stitching and extended-depth-of-focus. With the ability to calibrate scales at multiple magnifications, the software can be used for multi-level inspection. For Mac and Linux, there is a lite version of the software which can capture video and still images, and includes limited processing features.

The XCAM4K8MPA camera is intended to be used for the acquisition of digital images from the stereo microscope, biological microscope or online interactive teaching. The basic characteristics are listed as below:

- Sony Exmor CMOS sensor
- 4K HDMI/GE/WLAN multiple video outputs
- 4K/1080P auto switching according to the display resolution
- SD card/USB flash disk for the captured image and video storage
- Embedded XCAMView for the control of the camera
- With strong ISP and other related processing functions
- TouVi/TouPLite software for PC
- iOS/Android applications for smart phones or tablets



5.1.2 XCAM4K Series' Datasheet(2)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Sensitivity Dark Signal	FPS/Resolution	Binning	Exposure
XCAM4K8MPA XP4K8MA	4K/Sony IMX334(C) 1/1.8"(7.68x4.32)	2.0x2.0	505mv with 1/30s 0.13mv with 1/30s	60@3840*2160(HDMI) 60@1920*1080(HDMI) 30@3840*2160(WiFi, GE)	1x1	0.04ms~1000ms
XCAM4K16MPA XP4K16MA	Sony IMX183(C) 1/1.06"(13.06x7.27)	2.4x2.4	461mv with 1/30s 0.21mv with 1/30s	30@3840*2160(HDMI) 30@1920*1080(HDMI) 30@3840*2160(WiFi, GE)	1x1	0.04ms~2000ms

C: Color; M: Monochrome;

Interface & Button Functions



USB Mouse	Connect USB mouse for easy operation of the embedded XCamView software
USB3.0	Connecting USB flash disk for image or video storage; Connecting 5G WLAN adapter as WLAN camera in AP or STA mode;
HDMI	Comply with HDMI2.0 standard. 4K/1080P format video output and supporting auto switching between 4K and 1080P format according to the connected display resolution
GE	Gigabit Ethernet port to connect to the peripheral for the video streaming
SD	Comply with SDIO3.0 standard and SD card could be inserted for the images or videos storage
DC12V	Power adapter connection (12V)
ON/OFF	Power switch
LED	Camera status indicator

Other Specification for HDMI Output

UI Operation	With USB Mouse
Image Capture	8M (3840*2160) JPEG Image in SD Card or USB Flash Disk(XCAM4K8MPA) 16M (5440*3060) JPEG Image in SD Card or USB Flash Disk(XCAM4K16MPA)
Video Record	Video Format: 8M(3840*2160) H264 Encoded MP4 Format(XCAM4K8MPA, XCAM4K16MPA) Video Recording Frame Rate: 50~60FPS(XCAM4K8MA), 26~30FPS(XCAM4K16MPA) (related with the SD card speed class and video resolution)
Camera Control Panel	Including Exposure, Gain, White Balance, Color Adjustment, Sharpness and Denoising Control
Toolbar	Including Zoom, Mirror, Comparison(Video~image, image~image), Freeze, Cross, Browser Function

Other Specification for GE Output

White Balance	Auto/Manual/ROI White Balance
Color Technique	Ultra-Fine™ Color Engine
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture or Video


Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 8.1 / 10(32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher Memory: 4GB or More Ethernet Port: RJ45 Ethernet Port Display: 19" or Larger CD-ROM

Operating Environment

Operating Temperature (in Centidegree)	-10°~ 50°
Storage Temperature (in Centidegree)	-20°~ 60°
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 12V/1A Adapter

5.1.3 Dimension of XCAM4K Series



Dimension of XCAM4K Series

5.1.4 Packing Information of XCAM4K Series



Packing Information of XCAM4K Series

Standard Packing List

A	Gift box : L:25.5cm W:17.0cm H:9.0cm (1pcs, 1.43Kg/ box)
B	XCAM4K Series Camera
C	Power Adapter: Input: AC 100~240V 50Hz/60Hz, Output: DC 12V 1A American standard: Model: GS12U12-P1I 12W/12V/1A: UL/CUL/BSMI/CB/FCC EMI Standard: EN55022, EN61204-3, EN61000-3-2,-3, FCC Part 152 class B, BSMI CNS14338 EMS Standard: EN61000-4-2,3,4,5,6,8,11, EN61204-3, Class A Light Industry Standard European standard: Model:GS12E12-P1I 12W/12V/1A; TUV(GS)/CB/CE/ROHS EMI Standard: EN55022, EN61204-3, EN61000-3-2,-3, FCC Part 152 class B, BSMI CNS14338 EMS Standard: EN61000-4-2,3,4,5,6,8,11, EN61204-3, Class A Light Industry Standard
D	USB Mouse
E	HDMI 2.0 Cable(Support 3840x2160, 60FPS)
F	High-speed USB3.0 A male to A male gold-plated connectors cable /2.0m
G	CD (Driver & utilities software, Ø12cm)

Optional Accessory

H	SD Card (16G or above; Speed: Class 10)	
I	USB WLAN adapter	
J	Ethernet cable	
K	C-Mount to Dia.23.2mm Eyepiece Tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075
	C-Mount to Dia.31.75mm Eyepiece Tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075
L	C-Mount to Dia.23.2mm Eyepiece Tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075
	C-Mount to Dia.31.75mm Eyepiece Tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075
Note: For K and L optional items, please specify your camera type (C mount, microscope camera or telescope camera), Our engineer will help you to determine the right microscope or telescope camera adapter for your application;		
M	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube	
N	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube	
O	Calibration kit	106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)

5.1.5 Extension of XCAM4K Series with Microscope or Telescope Adapter


Extension	Picture	
C-mount Camera		Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;
Microscope Camera	 4K HDMI+AMAXXX(23.2mm Adapter)	 4K HDMI+FMAXXX(23.2mm Adapter)
Telescope Camera	 4K HDMI+ATAXXX(31.75mm Adapter)	 4K HDMI+FTAXXX(31.75mm Adapter)

5.1.6 Application of XCAM4K Series Camera


- Scientific research, digital teaching (teaching, demonstration and academic discussing);
- Digital laboratory, medical research;
- Machine vision (PCB detection, IC quality control);
- Medical treatment (pathological observation);
- Food (microbial colony observation and counting);
- Aviation and military;




5.1.7 Images Captured by XCAM4K8MPA




Rabbit Embryo




Ovary




Cotton Stem



Taste Bad



MK54-40



Corn Leaf

5.1.8 XCAM4K Camera and Microscope



Figure 5-1 XCAM4K Camera and Leica Microscope



Figure 5-2 XCAM4K Camera and Zeiss Microscope

5.2 XCAM1080PHA C-mount HDMI+USB Output CMOS Camera(1)



5.2.1 XCAM1080PHA's Basic Characteristic

XCAM1080PHA is a multiple interfaces (HDMI+USB2.0+SD card, so X here means multiple interfaces) CMOS camera and it adopts ultra-high performance Sony IMX236 CMOS sensor as the image-picking device. HDMI+USB2.0 are used as the data transfer interface to HDMI display or computer.

For HDMI output, The XCamView will be loaded and a camera control panel and toolbar are overlaid on the HDMI screen, in this case, the USB mouse can be used to set the camera, browse and compare the captured image, play the video etc.

For USB2.0 output, unplug the mouse and plug in the USB2.0 cable to the camera and computer, then the video stream can be transferred to computer with the advanced software ToupVi. With ToupVi, you can control the camera, process the image as other USB series camera.

The XCAM1080PHA's basic characteristic is as follows:

- All in 1(HDMI+USB+SD card) C-mount camera with Sony high sensitivity CMOS sensor;
- Simultaneous HDMI & USB output;
- CNC precision machining shell;
- Built-in mouse control;
- Built-in image capture & video record to SD card;
- Built-in camera control panel, including exposure(manual/auto)/gain, white balance(lockable), color adjustment, sharpness and denoising control;
- Built-in toolbar including zoom, mirror, comparison, freeze, cross, browser functions;
- Built-in image & video browsing, display & play;
- Ultra-Fine color engine with perfect color reproduction capability(USB);
- With advanced video & image processing application ToupVi , which including professional image processing such as 2D measurement, HDR, image stitching, EDF(Extended Depth of Focus), image segmentation & count, image stacking, color composite and denoising(USB);
- Support standard UVC for Windows/Linux/Mac(USB);

The possible applications of XCAM1080PHA are as follows:

- Scientific research, education (teaching, demonstration and academic exchanges);
- Digital laboratory, medical research;
- Industrial visual (PCB examination, IC quality control);
- Medical treatment (pathological observation);
- Food (microbial colony observation and counting);
- Aerospace, military (high sophisticated weapons);

5.2.2 XCAM1080PHA Datasheet(1)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Sensitivity Dark Signal	FPS/Resolution	Binning	Exposure
XCAM1080PHA XP1080A	1080P/Sony IMX236 1/2.8"(5.38x3.02)	2.8x2.8	510 mv with 1/30s 0.15 mv with 1/30s	30@1920*1080P(HDMI) 30@1920*1080(USB)	1x1	0.1ms~999ms

C: Color; M: Monochrome;

Interface & Button Functions



USB	USB Camera or USB Mouse
HDMI	HDMI Output
DC12V	12V Power in
SD	SD Card Slot
ON/OFF	Power On/off Switch

Other Specification for HDMI Output

UI Operation	With USB Mouse
Image Capture	High Speed in SD Card(8G)
Video Record	1080P 30fps in SD Card(8G)
Camera Control Panel	Including Exposure, Gain, White Balance, Color Adjustment, Sharpness and Denoising Control
Toolbar	Including Zoom, Mirror, Comparison, Freeze, Cross, Browser Function

Other Specification for USB Output

White Balance	Auto White Balance
Color Technique	Ultra-Fine™ Color Engine (USB)
Capture/Control SDK	Standard UVC for Windows/Linux/macOS(USB)
Recording System	Still Picture or Movie (USB)

Software Environment (for USB2.0 Connection)

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 8.1 /10(32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher Memory:4GB or More USB Port:USB2.0 High-speed Port Display:19" or Larger CD-ROM

Operating Environment

Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 12V/1A Adapter

5.2.3 XCAM1080PHA and Microscope



XCAM1080PHA and Its Back Panel



Different Views of XCAM1080PHA



XCAM1080PHA and Microscope




XCAM1080PHA+ Microscope+Display



XCamView UI for Mouse Control

5.2.4 Dimension of XCAM1080PHA



Dimension of XCAM1080PHA

5.2.5 Packing Information for XCAM1080PHA



Packing Information of XCAM1080PHA

Standard Packing List

A	Gift box : L:25.5cm W:17.0cm H:19.0cm (1pcs, 1.55kg/ box)
B	XCAM1080PHA camera Power Adapter: Input: AC 100~240V 50Hz/60Hz, Output: DC 12V 1A American standard: Model: GS12U12-P11 12W/12V/1A: UL/CUL/BSMI/CB/FCC EMI Standard: EN55022,EN61204-3, EN61000-3-2,-3, FCC Part 152 class B, BSMI CNS14338
C	EMS Standard:EN61000-4-2,3,4,5,6,8,11,EN61204-3,Class A Light Industry Standard European standard: Model:GS12E12-P11 12W/12V/1A; TUV(GS)/CB/CE/ROHS EMI Standard:EN55022,EN61204-3, EN61000-3-2,-3, FCC Part 152 class B, BSMI CNS14338 EMS Standard:EN61000-4-2,3,4,5,6,8,11,EN61204-3,Class A Light Industry Standard
D	HDMI Cable
E	USB Mouse
F	High-speed USB2.0 A male to A male gold-plated connectors cable /2.0m
G	CD (Driver & utilities software, Ø12cm)

Optional Accessory

H	Adjustable lens adapter	C-Mount to Dia.23.2mm Eyepiece Tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075
		C-Mount to Dia.31.75mm Eyepiece Tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075
I	Fixed lens Adapter	C-Mount to Dia.23.2mm Eyepiece Tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075
		C-Mount to Dia.31.75mm Eyepiece Tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075
Note: For H and I optional items, please specify your camera type(C mount, microscope camera or telescope camera), Our engineer will help you to determine the right microscope or telescope camera adapter for your application;			
J	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube		
K	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube		
L	Calibration kit	106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)	
M	SD Card(4G or 8G)		

5.2.6 Extension of XCAM1080PHA with Microscope or Telescope Adapter

Extension	Picture	
C-mount Camera		Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;
Microscope Camera	 XCAM1080PHA+AMAXXX(23.2mm Adapter)	 XCAM1080PHA+FMAXXX(23.2mm Adapter)
Telescope Camera:	 XCAM1080PHA+ATAXXX(31.75mm Adapter)	 XCAM1080PHA+FTAXXX(31.75mm Adapter)

5.3 XCAM1080PHB/PHD/PHE C-mount HDMI+WiFi Output CMOS Camera

5.3.1 XCAM1080PHB/PHD/PHE's Basic Characteristic

XCAM1080PHB/PHD/PHE is a multiple interfaces (HDMI+WiFi+SD card, X here means multiple interfaces) CMOS camera and it adopts ultra-high performance Sony CMOS sensor as the image-picking device. HDMI+WiFi are used as the data transfer interface to HDMI display or computer.

For HDMI output, The XCamView will be loaded and a camera control panel and toolbar are overlaid on the HDMI screen, in this case, the USB mouse can be used to set the camera, browse and compare the captured image, play the video etc.

For WiFi output, unplug the mouse and plug in the USB WiFi adapter, connect the computer WiFi to the camera, then the video stream can be transferred to computer with the advanced software ToupVi. With ToupVi, you can control the camera, process the image as our other USB series camera.



The XCAM1080PHB/PHD/PHE's basic characteristic is as follows:

- All in 1(HDMI+WiFi) C-mount camera with Sony high sensitivity CMOS sensor;
- For HDMI application, with built-in multiple-language XCamView software. The camera characteristic can be controlled by XCamView through the USB mouse. The other basic processing and choosing can also be realized by the XCamView;
- 1920 × 1080 (1080P) resolutions to match the current high-definition display on the market; Support plug and play application;
- For HDMI application, 5.04M resolution image(2592*1944 **XCAM1080PHB**) or 2.0M resolution image(1920*1080 **XCAM1080PHD/PHE(Global Shutter for PHE)**) can be captured and saved for browsing; For video, 1080P video stream(asf format) can be captured and saved;
- With the USB WiFi adapter, the **XCAM1080PHB/PHD/PHE** can be used as WiFi camera, the ToupVi/ToupLite advanced image processing software is used to display the video and capture image. support plug and play application;
- Ultra-Fine Color Engine with perfect color reproduction capability(WiFi);
- With advanced video & image processing application ToupVi , which including professional image processing such as 2D measurement, HDR, image stitching, EDF(Extended Depth of Focus), image segmentation & count, image stacking, color composite and denoising(USB);
- **XCAM1080PHB/PHD/PHE** can meet various applications and can be widely used in industrial inspection, education and research, materials analysis, precision measurement, medical analyses etc.

The possible applications of **XCAM1080PHB/PHD/PHE** are as follows:

- Scientific research, education (teaching, demonstration and academic exchanges);
- Digital laboratory, medical research;
- Industrial visual (PCB examination, IC quality control);
- Medical treatment (pathological observation);
- Food (microbial colony observation and counting);
- Aerospace;

5.3.2 XCAM1080PHB/PHD/PHE Datasheet(3)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Sensitivity Dark Signal	FPS/Resolution	Binning	Exposure
XCAM1080PHB XP1080B	1080P/5M/Sony IMX178(C) 1/1.8"(6.22x4.67)	2.4x2.4	425mv with 1/30s 0.15mv with 1/30s	30@1920*1080(HDMI) 25@1920*1080(WiFi)	1x1	0.03ms~918ms
XCAM1080PHD XP1080D	1080P/2M/Sony IMX185(C) 1/1.9"(7.20x4.05)	3.75x3.75	1120mv with 1/30s 0.15mv with 1/30s	30@1920*1080(HDMI) 25@1920*1080(WiFi)	1x1	0.06ms~918ms
XCAM1080PHE XP1080E	Sony IMX249(C, GS) 1/1.2"(11.25x6.33)	5.86*5.86	1016mv with 1/30s 0.15mv with 1/30s	30@1920*1080(HDMI) 25@1920*1080(WiFi)	1x1	0.043ms~1000ms

C: Color; M: Monochrome;

XCAM1080PHE adopt large Sony global shutter CMOS sensor which is a best replacement of traditional CCD video camera

Interface & Button Functions	
	USB
	HDMI
	DC12V
	SD
	ON/OFF
	LED

Other Specification for HDMI Output

UI Operation	With USB Mouse to Operate on the embedded XCamView
Image Capture	JPEG Format with 5M Resolution (2592*1944) in SD Card(8G) (XCAM1080PHB) JPEG Format with 2M Resolution in SD Card (XCAM1080PHD/PHE(Global Shutter for PHE))
Video Record	ASF Format 1080P 30fps in SD Card(8G)
Camera Control Panel	Including Exposure, Gain, White Balance, Color Adjustment, Sharpness and Denoising Control
Toolbar	Including Zoom, Mirror, Comparison, Freeze, Cross, Browser Function, Muti-language and XCamView Version Information

Other Specification for WiFi Output

UI Operation	ToupVi or ToupLite on Windows/Linux/OSX/Android Platform
WiFi Performance	802.11n 150Mbps; RF Power 20dBm(Maximum)
Maximum Connected Devices	3~6(According to the Environment and Connection Distance)
White Balance	Auto White Balance
Color Technique	Ultra-Fine™ Color Engine (WiFi)
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc) (WiFi)
Recording System	Still Picture or Movie (WiFi)

Software Environment (for USB2.0 Connection)

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 8.1/10(32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher Memory:4GB or More USB Port:USB2.0 High-speed Port(As Power Only, not as the USB Data Transfer) Display:19" or Larger CD-ROM

Operating Environment

Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 12V/1A Adapter

5.3.3 XCAM1080PHB/PHD/PHE and Microscope




XCAM1080PHB/PHD/PHE and Its Back Panel



Different Views of XCAM1080PHB/PHD/PHE



XCAM1080PHB/PHD/PHE and Microscope




XCAM1080PHB/PHD/PHE+ Microscope+Display



XCamView UI for Mouse Control

5.3.4 Dimension of XCAM1080PHB/PHD/PHE



Dimension of XCAM1080PHB/PHD/PHE

5.3.5 Packing Information for XCAM1080PHB/PHD/PHE



Packing information of XCAM1080PHB/PHD/PHE

Standard Packing List

A	Gift box : L:25.5cm W:17.0cm H:9.0cm (1pcs, 1.43Kg/ box)
B	XCAM1080PHB or XCAM1080PHD or XCAM1080PHE camera
C	Power Adapter: Input: AC 100~240V 50Hz/60Hz, Output: DC 12V 1A American standard: Model: GS12U12-PII 12W/12V/1A: UL/CUL/BSMI/CB/FCC EMI Standard:EN55022,EN61204-3, EN61000-3-2,-3, FCC Part 152 class B, BSMI CNS14338
D	EMS Standard:EN61000-4-2,3,4,5,6,8,11,EN61204-3,Class A Light Industry Standard European standard:Model:GS12E12-PII 12W/12V/1A; TUV(GS)/CB/CE/ROHS EMI Standard:EN55022,EN61204-3, EN61000-3-2,-3, FCC Part 152 class B, BSMI CNS14338 EMS Standard:EN61000-4-2,3,4,5,6,8,11,EN61204-3,Class A Light Industry Standard
E	HDMI Cable
F	USB Mouse
G	Wireless network adapter with USB interface
	CD (Driver & utilities software, Ø12cm)

Optional Accessory

H	Adjustable lens adapter	C-Mount to Dia.23.2mm Eyepiece Tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075
		C-Mount to Dia.31.75mm Eyepiece Tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075
I	Fixed lens Adapter	C-Mount to Dia.23.2mm Eyepiece Tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075
		C-Mount to Dia.31.75mm Eyepiece Tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075
Note: For H and I optional items, please specify your camera type(C mount, microscope camera or telescope camera), Our engineer will help you to determine the right microscope or telescope camera adapter for your application;			
J	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube		
K	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube		
L	Calibration kit	106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)	
M	SD Card(4G or 8G)		

5.3.6 Extension of XCAM1080PHB/PHD/PHE with Microscope or Telescope Adapter

Extension	Picture	
C-mount Camera		Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;
Microscope Camera	 XCAM1080PHB/PHD/PHE+AMAXXX(23.2mm Adapter)	 XCAM1080PHB/PHD/PHE+FMAXXX(23.2mm Adapter)
Telescope Camera:	 XCAM1080PHB/PHD/PHE+ATAXXX(31.75mm Adapter)	 XCAM1080PHB/PHD/PHE+FTAXXX(31.75mm Adapter)

5.4 ALPHA1080 Series HDMI+USB Outputs C-mount CMOS Camera(2)



5.4.1 ALPHA1080 Series' Basic Characteristics

ALPHA1080 series is a multiple outputs (HDMI+USB2.0+SD card) C-mount CMOS camera and it adopts ultra-high performance Sony CMOS sensor as the image-picking device. HDMI+USB2.0 are used as the data transfer interface to HDMI display or computer.

For HDMI camera mode, The **XCamView** will be loaded and the **Camera Control Panel+ Measurement Toolbar** and **Synthesis Camera Control Toolbar** are overlaid on the HDMI screen with the mouse move to the related region, in this case, the USB mouse can be used to set the camera, browse and compare the captured image, play the video and perform the measurement ital.

For **USB Video** camera mode, plug in the micro USB host cable to the camera's **USB Video** port and computer USB port, then the video stream can be transfer to computer with the advanced software **ToupVi /ToupLite**. With **ToupVi /ToupLite**, you can control the camera, process the video and image as our other **USB** series camera.

The **ALPHA1080** series' basic characteristics are as follows:

For **HDMI** output:

- All in 1(HDMI+USB+SD card) C-mount camera with Sony high sensitivity CMOS sensor;
- Simultaneous HDMI & USB output;
- Built-in mouse control;
- Built-in image capture & video record to SD card;
- Built-in camera control panel, including exposure(manual/auto)/gain, white balance(lockable), color adjustment, sharpness control;
- Built-in video and image measurement;
- Built-in toolbar including zoom, mirror, comparison, freeze, cross, browser functions;
- Built-in image & video browsing, display & play;
- Real time clock(RTC)

For **USB Video** mode:

- Ultra-Fine color engine with perfect color reproduction capability(USB);

- With advanced video & image processing application ToupVi , which including professional image processing such as 2D measurement, HDR, image stitching, EDF(Extended Depth of Focus), image segmentation & count, image stacking, color composite and denoising(USB);
- Support standard UVC protocol for Windows/Linux/Mac(USB);
- CNC precision machining shell;

The possible applications of ALPHA1080 series are as follows:

- Scientific research, education (teaching, demonstration and academic exchanges);
- Digital laboratory, medical research;
- Industrial visual (PCB examination, IC quality control, mechanical part measurement);
- Medical treatment (pathological observation);
- Food (microbial colony observation and counting);
- Aerospace, military (high sophisticated weapons);

5.4.2 ALPHA1080 Series Datasheet(2)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Sensitivity Dark Signal	FPS/Resolution	Binning	Exposure
ALPHA1080A AL1080A	1080P/Sony IMX290 1/2.8"(5.57x4.13)	2.9x2.9	1300mv with 1/30s 0.15 mv with 1/30s	26@1920*1080P(HDMI) 26@1920*1080(USB)	1x1	0.036ms~8s
ALPHA1080B AL1080B	1080P/Sony IMX185 1/1.9"(7.20x4.50)	3.75x3.75	1120mv with 1/30s 0.15 mv with 1/30s	26@1920*1080P(HDMI) 26@1920*1080(USB)	1x1	0.34ms~4s

C: Color; M: Monochrome;

Interface & Button Functions



HDMI	HDMI Output
USB Mouse	USB Mouse for the Control of the HDMI Mode
USB Video	USB Video for the PC
LED	Camera Status Indicate
SD	SD Card Slot
DC12V	12V/1A Power in
ON/OFF	Power ON/OFF Switch

Other Specification for HDMI Output

UI Operation	With USB Mouse for HDMI Mode
Image Capture	High Speed in SD Card(8G)
Video Record	1080P 26fps in SD Card(8G)(AVI Format in SD Card)
Camera Control Panel	Including Exposure, Gain, White Balance, Color Adjustment and Sharpness Control
Toolbar	Including Zoom, Mirror, Comparison, Freeze, Cross, Browser Function

Other Specification for USB Output

White Balance	Auto White Balance, Manual White Balance, ROI White Balance()
Color Technique	Ultra-Fine™ Color Engine (USB2.0)
Capture/Control SDK	Standard UVC for Windows(USB2.0)
Recording System	Still Picture or Movie (HDMI or USB)

Software Environment (for USB2.0 Connection)

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 8.1 / 10(32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory:4GB or More
	USB Port:USB2.0 High-speed Port
	Display:19" or Larger
	CD-ROM

Operating Environment

Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 12V/1A Adapter

5.4.3 ALPHA1080 Series and Microscope



ALPHA1080 Series and Its Back Panel




Different Views of ALPHA1080 Series



ALPHA1080 Series and Microscope



ALPHA1080 Series+ Microscope+Display



ALPHA1080 XCamView UI for Mouse Control

5.4.4 Dimension of ALPHA1080 Series



Dimension of ALPHA1080 Series

5.4.5 Packing Information for ALPHA1080 Series



Packing Information of ALPHA1080

Standard Packing List

A	Gift box : L:25.5cm W:17.0cm H:19.0cm (1pcs, 1.55kg/ box)
B	ALPHA1080 Series camera
C	Power Adapter: Input: AC 100~240V 50Hz/60Hz, Output: DC 12V 1A American standard: Model: GS12U12-PII 12W/12V/1A; UL/CUL/BSMI/CB/FCC EMI Standard: EN55022,EN61204-3, EN61000-3-2,-3, FCC Part 152 class B, BSMI CNS14338 EMS Standard: EN61000-4-2,3,4,5,6,8,11,EN61204-3,Class A Light Industry Standard European standard: Model:GS12E12-PII 12W/12V/1A; TUV(GS)/CB/CE/ROHS EMI Standard: EN55022,EN61204-3, EN61000-3-2,-3, FCC Part 152 class B, BSMI CNS14338 EMS Standard: EN61000-4-2,3,4,5,6,8,11,EN61204-3,Class A Light Industry Standard
D	HDMI Cable
E	USB Mouse
F	Micro USB2.0 cable /2.0m
G	CD (Driver & utilities software, Ø12cm)



Optional Accessory



H	Adjustable lens adapter	C-Mount to Dia.23.2mm Eyepiece Tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075
		C-Mount to Dia.31.75mm Eyepiece Tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075
I	Fixed lens Adapter	C-Mount to Dia.23.2mm Eyepiece Tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075
		C-Mount to Dia.31.75mm Eyepiece Tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075
J	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube		
K	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube		
L	Calibration kit	106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)	
M	SD Card(4G,8G,16G)		



5.4.6 Extension of ALPHA1080 with Microscope or Telescope Adapter



Extension		Picture
C-mount camera		Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Microscope imaging;
Microscope Camera	 ALPHA1080+AMAXXX(23.2mm Adapter)	 ALPHA1080+FMAXXX(23.2mm Adapter)
Telescope Camera	 ALPHA1080+ATAXXX(31.75mm Adapter)	 ALPHA1080+FTAXXX(31.75mm Adapter)

5.4.7 Sample Photos Captured with ALPHA1080A









5.5 XCAM0720PHB/PHC C-mount HDMI CMOS Camera (2)

5.5.1 XCAM0720PHB/PHC's Basic Characteristic

- Through standard HDMI interface to stream the video to display or HDTV;
- Aptina CMOS sensor;
- Easy connecting to other equipment on the production line with the C-mount optical interface;
- High-resolution and high frame rate, perfect color reproduction, highly integrated and compact, low failure rate and stable performance;
- 1280 × 720 (720P) resolutions to match the current high-definition display on the market;
- XCAM720PHB/PHC embedded XCamView based on the Qt platform. The camera characteristic can be controlled by XCamView through the mouse. The other basic processing and choosing can also be realized by the XCamView;
- XCAM0720PHB/PHC can meet various applications and can be widely used in industrial inspection, education and research, materials analysis, precision measurement, medical analyses etc.



Photos of XCAM0720PHB/PHC

5.5.2 XCAM0720PHB/PHC Datasheet(2)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Responsivity Dynamic range SNRmax	FPS/Resolution	Binning	Exposure(ms)
XCAM0720PHB XP0720B	720P/1.2M/AR0130(C) 1/3“(4.80x2.70)	3.75 x3.75	6.5v/lux-sec 85.3dB 44dB	30@1280x720	1x1	0.2ms~2000ms
XCAM0720PHC XP0720C	720P/2M/IMX322(C) 1/2. 8”(5.78x3.02)	2.8 x2.8	510mv with 1/30s (G Sensitivity) 0.15mv with 1/30s (Dark Signal)	30@1280x720 (HDMI) 1920x1080 (Capture)	1x1	0.06ms~1900ms

Interface & Button Functions



Camera Interface

HDMI	HDMI Output Port
USB	USB Mouse for XCamView Control
DC12V	Power Input Slot
SD	SD Card Slot

Overall Dimensions

Width x Depth x Height	50 mm (1.97") x 50 mm (1.97") x 61mm (2.4")
Shipping Weight	0.47kg (0.55 lbs)

Operating Environment

Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V/1A Adapter

Optional Accessories


Lens	C-mount Lens
Cable	HDMI Cable
Memory Card	SD Card
Mouse	USB mouse/USB Wireless Mouse

5.5.3 Hardware Interface and XCamView UI Description

The XCAM0720PHB/PHC light indicator flashes about 15s after the power on. The camera will load XCamView, and then the system begins to work. Auto exposure and white balance are the default state now.



- HDMI: The HDMI cable connected to the HDMI diaplayer;
- USB: USB mouse;
- DC 12V: Power in 12V/1A;
- LED: The blue LED indicator;
- SD: SD card;



The GUI of the embeded camera control panel of XCamView in XCAM720PHB



XCamView toolbar for XCAM0720PHB/PHC

Move mouse to the bottom of the HDMI displayer, the bottom toolbar will be available. The function of each toolbar buttons are described as follows:

- 1: Image Capture
- 2: Digital Zoom In
- 3: Digital Zoom Out
- 4: Horizontal Flip
- 5: Vertical Flip
- 6: Video Freez /Cancel Video Freeze
- 7: Display/Hide the Camera Control Panel
- 8: Display the XCamView Version Information

5.5.4 Dimension of XCAM0720PHB/PHC



Dimension of XCAM720PHB/PHC

5.5.5 Packing Information for XCAM0720PHB/PHC



Packing Information for XCAM0720PHB/PHC

Standard Packing List

A	Gift box : L:17.5cm W:17.5cm H:8.5cm (1pcs, 0.85kg/ box)
B	XCAM0720PHB or XCAM0720PHC
C	Power Adapter: Input: AC 100~240V 50Hz/60Hz, Output: DC 12V 1A American standard: Model: GS12U12-PII 12W/12V/1A; UL/CUL/BSMI/CB/FCC EMI Standard:EN55022,EN61204-3, EN61000-3-2,-3, FCC Part 152 class B, BSMI CNS14338
D	EMS Standard:EN61000-4-2,3,4,5,6,8,11,EN61204-3,Class A Light Industry Standard
E	European standard: Model:GS12E12-PII 12W/12V/1A; TUV(GS)/CB/CE/ROHS EMI Standard:EN55022,EN61204-3, EN61000-3-2,-3, FCC Part 152 class B, BSMI CNS14338 EMS Standard:EN61000-4-2,3,4,5,6,8,11,EN61204-3,Class A Light Industry Standard
D	HDMI Cable
E	USB mouse/USB Wireless Mouse

Optional Accessory

F	Adjustable lens adapter	C-Mount to Dia.23.2mm Eyepiece Tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075
		C-Mount to Dia.31.75mm Eyepiece Tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075
G	Fixed lens Adapter	C-Mount to Dia.23.2mm Eyepiece Tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075
		C-Mount to Dia.31.75mm Eyepiece Tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075
H	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube		
I	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube		
J	Calibration kit 106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)		
K	SD Card(4G or 8G)		

5.5.6 Extension of XCAM0720PHB/PHC with Microscope or Telescope Adapter

Extension	Picture	
C-mount Camera		Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;
Microscope Camera	 XCAM0720PHB+AMAXXX(23.2mm Adapter)	 XCAM0720PHB+FMAXXX(23.2mm Adapter)
Telescope Camera:	 XCAM0720PHB+ATAXXX(31.75mm Adapter)	 XCAM0720PHB+FTAXXX(31.75mm Adapter)

5.6 XCAM0720PHA C-mount HDMI CMOS Camera(1) (Discontinued)

5.6.1 XCAM0720PHA's Basic Characteristic

- Through standard HDMI interface to stream the video to display or HDTV.
- Aptina CMOS sensor;
- Easy connecting to other equipment on the production line with the C-mount interface.
- High-resolution and high frame rate, perfect color reproduction, highly integrated and compact, low failure rate and stable performance.
- 1280 × 720 (720P) resolutions to match the current high-definition display on the market.
- Supporting various OSD cursors which can be toggled On/Off (functions shift as users press the button). The OSDs including: scale, double horizontal line, double vertical line, double cross line, Tri-cross line.
- Function buttons including automatic white balance and exposure on/off (AEWB), saving images to SD card (SAVE), video stream and freeze on/off (FREEZE), remote image snapshot controller to reduce the vibration blur (REMOTE).
- Meet various applications and can be widely used in industrial inspection, education and research, materials analysis, precision measurement, medical analyses etc.



5.6.2 XCAM0720PHA Datasheet

Order Code	Sensor & Size(mm)	Pixel(μm)	G Responsivity Dynamic range SNRmax	FPS/Resolution	Binning	Exposure(ms)
XCAM0720PHA XP0720A(Suspended)	720P/MT9P031 (C) 1/2.5"(5.70x4.28)	2.2x2.2	1.4 V/lux-sec 70.1dB 38.1dB	30@1280x720	1x1	0.21ms~33ms

Interface & Button Functions



Button 1	Video Stream/Freeze
Button 2	AEWB ON/OFF
Button 3	Save Image to SD Card
Button 4	Cursor ON/OFF

1X HDMI Output Port
1X SD Card Slot
1X Power Input Slot
1X Remote Switch Slot

Overall Dimensions

Width X Depth X Height	68 mm (2.67") X 68 mm (2.67") X 92mm (3.62")
Shipping Weight	0.25 kg (0.55 lbs)

Operating Environment

Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V/1A Adapter

Optional Accessories


Lens	C-mount Lens
Cable	HDMI Cable
Memory Card	SD Card
Remote Image Save Switch	2.5mm Headphone Jack Remote Image Save Switch

5.6.3 Function Key Description


The XCAM0720PHA light indicator flashes about 15s after the power on. Then the XCAM0720PHA will load software, after finish loading, the system begins to work. Auto exposure and white balance are the default state now.



- **FREEZE** button: Toggle between the video stream mode/freeze mode(Default is video stream);
- **AEWB** button: Toggle auto exposure and white balance on/off (Default is on);
- **SAVE** button: Saving the current screen to the image SD card, the compression format is JPEG with a resolution of 1280x720, users can press the button or click the remote controller button to save picture;




- **CURSOR** button: Toggle the OSD cursor on/off (default is off).Crosshair style including: scale, double horizontal line, double vertical line, double cross line, Tri-factor cross line. Functions shift as user press the button.




Scale


Default is off




Scale




Two horizontal lines



Two horizontal lines



Double cross line



Tri-factor cross line

5.6.4 Dimension of XCAM0720PHA



5.6.5 Packing Information for XCAM720PHA



Packing Information of XCAM0720PHA

Standard Packing List

A	Gift box : L:25.5cm W:17.0cm H:19.0cm (1pcs, 1.43Kg/ box)
B	XCAM0720PHA
C	Power Adapter: Input: AC 100~240V 50Hz/60Hz, Output: DC 12V 1A American standard: Model: GS12U12-PII 12W/12V/1A: UL/CUL/BSMI/CB/FCC EMI Standard: EN55022,EN61204-3, EN61000-3-2,-3, FCC Part 152 class B, BSMI CNS14338 EMS Standard: EN61000-4-2,3,4,5,6,8,11,EN61204-3,Class A Light Industry Standard European standard: Model:GS12E12-PII 12W/12V/1A; TUV(GS)/CB/CE/ROHS EMI Standard:EN55022,EN61204-3, EN61000-3-2,-3, FCC Part 152 class B, BSMI CNS14338 EMS Standard:EN61000-4-2,3,4,5,6,8,11,EN61204-3,Class A Light Industry Standard
D	HDMI Cable
E	2.5mm Headphone Jack Remote Image Save Switch

Optional Accessory

F	Adjustable lens adapter	C-Mount to Dia.23.2mm Eyepiece Tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075
		C-Mount to Dia.31.75mm Eyepiece Tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075
G	Fixed lens Adapter	C-Mount to Dia.23.2mm Eyepiece Tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075
		C-Mount to Dia.31.75mm Eyepiece Tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075
H	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube		
I	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube		
J	Calibration kit 106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)		
K	SD Card(4G or 8G)		

5.6.6 Extension of XCAM0720PHA Camera with Microscope or Telescope Adapter

Extension	Picture	
C-mount Camera		Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;
Microscope Camera	 XCAM0720PHA+AMAXXX(23.2mm Adapter)	 XCAM0720PHA+FMAXXX(23.2mm Adapter)
Telescope Camera:	 XCAM0720PHA+ATAXXX(31.75mm Adapter)	 XCAM0720PHA+FTAXXX(31.75mm Adapter)

6 Microscope TE-Cooling USB2.0 and 3.0 CCD Camera

6.1 MTR3CCD Series TE-Cooling C-mount USB3.0 CCD Camera

6.1.1 The Basic Characteristic of MTR3CCD

MTR3CCD camera adopts Sony Exview HAD CCD II sensor as the image-picking device with two-stage peltier cooling sensor chip to -40 degree below ambient temperature. This will greatly increase the signal to noise ratio and decrease the image noise. Smart structure is designed to assure the heat radiation efficiency and avoid the moisture problem. Electric fan is used to increase the heat radiation speed.

USB3.0 is used as the data transfer interface to increase the frame rate.

MTR3CCD comes with advanced video & image processing application ToupVi; Providing Windows/Linux/OSX multiple platform SDK; Native C/C++, C#/VB.NET, DirectShow, Twain Control API;

The **MTR3CCD** can be widely used in low light environment and microscope fluorescence image capture and analysis, as well as the astronomy deep sky application.



The basic characteristic of MTR3CCD can be summarized as follows:

- Standard C-Mount camera with SONY ExView HAD CCD II sensors from 1.4M to 12M;
- Two-stage TE-cooling with controllable electric fan;
- Sensor chip cooling up to 40°C below ambient temperature;
- Working temperature can be regulated to specified temperature in 5 minutes;
- Smart structure to assure the heat radiation efficiency and avoid the moisture problem;
- IR-CUT/AR coated windows;
- Up to 1 hour long time exposure;
- USB3.0 5Gbit/second interface ensuring high speed data transmission;
- Ultra-Fine™ color engine with perfect color reproduction capability;
- With advanced video & image processing application ToupView;
- Support both video and trigger modes;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.NET, DirectShow, Twain control API;

6.1.2 MTR3CCD Datasheet(12)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Sensitivity Dark Signal	FPS/Resolution	Binning	Exposure
MTR3CCD12000KPA MP112000A(New)	12M/ICX834AQG(C) 1"(13.15x8.77)	3.1x3.1	420mv with 1/30s 15.2mv with 1/30s	3.6@4248x2836 3.6@2124x1418	1x1, 2x2	0.06ms~1h
MTR3CCD12000KMA MM112000A(New)	12M/ICX834ALG(M) 1"(13.15x8.77)	3.1x3.1	420mv with 1/30s 12mv with 1/30s (F8.0)	3.6@4248x2836 3.6@2124x1418	1x1, 2x2	0.06ms~1h
MTR3CCD09000KPA MP109000A(New)	9.0M/ICX814AQG(C) 1"(12.47x9.98)	3.69x3.69	580mv with 1/30s 12mv with 1/30s	4.4@3388x2712 4.4@1694x1356	1x1, 2x2	0.06ms~1h
MTR3CCD09000KMA MM109000A(New)	9.0M/ICX814ALG(M) 1"(12.47x9.98)	3.69x3.69	660mv with 1/30s 12mv with 1/30s (F8.0)	4.4@3388x2712 4.4@1694x1356	1x1, 2x2	0.06ms~1h
MTR3CCD06000KPA MP106000A	6.0M/ICX694AQG(C) 1"(12.48x9.99)	4.54x4.54	880mv with 1/30s 8mv with 1/30s	7.5@2748x2200 14@2748x1092	1x1	0.06ms~1h
MTR3CCD06000KMA MM106000A	6.0M/ICX694ALG(M) 1"(12.48x9.99)	4.54x4.54	1000mv with 1/30s 8mv with 1/30s	7.5@2748x2200 14@2748x1092	1x1	0.06ms~1h
MTR3CCD02800KPA MP102800A(New)	2.8M/ICX674AQG(C) 2/3"(8.81x6.63)	4.54x4.54	800mv with 1/30s 4mv with 1/30s	15@1938x1460 17@1610x1212 18@1930x1092	1x1	0.05ms~1h
MTR3CCD02800KMA MM102800A(New)	2.8M/ICX674ALG(M) 2/3"(8.81x6.63)	4.54x4.54	950mv with 1/30s 4mv with 1/30s	15@1938x1460 17@1610x1212 18@1930x1092	1x1	0.05ms~1h
MTR3CCD01400KPA MP101400A	1.4M/ICX285AQ(C) 2/3"(8.88x6.70)	6.45x6.45	1240mv with 1/30s 10mv with 1/30s	15@1360x1024	1x1	0.07ms~1h
MTR3CCD01400KMA MM101400A	1.4M/ICX285AL(M) 2/3"(8.88x6.70)	6.45x6.45	1300mv with 1/30s 11mv with 1/30s	15@1360x1024	1x1	0.07ms~1h
MTR3CCD01400KPB MP101400B(New)	1.4M/ICX825AQ(A(C) 2/3"(8.88x6.70)	6.45x6.45	2000mv with 1/30s 4.8mv with 1/30s	25@1376x1040	1x1	0.07ms~1h
MTR3CCD01400KMB MM101400B(New)	1.4M/ICX825ALA(M) 2/3"(8.88x6.70)	6.45x6.45	2000mv with 1/30s 4.8mv with 1/30s	25@1376x1040	1x1	0.07ms~1h

C:Color; M:Monochrome;

Other Specification for MTR3CCD Cameras

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	ROI White Balance/ Manual Temp Tint Adjustment/NA for Monochromatic Sensor
Color Technique	Ultra-Fine™ Color Engine/NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Two-stage TE-cooling System -45 °C below Camera Body Temperature

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port External Power Adapter for Cooling System, DC12V, 3A

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 10 (32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory:2GB or More
	USB Port:USB2.0 High-speed Port
	Display:17" or Larger
	CD-ROM

6.1.3 MTR3CCD Dimension

The MTR3CCD body, made from tough, alloy with CNC technique, ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT or AR to block the IR light or protect the camera sensor. The fan's vibration is minimized to the low level to eliminate the vibration caused imaging blur. This design ensures a rugged, robust solution with an increased lifespan when compared to the other industrial camera solutions.



Dimension of MTR3CCD

6.1.4 Packing Information for MTR3CCD Camera



Packing Information of MTR3CCD Camera

Standard Package			
A	Carton L:50cm W:30cm H:30cm (20pcs, 12~17Kg/ carton), not shown in the photo		
B	3-A safety equipment case: L:28cm W:23cm H:15cm (1pcs, 2.8Kg/ box); Carton size:L:28.2cm W:25.2cm H:16.7cm		
C	MTR3CCD camera(C-mount)		
D	Power adapter: input: AC 100~240V 50Hz/60Hz, output: DC12 V 3A		
E	High-Speed USB3.0 A male to B male gold-plated connectors cable /2.0m		
F	CD (Driver & utilities software, Ø12cm)		
Optional Accessory			
G	Adjustable lens adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075 108004/AMA100
		C-Mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075 108011/ATA100
H	Fixed lens Adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075 108008/FMA100
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075 108014/FTA100
I	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube		
J	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube		
K	External trigger control line		
L	Calibration kit	106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)	

~~6.2 SCCC Series TE Cooling C mount USB2.0 CCD Camera~~^{suspended}

6.2.1 The Basic Characteristic of SCCC

SCCC adopts semiconductor cooling peltier chip technique to keep Sony ExView HAD or HAD **CCD** sensor (The image-picking device) at low temperature. This will greatly increase the signal to noise ratio and decrease the image noise. Besides, integrated heat pipe-heat sink technique is used to transfer the heat to the camera housing fins. No fan is needed to keep the camera from vibration.

USB2.0 is used as the data transfer interface to keep the moderate frame rate.

SCCC comes with advanced video & image processing application ToupView; Providing Windows/Linux/OSX multiple platform SDK; Native C/C++, C#/VB.NET, DirectShow, Twain Control API;

The SCCC can be widely used in low light environment and microscope fluorescence image capture and analysis.

The basic characteristic of SCCC is summarized as follows:

- Standard C-Mount camera with SONY ExView or Super HAD CCD 1.4~5.2M sensor;
- Well-designed high-performance TE-cooling with heat pipe heat sink structure;
- Up to 20 degrees temperature drop ensures high quality image with lower noise;
- C-mount camera;
- Supporting up to 4 minutes long time exposure;
- USB2.0 interface ensuring high speed data transmission;
- Ultra-Fine™ color engine with perfect color reproduction capability;
- With advanced video & image processing application ToupView;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.NET, DirectShow, Twain Control API;



6.2.2 SCCCDS Datasheet(5)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Sensitivity Dark Signal	FPS/Resolution	Binning	Exposure
SCCCD05200KPA TP905200A	5.2M/ICX655AQ(C) 2/3" (8.44x7.07)	3.45x3.45	420mv with 1/30s 4mv with 1/30s	4.3@2448x2050 10.5@960x720	1x1	0.22ms~60s
SCCCD01400KPA TP901400A	1.4M/ICX285AQ(C) 2/3" (8.77x6.60)	6.45x6.45	1240mv with 1/30s 10mv with 1/30s	15@1360x1024	1x1	0.12ms~240s
SCCCD01400KMA TM901400A	1.4M/ICX285AL(M) 2/3" (8.77x6.60)	6.45x6.45	1300mv with 1/30s 11mv with 1/30s	15@1360x1024	1x1	0.12ms~240s
SCCCD01400KPB TP901400B	1.4M/ICX205AK(C) 1/2" (6.32x4.76)	4.65x4.65	400mv with 1/30s 16mv with 1/30s	15@1360x1024	1x1	0.12ms~240s
SCCCD01400KMB TM901400B	1.4M/ICX205AL(M) 1/2" (6.32x4.76)	4.65x4.65	450mv with 1/30s 16mv with 1/30s	15@1360x1024	1x1	0.12ms~240s

C:Color; M:Monochrome;

Other Specification for SCCCDS Cameras

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	ROI White Balance/ Manual Temp Tint Adjustment/NA for Monochromatic Sensor
Color Technique	Ultra-Fine™ Color Engine/NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	TE-cooling System -20 °C below Ambient Temperature

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port External Power Adapter for Cooling System, DC 3V, 5A

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 10 (32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher Memory:2GB or More USB Port:USB2.0 High-speed Port Display:17" or Larger CD-ROM

6.2.3 Dimension of SCCC

The SCCC body, made from tough, alloy with CNC technique, ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT to protect the camera sensor and block the IR light. No moving parts included. This design ensures a rugged, robust solution with an increased lifespan when compared to other industrial camera solutions.



6.2.4 Packing Information for SCCC



Packing Information of SCCC

Standard Package	
A	3-A safety equipment case: L:28cm W:23cm H:15cm (1pcs, 3.7Kg/ box); carton size:L:28.2cm W:25.5cm H:16.7cm
B	SCCCD(C-mount)
C	CD (Driver & utilities software, Ø12cm)
D	High-Speed USB2.0 A male to B male gold-plated connectors cable /2.0m
E	Power Adapter: input: AC 100~240V 50Hz/60Hz, output: DC 3V 5A
F	Power cord
Optional Accessories	
G	Calibration kit: TS-M1(X=0.01mm/100Div.); TS-M2(X,Y=0.01mm/100Div.); TS-M7 (X=0.01mm/100Div., 0.10mm/100Div.)

7 Microscope USB3.0 CCD Camera

7.1 U3CCD Series C-mount USB3.0 CCD Camera

7.1.1 U3CCD Basic Characteristic

U3CCD is an ExView HAD CCD series camera. It adopts Sony ExView HAD CCD sensor as the image-picking device. Sony ExView HAD CCD is a CCD that drastically improves light efficiency by including near infrared light region as a basic structure of HAD (Hole-Accumulation-Diode) sensor. We uses EXCCD for simplicity. USB3.0 is used as the data transfer interface.

U3CCD hardware resolutions range from 1.4M to 12M and come with the integrated CNC aluminum alloy compact housing.

U3CCD comes with advanced video & image processing application ToupView; Providing Windows/Linux/ OSX multiple platforms SDK; Native C/C++, C#/VB.NET, DirectShow, Twain Control API;

The U3CCD can be widely used in bright field light environment and microscope image capture and analysis with higher frame rate.

The U3CCD characteristic is as follows:

- Standard C-Mount camera with SONY ExView HAD CCD II sensors from 1.4M ~12M;
- IR-CUT Coated Windows
- Up to 1000s long time exposure;
- USB3.0 5Gbit/second interface ensuring high speed data transmission;
- Ultra-Fine™ color engine with perfect color reproduction capability;
- With advanced video & image processing application ToupView;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.NET, DirectShow, Twain Control API;



7.1.2 U3CCD Datasheet (10)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Sensitivity Dark Signal	FPS/Resolution	Binning	Exposure
U3CCD12000KPA NP112000A(New)	12M/ICX834AQG(C) 1"(13.15x8.77)	3.1x3.1	420mv with 1/30s 15.2mv with 1/30s	3.6@4248x2836 3.6@2124x1418	1x1, 2x2	0.06ms~1000s
U3CCD12000KMA NM112000A(New)	12M/ICX834ALG(M) 1"(13.15x8.77)	3.1x3.1	420mv with 1/30s 12mv with 1/30s (F8.0)	3.6@4248x2836 3.6@2124x1418	1x1, 2x2	0.06ms~1000s
U3CCD09000KPA NP109000A(New)	9.0M/ICX814AQG(C) 1"(12.47x9.98)	3.69x3.69	580mv with 1/30s 12mv with 1/30s	4.4@3388x2712 4.4@1694x1356	1x1, 2x2	0.06ms~1000s
U3CCD09000KMA NM109000A(New)	9.0M/ICX814ALG(M) 1"(12.47x9.98)	3.69x3.69	660mv with 1/30s 12mv with 1/30s (F8.0)	4.4@3388x2712 4.4@1694x1356	1x1, 2x2	0.06ms~1000s
U3CCD06000KPA NP106000A	6.0M/ICX694AQG(C) 1"(12.48x9.99)	4.54x4.54	880mv with 1/30s 8mv with 1/30s	7.5@2748x2200 14@2748x1092	1x1	0.06ms~1000s
U3CCD06000KMA NM106000A	6.0M/ICX694ALG(M) 1"(12.48x9.99)	4.54x4.54	1000mv with 1/30s 8mv with 1/30s	7.5@2748x2200 14@2748x1092	1x1	0.06ms~1000s
U3CCD02800KPA NP102800A	2.8M/ICX674AQG(C) 2/3"(8.81x6.63)	4.54x4.54	800mv with 1/30s 4mv with 1/30s	15@1938x1460 17@1610x1212 18@1930x1092	1x1	0.05ms~1000s
U3CCD02800KMA NM102800A	2.8M/ICX674ALG(M) 2/3"(8.81x6.63)	4.54x4.54	950mv with 1/30s 4mv with 1/30s	15@1938x1460 17@1610x1212 18@1930x1092	1x1	0.05ms~1000s
U3CCD01400KPB NP101400B(New)	1.4M/ICX825AQA(C) 2/3"(8.88x6.70)	6.45x6.45	2000mv with 1/30s 4.8mv with 1/30s	25@1376x1040	1x1	0.07ms~1000s
U3CCD01400KMB NM101400B(New)	1.4M/ICX825ALA(M) 2/3"(8.88x6.70)	6.45x6.45	2000mv with 1/30s 4.8mv with 1/30s	25@1376x1040	1x1	0.07ms~1000s

C: Color; M: Monochrome;

Other Specification for U3CCD Camera

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	ROI White Balance/ Manual Temp Tint Adjustment/NA for Monochromatic Sensor
Color Technique	Ultra-Fine™ Color Engine/NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Natural

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 10 (32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory: 2GB or More
	USB Port: USB3.0 High-speed Port
	Display: 17" or Larger
	CD-ROM

7.1.3 Dimension of U3CCD

The U3CCD body, made from tough, CNC aluminum alloy, ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT to protect the camera sensor. No moving parts included. This design ensures a rugged, robust solution with an increased lifespan when compared to other industrial camera solutions.



Dimension of U3CCD Series Camera

7.1.4 Packing Information for U3CCD Series Camera



Packing Information of U3CCD Series Camera

Standard Camera Packing List

- A Carton L:52cm W:32cm H:33cm (20pcs, 12~17Kg/ carton), not shown in the photo
- B Gift box L:15cm W:15cm H:10cm (0.7~0.75Kg/ box)
- C U3CCD series USB3.0 C-mount CMOS camera
- D High-speed USB3.0 A male to B male gold-plated connectors cable /2.0m
- E CD (Driver & utilities software, Ø12cm)

Optional Accessory

		C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075 108004/AMA100
F	Adjustable lens adapter	C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075 108011/ATA100
		C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075 108008/FMA100
G	Fixed lens Adapter	C-Mount to Dia.31.75mm Eyepiece Tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075 108014/FTA100
H	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube		
I	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube		
J	108017(Dia.23.2mm to 31.75mm Ring)/ Adapter rings for 31.75mm eyepiece tube		
K	Calibration kit	106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)	

7.1.5 Extension of U3CCD with Microscope or Telescope Adapter

Extension	Picture	
C-mount Camera		Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;
Microscope Camera	 	U3CCD+AMAXXX(23.2mm Adapter) U3CCD+FMAXXX(23.2mm Adapter)
Telescope Camera	 	U3CCD+ATAXXX(31.75mm Adapter) U3CCD+FTAXXX(31.75mm Adapter)

8 Microscope USB2.0 CCD Camera

8.1 EXCCD Series C-mount USB2.0 CCD Camera

8.1.1 EXCCD Basic Characteristic

EXCCD is an [ExView HAD CCD](#) camera and it adopts Sony ExView HAD CCD sensor as the image-picking device. Sony ExView HAD CCD is a CCD that drastically improves light efficiency by including near infrared light region as a basic structure of HAD (Hole-Accumulation-Diode) sensor. We uses EXCCD for simplicity. US B2.0 is used as the data transfer interface.

EXCCD comes with advanced video & image processing application ToupView; Providing Windows/Linux/OSX multiple platform SDK; Native C/C++, C#/VB.NET, DirectShow, Twain Control API;

The EXCCD can be widely used in low light environment and microscope fluorescence image capture and analysis.

The EXCCD's basic characteristic is as follows:

- Standard C-Mount camera with SONY ExView 0.3M~1.4M sensors;
- USB2.0 interface ensuring high speed data transmission;
- Ultra-Fine color engine with perfect color reproduction capability;
- With advanced video & image processing application ToupView;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.NET, DirectShow, Twain Control API;



8.1.2 EXCCD Datasheet(4)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Sensitivity Dark Signal	FPS/Resolution	Binning	Exposure
EXCCD01400KPA TP801400A	1.4M/ICX285AQ(C) 2/3" (8.77x6.60)	6.45x6.45	1240mv with 1/30s 10mv with 1/30s	15@1360x1024	1x1	0.12ms~240s
EXCCD01400KMA TM801400A	1.4M/ICX285AL(M) 2/3" (8.77x6.60)	6.45x6.45	1300mv with 1/30s 11mv with 1/30s	15@1360x1024	1x1	0.12ms~240s
EXCCD00440KMA TM800440A	0.44M/ICX829AL(M) 1/2"(6.43x4.80)	8.6X8.3	2800mv with 1/30s 2mv with 1/30s	46@748X578	1X1	0.20ms~3600s
EXCCD00300KMA TM800300A	0.3M ICX618AL(M) 1/4" (3.58x2.69)	5.6x5.6	1200mv with 1/30s 4mv with 1/30s	72@640x480	1x1	0.06ms~40s

C: Color; M: Monochrome;

Other Specification for EXCCD Cameras

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	ROI White Balance/ Manual Temp Tint Adjustment /NA for Monochromatic Sensor
Color Technique	Ultra-Fine™ Color Engine /NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Natural

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 10 (32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory:2GB or More
	USB Port:USB2.0 High-speed Port
	Display:17" or Larger
	CD-ROM

8.1.3 Dimension of EXCCD

The EXCCD body, made from tough, aluminum alloy, ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT to protect the camera sensor. No moving parts included. This design ensures a rugged, robust solution with an increased lifespan when compared to other industrial camera solutions.



Dimension of EXCCD

8.1.4 Packing Information of EXCCD



Packing Information of EXCCD

Standard Camera Packing List

- A Carton L:52cm W:32cm H:33cm (20pcs, 12~17Kg/ carton), not shown in the photo
- B Gift box L:15cm W:15cm H:10cm (0.67~0.80Kg/ box)
- C EXCCD series USB2.0 C-Mount camera
- D High-speed USB2.0 A male to B male gold-plated connectors cable /2.0m
- E CD (Driver & utilities software, Ø12cm)

Optional Accessory

F	Adjustable lens adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075
		C-Mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075
G	Fixed lens Adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075
H	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube		
I	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube		
J	108017(Dia.23.2mm to 31.75mm Ring)/ Adapter rings for 31.75mm eyepiece tube		
K	Calibration kit	106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)	

8.1.5 Extension of EXCCD with Microscope or Telescope Adapter

Application	Picture	Picture
C-mount Camera		Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;
Microscope Camera	 EXCCD+AMAXXX(23.2mm Adapter)	 EXCCD+FMAXXX(23.2mm Adapter)
Telescope Camera	 EXCCD+ATAXXX(31.75mm Adapter)	 EXCCD+FTAXXX(31.75mm Adapter)

8.2 UHCCD Series C-mount USB2.0 CCD Camera

8.2.1 UHCCD Basic Characteristic

UHCCD is an [ultra-high performance Super HAD CCD](#) camera. The camera adopts Sony Super HAD CCD sensor as the image-picking device; The Super HAD CCD is a version of Sony's high performance CCD HAD (Hole-Accumulation Diode) sensor with sharply improved sensitivity by the incorporation of a new semiconductor technology developed by Sony Corporation. USB2.0 is used as the data transfer interface.

UHCCD comes with advanced video & image processing application ToupView; Providing Windows/Linux/OSX multiple platform SDK; Native C/C++, C#/VB.NET, DirectShow, Twain Control API;

The UHCCD can be widely used in bright field light environment and microscope image capture and analysis.

The UHCCD's basic characteristic is as follows:

- Standard C-Mount camera with SONY Super HAD CCD 0.8~5.2M sensor;
- USB2.0 interface ensuring high speed data transmission;
- Ultra-Fine color engine with perfect color reproduction capability;
- With advanced video & image processing application ToupView;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.NET, DirectShow, Twain Control API;



8.2.2 UHCCD Datasheet(9)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Sensitivity Dark Signal	FPS/Resolution	Binning	Exposure
UHCCD05200KPA TP705200A	5.2M/ICX655AQ(C) 2/3“(8.44x7.07)	3.45x3.45	420mv with 1/30s 4mv with 1/30s	4.3@2448x2050 10.5@960x720	1x1	0.22ms~60s
UHCCD05100KPA TP705100A	5.1M/ICX452AQ(C) 1/1.8“(7.19x5.39)	2.775x2.775	260mv with 1/30s 16mv with 1/30s	4@2592x1944 35@560x420	1x1, 2x2	0.212ms~77ms
UHCCD05000KPA TP705000A	5.0M/ICX282AQ(C) 2/3“(8.70x6.53)	3.40x3.40	280mv with 1/30s 16mv with 1/30s	4.5@2560x1920 9@1280x960	1x1, 2x2	0.203ms~60s
UHCCD03100KPB TP703100B(Suspended)	3.1M/ICX252AQ(C) 1/1.8“(7.06x5.30)	3.45x3.45	270mv with 1/30s 42mv with 1/30s	6@2048x1536 41@640x480	1x1, 2x2	0.178ms~77ms
UHCCD02000KPA TP702000A	2.0M/ICX274AQ(C) 1/1.8“(7.04x5.28)	4.40x4.40	420mv with 1/30s 8mv with 1/30s	10@1600x1200	1x1	0.135ms~60s
UHCCD01400KPA TP701400A	1.4M/ICX205AK(C) 1/2“(6.32x4.76)	4.65x4.65	400mv with 1/30s 16mv with 1/30s	8@1360x1024	1x1	0.227ms~60s
UHCCD01400KPB TP701400B	1.4M/ICX205AK(C) 1/2“(6.32x4.76)	4.65x4.65	400mv with 1/30s 16mv with 1/30s	15@1360x1024	1x1	0.127ms~60s
UHCCD01400KMB TM701400B	1.4M/ICX205AL(M) 1/2“(6.32x4.76)	4.65x4.65	450mv with 1/30s 16mv with 1/30s	15@1360x1024	1x1	0.127ms~60s
UHCCD00800KPA TP700800A	0.8M/ICX204AK(C) 1/3“(4.76x3.57)	4.65x4.65	400mv with 1/30s 6mv with 1/30s	16@1024x768	1x1	0.16ms~60s

C:Color; M:Monochrome;

Other Specification for UHCCD

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	ROI White Balance/ Manual Temp Tint Adjustment/NA for Monochromatic Sensor
Color Technique	Ultra-Fine™ Color Engine/NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Natural

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 10 (32 & 64 bit) OSX(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory:2GB or More
	USB Port:USB2.0 High-speed Port
	Display:17" or Larger
	CD-ROM

8.2.3 Dimension of UHCCD

The UHCCD body, made from tough, aluminum alloy, ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT to protect the camera sensor. No moving parts included. This design ensures a rugged, robust solution with an increased lifespan when compared to other industrial camera solutions.



Dimension of UHCCD

8.2.4 Packing Information of UHCCD



Packing Information of UHCCD

Standard Camera Packing List

A	Carton L:52cm W:32cm H:33cm (20pcs, 12~17Kg/ carton), not shown in the photo
B	Gift box L:15cm W:15cm H:10cm (0.67~0.8Kg/ box)
C	UHCCD series camera
D	High-speed USB2.0 A male to B male gold-plated connectors cable /2.0m
E	CD (Driver & utilities software, Ø12cm)

Optional Accessory

F	Adjustable lens adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075
G	Fixed lens Adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075
H	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube		
I	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube		
J	108017(Dia.23.2mm to 31.75mm Ring)/ Adapter rings for 31.75mm eyepiece tube		
K	Calibration kit	106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)	

8.2.5 Extension of UHCCD with Microscope or Telescope Adapter

Extension	Picture	Picture
C-mount Camera		Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;
Microscope Camera	 UHCCD+AMAXXX(23.2mm Adapter)	 UHCCD+FMAXXX(23.2mm Adapter)
Telescope Camera	 UHCCD+ATAXXX(31.75mm Adapter)	 UHCCD+FTAXXX(31.75mm Adapter)

9 Microscope USB3.0 CMOS Camera

9.1 MTR3CMOS Series TE-Cooling C-mount USB3.0 CMOS Camera

9.1.1 The Basic Characteristic of MTR3CMOS

MTR3CMOS camera adopts SONY Exmor CMOS sensor as the image-picking device and USB3.0 is used as the transfer interface to increase the frame rate.

With the two-stage peltier cooling sensor chip to -42 degree below ambient temperature. This will greatly increase the signal to noise ratio and decrease the image noise. Smart structure is designed to assure the heat radiation efficiency and avoid the moisture problem. Electric fan is used to increase the heat radiation speed.

USB3.0 is used as the data transfer interface to increase the frame rate.

MTR3CMOS comes with advanced video & image processing application ToupView; Providing Windows/Linux/OSX multiple platform SDK; Native C/C++, C#/VB.NET, DirectShow, Twain Control API;

The **MTR3CMOS** can be widely used in low light environment and microscope fluorescence image capture and analysis, as well as the astronomy deep sky application.



The basic characteristic of MTR3CMOS can be summarized as follows:

- Standard C-Mount camera with SONY Exmor CMOS sensors from 1.7M to 45M;
- Two-stage TE-cooling with controllable electric fan;
- Sensor chip cooling up to 42°C below ambient temperature;
- Working temperature can be regulated to specified temperature in 5 minutes;
- Smart structure to assure the heat radiation efficiency and avoid the moisture problem;
- IR-CUT/AR coated windows;
- Up to 1 hour long time exposure;
- USB3.0 5Gbit/second interface ensuring high speed data transmission;
- Ultra-Fine™ color engine with perfect color reproduction capability;
- With advanced video & image processing application ToupView;
- Support both video and trigger modes;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.NET, DirectShow, Twain control API;

9.1.2 MTR3CMOS Datasheet(13)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Sensitivity Dark Signal	FPS/Resolution	Binning	Exposure
MTR3CMOS45000KMA MTRP14500A (New) 20200118	45M/IMX492(M) 4/3 "(17. 47x12. 86)	2.315 x2.315	TBD	8@8192x5556 10@8192x4320 9@7408x5556	1x1 1x1 1x1	0.1ms~3600s
MTR3CMOS26000KPA MTRP126000A 2020年3月份量产	26M/IMX571(C) 1.8 "(23.48x15. 67) APS-C	3.76 x3.76	485mv with 1/30s 0.07mv with 1/30s	14@6224x4168(16bit) 37@3104x2084 110@2064x1388	1x1 2x2 3x3	0.1ms~3600s
MTR3CMOS09000KPA MTRP109000A 2020年3月份量产	9M/IMX533(C) 1 "(11. 28x11. 28)	3.76 x3.76	534mv with 1/30s 0.1mv with 1/30s	42@3000x3000(14bit) 126@1500x1500 188@1000x1000	1x1 2x2 3x3	0.1ms~3600s
MTR3CMOS21000KPA MTRP121000A 20190910	21M/IMX269(C) 4/3 "(17. 4x13. 1)	3.3 x3.3	400mv with 1/30s 0.1mv with 1/30s	5@5280x3956 6@3952x3952 15@2640x1978 50@1760x1318 100@584x440	1x1 1x1 2x2 3x3 9x9	0.1ms~3600s
MTR3CMOS20000KPA MTRP120000A	20M/IMX183(C) 1 "(13.056x8.755)	2.4 x2.4	462mv with 1/30s 0.21mv with 1/30s	5@5440x3648 10@4096x2160 15@2736x1824 30@1824x1216	1x1, 1x1, 2x2, 3x3	0.1ms~3600s
MTR3CMOS20000KMA MTRM120000A	20M/IMX183(M) 1 "(13.056x8.755)	2.4 x2.4	388mv with 1/30s 0.21mv with 1/30s (F8.0)	17.8@5440x3648 41@4096x2160 51@2736x1824 64@1824x1216	1x1, 1x1, 2x2, 3x3	0.1ms~3600s
MTR3CMOS16000KPA MTRP116000A	16M/MN34230PLJ(C) 4/3" (17.6x13.3)	3.8x3.8	2413LSB 89.1LSB (Gain = 0dB)	6@4640x3506 20@2304x1750 48@1536x1160	1x1 2x2 3x3	0.15ms~3600s
MTR3CMOS16000KMA MTRM116000A	16M/MN34230ALJ(M) 4/3" (17.6x13.3)	3.8x3.8	2650LSB 89.1LSB (Gain = 0dB)	22.5@4648x3506 43.0@2304x1750 48.0@1536x1168	1x1 2x2 3x3	0.15ms~3600s
MTR3CMOS10300KPA MTRP110300A	10.3M/IMX294(C) 4/3 "(17.47x12.86)	4.63 x4.63	419mv with 1/30s 0.12mv with 1/30s	7.5@3704x2778 8.5@4096x2160 30@2048x1080 60@1360x720	1x1, 1x1, 2x2, 3x3	0.15ms~3600s
MTR3CMOS07100KPA MTRP107100A	7.0M/IMX428(C, GS) 1.1 "(14. 4x9. 9)	4. 5 x4. 5	2058mv with 1/30s 0. 15mv with 1/30s	12@3200x2200 33@1600x1100	1x1 1x1	0.1ms~3600s
MTR3CMOS07100KMA MTRM107100A	7.0M/IMX428(M, GS) 1.1 "(14. 4x9. 9)	4. 5 x4. 5	3354mv with 1/30s 0.15mv with 1/30s	51@3200x2200 133@1600x1100	1x1 2x2	0.1ms~3600s
MTR3CMOS01700KPA MTRP101700A	1.7M/IMX432(C, GS) 1.1 "(14. 4x9. 9)	9.0 x9.0	4910mv with 1/30s 0.3mv with 1/30s	33@1600x1100	1x1	0.1ms~3600s
MTR3CMOS01700KMA MTRM101700A	1.7M/IMX432(M, GS) 1.1 "(14. 4x9. 9)	9.0 x9.0	8100mv with 1/30s 0.3mv with 1/30s	94@1600x1100	1x1	0.1ms~3600s

C:Color; M:Monochrome;

Other Specification for MTR3CMOS Cameras

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	ROI White Balance/ Manual Temp Tint Adjustment/NA for Monochromatic Sensor
Color Technique	Ultra-Fine™ Color Engine/NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Two-stage TE-cooling System -45 °C below Camera Body Temperature

Operating Environment

Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 /10 (32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory:2GB or More
	USB Port:USB3.0 High-speed Port
	Display:17" or Larger CD-ROM

9.1.3 MTR3CMOS Dimension

The MTR3CMOS body, made from tough, alloy with CNC technique, ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT or AR to block the IR light or protect the camera sensor. The fan's vibration is minimized to the low level to eliminate the vibration caused imaging blur. This design ensures a rugged, robust solution with an increased lifespan when compared to the other industrial camera solutions.



Dimension of MTR3CMOS


9.1.4 Packing Information for MTR3CMOS Camera




Packing Information of MTR3CMOS Camera

Standard Package			
A	Carton L:50cm W:30cm H:30cm (20pcs, 12~17Kg/ carton), not shown in the photo(TBD)		
B	3-A safety equipment case: L:28cm W:23cm H:15cm (1pcs, 2.8Kg/ box); Carton size:L:28.2cm W:25.2cm H:16.7cm(TBD)		
C	MTR3CMOS camera(C-mount)		
D	Drying tube and desiccant		
E	Power adapter: input: AC 100~240V 50Hz/60Hz, output: DC12 V 3A		
F	High-Speed USB3.0 A male to B male gold-plated connectors cable /1.5m		
G	CD (Driver & utilities software, Ø12cm)		
Optional Accessory			
H	Adjustable lens adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075 108004/AMA100
		C-Mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075 108011/ATA100
I	Fixed lens Adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075 108008/FMA100
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075 108014/FTA100
J	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube		
K	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube		
L	Calibration kit 106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)		

9.1.5 Extension of MTR3CMOS with Microscope Adapter




MTR3CMOS+AMAXXX(23.2mm Adapter)




MTR3CMOS+FMAXXX(23.2mm Adapter)

9.1.6 Sample Photos Captured with MTR3CMOS Camera



Hot noise for the MTR3CMOS at Gain 20 , 600 second, 15 Centidegree



Hot noise for the MTR3CMOS Gain 20 , 600 second, minus 15 Centidegree

9.2 T3CMOS Series TE-Cooling C-mount USB3.0 CMOS Camera

9.2.1 The Basic Characteristic of T3CMOS



The basic characteristic of T3CMOS can be summarized as follows:

- Standard C-Mount camera with SONY Exmor CMOS sensors from 1.7M to 20M;
- Professional designed high-performance, small size Tec-cooling structure, suitable for installation in equipment with high requirements for camera size;
- Controllable sensor temperature drops of up to 25 degrees below ambient temperature;
- Smart sensor protection glass anti-fogging technique under ultra-low temperature;
- T3CMOS integrated with 12 bit Ultra-fine™ Hardware Image Signal Processor Video Pipeline(Ultra-fine™ [HISP VP](#)) for Demosaic, Automatic Exposition, Gain Adjustment, One Push White Balance, Chrominance Adjustment, Saturation Adjustment, Gamma Correction, Luminance Adjustment, Contrast Adjustment, Bayer and finally form RAW data for 8/12 bit output. This will move the heavier burden of the processing from the PC CPU to the Ultra-fine™ [HISP VP](#) and greatly accelerating the processing speed.
- IR-CUT/AR coated windows;
- Up to 1 hour long time exposure;
- USB3.0 5Gbit/second interface ensuring high speed data transmission;
- With advanced video & image processing application ToupView;
- Support both video and trigger modes;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.NET, DirectShow, Twain control API;

9.2.2 T3CMOS Datasheet(6)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Sensitivity Dark Signal	FPS/Resolution	Binning	Exposure
T3CMOS20000KMA UM20000A (New)	20M/IMX183(M) 1“(13. 06x8. 84)	2.4 x2.4	777mv with 1/30s 0.2mv with 1/30s	18@5440x3648 49@2736x1824 59@1824x1216	1x1 2x2 3x3	0.1ms~1000s
T3CMOS20000KPA UP20000A (New)	20M/IMX183(C) 1“(13. 06x8. 84)	2.4 x2.4	462mv with 1/30s 0.2mv with 1/30s	18@5440x3648 49@2736x1824 59@1824x1216	1x1 2x2 3x3	0.1ms~1000s
T3CMOS07100KMA UM07100A (New)	7. 1M/IMX428(M, GS) 1.1“(14. 4x9. 9)	4.5 x4.5	3354mv with 1/30s 0.15mv with 1/30s	51@3200x2200 136@1584x1100	1x1 1x1	0.1ms~1000s
T3CMOS07100KPA UP07100A (New)	7. 1M/IMX428(C, GS) 1.1“(14. 4x9. 9)	4.5 x4.5	2058mv with 1/30s 0.15mv with 1/30s	51@3200x2200 136@1584x1100	1x1 1x1	0.1ms~1000s
T3CMOS01700KMA UM01700A (New)	1. 7M/IMX432(M, GS) 1.1“(14. 4x9. 9)	9.0 x9.0	8100mv with 1/30s 0.3mv with 1/30s	98@1600x1100	1x1	0.1ms~1000s
T3CMOS01700KPA UP01700A (New)	1. 7M/IMX432(C, GS) 1.1“(14. 4x9. 9)	9.0 x9.0	4910mv with 1/30s 0.3mv with 1/30s	98@1600x1100	1x1	0.1ms~1000s

C:Color; M:Monochrome;

Other Specification for T3CMOS Cameras

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	ROI White Balance/ Manual Temp Tint Adjustment/NA for Monochromatic Sensor
Color Technique	Ultra-Fine™ Color Engine/NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Two-stage TE-cooling System -45 °C below Camera Body Temperature

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port External Power Adapter for Cooling System, DC12V, 3A

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 10 (32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory:2GB or More
	USB Port:USB3.0 High-speed Port
	Display:17" or Larger
	CD-ROM

9.2.3 T3CMOS Dimension

The T3CMOS body, made from tough, alloy with CNC technique, ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT or AR to block the IR light or protect the camera sensor. The fan's vibration is minimized to the low level to eliminate the vibration caused imaging blur. This design ensures a rugged, robust solution with an increased lifespan when compared to the other industrial camera solutions.



Dimension of T3CMOS

9.2.4 Packing Information for T3CMOS Camera



Packing Information of T3CMOS Camera

Standard Package

A	Carton L:50cm W:30cm H:30cm (20pcs, 12~17Kg/ carton), not shown in the photo(TBD)
B	3-A safety equipment case: L:28cm W:23cm H:15cm (1pcs, 2.8Kg/ box); Carton size:L:28.2cm W:25.2cm H:16.7cm(TBD)
C	T3CMOS camera(C-mount)
D	Drying tube and desiccant
E	Power adapter: input: AC 100~240V 50Hz/60Hz, output: DC12 V 3A
F	High-Speed USB3.0 A male to B male gold-plated connectors cable /1.5m
G	CD (Driver & utilities software, Ø12cm)

Optional Accessory

H	Adjustable lens adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075 108004/AMA100
		C-Mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075 108011/ATA100
I	Fixed lens Adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075 108008/FMA100
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075 108014/FTA100

J	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube
K	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube
L	Calibration kit 106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)

9.2.5 Extension of T3CMOS with Microscope Adapter




T3CMOS+AMAXXX(23.2mm Adapter)




T3CMOS+FMAXXX(23.2mm Adapter)

9.2.6 Sample Photos Captured with T3CMOS Camera



Hot noise for the T3CMOS at Gain 20 , 600 second, 15 Centidegree



Hot noise for the T3CMOS Gain 20 , 600 second, minus 15 Centidegree

9.3 BigEye Series M42 and M42 to C or F Mount USB3.0 CMOS Camera

9.3.1 Characteristic

- Large scientific CMOS sensor (SONY or GSENSE Back-illuminated CMOS sensor);
- Wide spectrum range, some models even have high response in the ultra-violet to infrared wavelength;
- Real-time 8/12bit depth switch(depending on sensor);
- Ultra-fine™ HISP VP and USB3.0 5 Gbps interface ensuring high frame rates(Up to 30 frames for 10M resolution);
- Ultra low noise and low power dissipation by using column-parallel A/D conversion;
- With hardware resolution from 4.2M to 10.3M;
- Rolling Shutter or Global Shutter;
- Standard M42 mount and M42 to C-mount or F-mount;
- CNC aluminum alloy housing;
- With advanced video & image processing application ToupView;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.Net, DirectShow, Twain;



BigEye's different views



BigEye+F-mount

BigEye + F-mount+Lens



BigEye with F-mount+Lens




BigEye with F-mount and Lens


9.3.2 BigEye Datasheet (3)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Sensitivity Dark Signal	FPS/Resolution	Binning	Exposure
BigEye10000KPA BP91000A (New)	10.3M/IMX294(C) 4/3 "(17.47x12.86)	4.63 x4.63	419mv with 1/30s 0.12mv with 1/30s	30@3704x2778 34.5@4096x2160 39.5@2760x2072 62@2048x1080 86@1360x720	1x1, 1x1, 1x1, 2x2, 3x3	0.1ms~15s
BigEye4200KMA BM94200A (New)	4.2M/GSENSE2020S(M,RS or GS) 1.2"(13.31x13.31)	6.5x 6.5	8.1×10^7 (e- /((W/m ²).s)) Peak QE 64.2% @595nm DS	45@2048x2046 45@1024 x 1023	1x1 2x2	0.01ms~1000s
BigEye4200KMB BM94200B (New)	4.2M/GSENSE2020BSI(M,UV, RS GS) 1.2"(13.31x13.31)	6.5 x 6.5	1.1×10^8 (e- /((W/m ²).s)) Peak QE 93.7% @595nm	22@2048 x2046 22@1024 x1023	1x1 2x2	0.01ms~1000s

C: Color; M: Monochrome; GS: Global Shutter, UV: Good UV response



Spectral response of GSENSE2020e and GSENSE2020s



Spectral Response of GSENSE2020BSI

Other Specification for BigEye Camera

Spectral Range	200-1100nm (UV without IR-cut Filter) or 400-900nm
White Balance	ROI White Balance/ Manual Temp Tint Adjustment/NA for Monochromatic Sensor
Color Technique	Ultra-fine™ HISPV /NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Natural

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 /10 (32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory: 2GB or More
	USB Port: USB3.0 High-speed Port
	Display: 17" or Larger CD-ROM

9.3.3 Dimension of BigEye

The BigEye body, made from tough, CNC aluminum alloy, ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT or AR glass to protect the camera sensor. No moving parts included. This design ensures a rugged, robust solution with an increased lifespan when compared to other industrial camera solutions.



Dimension of BigEye with M42x0.75 or F-mount Interface

9.3.4 Packing Information for BigEye



Packing Information of BigEye Series camera

Standard Camera Packing List

A	Carton L:52cm W:32cm H:33cm (20pcs, 12~17Kg/ carton), not shown in the photo
B	Gift box L:15cm W:15cm H:10cm (0.58~0.6Kg/ box)
C	BigEye series USB3.0 C-mount CMOS camera
D	High-speed USB3.0 A male to B male gold-plated connectors cable /2.0m
E	CD (Driver & utilities software, Ø12cm)

Optional Accessory

F	M42x0.75mm-mount to C-mount converter (If C-mount adapter is used)
G	M42x0.75mm-mount to F-mount converter (If F-mount lens is used)
H	Phototube to M42x0.75 mount adapter (U-TV1.2XT2) for Olympus microscope
I	Phototube to M42x0.75 mount adapter (MQD42120 MBB42120) for Nikon microscope
J	Phototube to M42x0.75 mount adapter (P95-T2 4/ P95-C 1" 1.0 x 3" 1.2x) for Zeiss Primo Star series , Zeiss Primo vert series microscope
K	Phototube to M42x0.75 mount adapter (11541510-120 HT2-1.2X) for Leica microscope
L	Phototube to M42x0.75 mount adapter (60N-T2 4/3" 1.2x) for Zeiss Axio series microscope
Note: For 4/3" sensor, 1.2X adapter with M42x0.75 mount should be chosen, for the 1.2" sensor, 1.0X adapter with C-mount could be used to get the better FOV;	
M	Calibration kit 106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)

9.4 I3 Series C-mount USB3.0 CMOS Camera with Hardware ISP

9.4.1 I3 Basic Characteristic

The basic characteristic of I3 cameras are as follows:

- Including I3ISPM (Color, GS) and I3CMOS (Mono, GG) series;
- , SONY Exmor R(**Back-illuminated**) C-mount CMOS sensor with USB3.0 interface;
- Real-time 8/12bit depth switch(depending on sensor);
- Ultra-fine™ HISP VP and USB3.0 5 Gbps interface ensuring high frame rates(Up to 17 frames for 21M Resolution);
- Ultra low noise and low power dissipation by using column-parallel A/D conversion;
- With hardware resolution among 0.5M to 5M;
- Support hardware/software triggering, free running mode;
- Support firmware updating;
- CNC aluminum alloy housing;
- With advanced video & image processing application ToupView;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.Net, DirectShow, Twain, LabView



9.4.2 I3CMOS Datasheet (6)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Sensitivity Dark Signal	FPS/Resolution	Binning	Exposure
I3CMOS00500KMA IM700500A(New)	0.5M/Sony IMX433LLJ 1/1.7" (7.31x5.58)	9.0x9.0	8100mv with 1/30s 0.30mv with 1/30s	166.5fps@812 × 620	1x1	15us~5s
I3CMOS01500KMA IM701500A(New)	1.5M/ Sony IMX273LLR 1/2.9" (4.97x3.73)	3.45×3.45	1830mv with 1/30s 0.19mv with 1/30s	226.5@1440 × 1080 506@720 × 540	1x1 2x2	15us~5s
I3CMOS03100KMA IM703100A(New)	3.1M/ Sony IMX252LLR 1/1.8" (7.07x5.30)	3.45×3.45	1830mv with 1/30s 0.15mv with 1/30s	110@2048 × 1536 235@1024 × 768	1x1 1x1	15us~5s
I3CMOS03100KMB IM703100B(New)	3.1M/ Sony IMX265LLR 1/1.8" (7.07x5.30)	3.45×3.45	1830mv with 1/30s 0.15mv with 1/30s	55.6@2048 × 1536 116.6fps@1024 × 768	1x1 1x1	15us~5s
I3CMOS05000KMA IM705000A	5.0M/ Sony IMX250LLR 2/3" (8.45x7.07)	3.45×3.45	1830mv with 1/30s 0.15mv with 1/30s	71@2448 × 2048 175.8@1224 × 1024	1x1 1x1	15us~5s
I3CMOS05000KMB IM705000B	5.0M/ Sony IMX264LLR 2/3" (8.45x7.07)	3.45×3.45	1830mv with 1/30s 0.15mv with 1/30s	35.7@2448 × 2048 88.4@1224 × 768	1x1 1x1	15us~5s

9.4.3 I3ISPM Datasheet (6)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Sensitivity Dark Signal	FPS/Resolution	Binning	Exposure
I3ISPM00500KPA IP800500A(New)	0.5M/IMX433LQJ(C,GS) 1/1.7" (7.31x5.58)	9.0x9.0	4610mv with 1/30s 0.3mv with 1/30s	166.5fps@812 × 620	1x1	15us~5s
I3ISPM01500KPA IP801500A(New)	1.5M/IMX273LQR(C,GS) 1/2.9" (4.97x3.73)	3.45×3.45	1146mv with 1/30s 0.15mv with 1/30s	226.5@1440 × 1080 506@720 × 540	1x1 1x1	15us~5s
I3ISPM03100KPA IP803100A(New)	3.1M/IMX252LQR(C,GS) 1/1.8" (7.07x5.30)	3.45×3.45	1146mv with 1/30s 0.15mv with 1/30s	114@2048 × 1536 231@1024 × 768	1x1 1x1	15us~5s
I3ISPM03100KPB IP803100B(New)	3.1M/IMX265LQR(C,GS) 1/1.8" (7.07x5.30)	3.45×3.45	1146mv with 1/30s 0.15mv with 1/30s	55.6@2048 × 1536 116.6fps@1024 × 768	1x1 1x1	15us~5s
I3ISPM05000KPA IP805000A	5.0M/IMX250LQR(C,GS) 2/3" (8.45x7.07)	3.45×3.45	1146mv with 1/30s 0.15mv with 1/30s	71@2448 × 2048 175.8@1224 × 1024	1x1 1x1	15us~5s
I3ISPM05000KPB IP805000B	5.0M/IMX264LQR(C,GS) 2/3" (8.45x7.07)	3.45×3.45	1146mv with 1/30s 0.15mv with 1/30s	35.7@2448 × 1536, 88.4@1224 × 1024	1x1 1x1	15us~5s

C: Color; M: Monochrome; GS: Global Shutter

Other Specification for I3 Camera

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	ROI White Balance/ Manual Temp Tint Adjustment/NA for Monochromatic Sensor
Color Technique	Ultra-fine™ HISPV /NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Running Mode	Free/Software Triggering /External Triggering
Cooling System*	Natural

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port

Software Environment


Operating System	Microsoft® Windows® XP / Vista / 7 / 8 /10 (32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory: 2GB or More
	USB Port: USB3.0 High-speed Port
	Display: 17" or Larger
	CD-ROM

9.4.4 Dimension of I3

The I3 body, made from tough, CNC aluminum alloy, ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT to protect the camera sensor. No moving parts included. This design ensures a rugged, robust solution with an increased lifespan when compared to other industrial camera solutions.



Dimension of I3



Dimension of I3 PC-board

9.4.5 Packing Information for I3



Packing Information of I3

Standard Camera Packing List

A	Carton L:52cm W:32cm H:33cm (20pcs, 12~17Kg/ carton), not shown in the photo
B	Gift box L:15cm W:15cm H:10cm (0.58~0.6Kg/ box)
C	I3 series USB3.0 C-mount CMOS camera
D1	High-speed USB3.0 A male to B male gold-plated connectors cable /3.0m
D2	Lockable high-speed micro USB3.0 cable(Optional)
E	6 Pin I/O cable
F	CD (Driver & utilities software, Ø12cm)

Optional Accessory

G	Adjustable lens adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075 108004/AMA100
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075 108011/ATA100
H	Fixed lens Adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075 108008/FMA100
		C-Mount to Dia.31.75mm Eyepiece Tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075 108014/FTA100

I	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube
J	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube
K	108017(Dia.23.2mm to 31.75mm Ring)/ Adapter rings for 31.75mm eyepiece tube
L	Calibration kit 106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)

9.4.6 Extension of I3 with Microscope or Telescope Adapter

Extension		Picture
C-mount Camera		Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;
Microscope Camera	 I3+AMAXXX(23.2mm Adapter)	 I3+FMAXXX(23.2mm Adapter)
Telescope Camera	 I3+ATAXXX(31.75mm Adapter)	 I3+FTAXXX(31.75mm Adapter)

9.5 E3ISPM Series C-mount USB3.0 CMOS Camera with Hardware ISP and Video Pipeline

9.5.1 E3ISPM Basic Characteristic

E3ISPM adopt SONY Exmor [CMOS](#) sensor as the image-picking device and [USB3.0](#) is used as the transfer interface.

E3ISPM hardware resolutions range from 1.5M to 21M and come with the integrated CNC aluminum alloy compact housing.

E3ISPM integrated with 12 bit Ultra-fine™ Hardware Image Signal Processor Video Pipeline(Ultra-fine™ [HISP VP](#)) for Demosaic, Automatic Exposition, Gain Adjustment, One Push White Balance, Chrominance Adjustment, Saturation Adjustment, Gamma Correction, Luminance Adjustment, Contrast Adjustment, Bayer and finally form RAW data for 8/12 bit output. This will move the heavier burden of the processing from the PC to the Ultra-fine™ [HISP VP](#) and greatly accelerating the processing speed.

E3ISPM comes with advanced video & image processing application ToupView; Providing Windows/Linux/macOS/Android multiple platform SDK (Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc);

The E3ISPM can be widely used in bright field light environment and microscope image capture and analysis with higher frame rate.

The basic characteristic of E3ISPM cameras are as follows:

- SONY Exmor, Exmor R([Back-illuminated](#)), Exmor RS CMOS sensor with [USB3.0](#) interface;
- Real-time 8/12bit depth switch(depending on sensor);
- Ultra-fineTM HISP VP and [USB3.0](#) 5 Gbps interface ensuring high frame rates(Up to 17 frames for 21M Resolution);
- Super high sensitivity up to 1120mV(IMX264);
- Ultra low noise and low power dissipation by using column-parallel A/D conversion;
- With hardware resolution among 1.5M to 21M;
- Rolling Shutter or Global Shutter;
- Standard C-Mount camera;
- CNC aluminum alloy housing;
- With advanced video & image processing application ToupView;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.Net, DirectShow, Twain, LabView



9.5.2 E3ISPM Datasheet (16)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Sensitivity Dark Signal	FPS/Resolution	Binning	Exposure
E3ISPM21000KPA IP121000A(New)	21M/IMX269 (C) 4/3 "(17.4x13.0)	3.3 x3.3	399mv with 1/30s 0.1mv with 1/30s	17@5280x3954 17@3952x3952 56@2640x1976 67@1760x1316 192@584x438	1x1 1x1 2x2 3x3 9x9	0.1ms~15s
E3ISPM20000KPA IP120000A	20M/IMX183(C) 1 "(13.06x8.76)	2.4 x2.4	462mv with 1/30s 0.21mv with 1/30s	15@5440x3648 50@2736x1824 60@1824x1216	1x1 2x2 3x3	0.1ms~15s
E3ISPM18000KPA IP118000A(New)	18M/SONY Special(C) 1/2.2 "(5.86x4.46)	1.2 x1.2	130mv with 1/30s 0.1mv with 1/30s	17@4880x3720 40@2448x1836 50@1728x1296	1x1 2x2 3x3	0.1ms~15s
E3ISPM15600KPA IP115600A(New)	15.6M/SONY Special (C) 1.1 "(13.0x13.0)	3.3 x3.3	399mv with 1/30s 0.1mv with 1/30s	17@3952x3952 56@1976x1976 67@1316x1316	1x1 2x2 3x3	0.1ms~15s
E3ISPM12300KPA IP112300A(New)	12.3M/IMX304(C, GS) 1.1"(14.13x10.35)	3.45x3.45	1146mv with 1/30s 0.1mv with 1/30s	23.4@4096x3000 46.3@2048x1500	1x1 1x1	0.244ms~15s
E3ISPM12000KPA IP112000A	12M/IMX226(C) 1/1.7"(7.40x5.55)	1.85x1.85	280mv with 1/30s 0.1mv with 1/30s	25@4000x3000 50@2048x1080	1x1 2x2	0.1ms~15s
E3ISPM09000KPA IP109000A(New)	9.0M/IMX305(C, GS) 1" (14.13x7.45)	3.45x3.45	1146mv with 1/30s 0.15mv with 1/30s	34@4096x2160 60@2048x1080	1x1 1x1	0.1ms~15s
E3ISPM08300KPA IP108300A(New)	8.3M/IMX274(C) 1/2.5"(6.22x3.50)	1.62x1.62	236mv with 1/30s 0.1mv with 1/30s	32@3840x2160 65@1920x1080	1x1 2x2	0.244ms~15s
E3ISPM08300KPB IP108300B(New)	8.3M/IMX334(C) 1/1.8"(7.68x4.32)	2.0x2.0	505mv with 1/30s 0.1mv with 1/30s	35@3840x2160 60@1920x1080	1x1 2x2	0.02ms~15s
E3ISPM06300KPA IP106300A	6.3M/IMX178(C) 1/1.8" (7.37x4.92)	2.4x2.4	425mv with 1/30s 0.15mv with 1/30s	30@3072 x2048 38@1536x 1024 @8 or 12bit	1x1 2x2	0.1ms~15s
E3ISPM06300KPB IP106300B(New)	6.3M/IMX178(C) 1/1.8" (7.37x4.92)	2.4x2.4	425mv with 1/30s 0.15mv with 1/30s	59@3072 x2048 59@1536x 1024 @8 or10 bit	1x1 2x2	0.02ms~15s
E3ISPM05000KPA IP105000A(New)	5.0M/IMX264(C, GS) 2/3" (8.45x7.07)	3.45x3.45	1146mv with 1/30s 0.15mv with 1/30s	35@2448x2048 50@1224x1024	1x1 1x1	0.1ms~15s
E3ISPM03100KPA IP103100A(New)	3.1M/IMX265(C, GS) 1/1.8" (7.07x5.30)	3.45x3.45	1146mv with 1/30s 0.15mv with 1/30s	53@2048x1536 85@1024x768	1x1 1x1	0.1ms~15s
E3ISPM03100KPB IP103100B	3.1M/IMX123(C) 1/2.8" (5.12x3.84)	2.5x2.5	600mv with 1/30s 0.15mv with 1/30s	50@2048x1536 50@1920x1080	1x1 1x1	0.1ms~15s
E3ISPM02000KPA IP102000A(New)	2M/IMX385(C) 1/2"(7.2x4.05)	3.75x3.75	2350mv with 1/30s 0.15mv with 1/30s	125@1920x1080	1x1	0.1ms~15s
E3ISPM01500KPA IP101500A(New)	1.5M/IMX273(C, GS) 1/2.9" (4.968x3.726)	3.45x3.45	1146mv with 1/30s 0.15mv with 1/30s	164@1440x1080 320@720x540	1x1 2x2	0.1ms~15s

C: Color; M: Monochrome; GS: Global Shutter

Other Specification for E3ISPM Camera

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	ROI White Balance/ Manual Temp Tint Adjustment/NA for Monochromatic Sensor
Color Technique	Ultra-fine™ HISPV /NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Natural

Operating Environment

Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB3.0 Port. Compatible with USB2.0

Software Environment


Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 10 (32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher Memory: 2GB or More

E3ISPM Series C-mount USB3.0 CMOS Camera with Hardware ISP and Video Pipeline

	USB Port: USB3.0 High-speed Port
	Display: 17" or Larger
	CD-ROM

9.5.3 Dimension of E3ISPM

The E3ISPM body, made from tough, CNC aluminum alloy, ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT to protect the camera sensor. No moving parts included. This design ensures a rugged, robust solution with an increased lifespan when compared to other industrial camera solutions.



Dimension of E3ISPM

9.5.4 Packing Information for E3ISPM



Packing Information of E3ISPM

Standard Camera Packing List

- A Carton L:52cm W:32cm H:33cm (20pcs, 12~17Kg/ carton), not shown in the photo
- B Gift box L:15cm W:15cm H:10cm (0.58~0.6Kg/ box)
- C E3ISPM series USB3.0 C-mount CMOS camera
- D High-speed USB3.0 A male to B male gold-plated connectors cable /2.0m
- E CD (Driver & utilities software, Ø12cm)

Optional Accessory

F	Adjustable lens adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075 108004/AMA100
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075 108011/ATA100
G	Fixed lens Adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075 108008/FMA100
		C-Mount to Dia.31.75mm Eyepiece Tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075 108014/FTA100
H	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube		
I	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube		
J	108017(Dia.23.2mm to 31.75mm Ring)/ Adapter rings for 31.75mm eyepiece tube		
K	Calibration kit	106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)	

9.5.5 Extension of E3ISPM with Microscope or Telescope Adapter

Extension	Picture
C-mount Camera	 <p>Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;</p>
Microscope Camera	 <p>E3ISPM+AMAXXX(23.2mm Adapter)</p>  <p>E3ISPM+FMAXXX(23.2mm Adapter)</p>
Telescope Camera	 <p>E3ISPM+ATAXXX(31.75mm Adapter)</p>  <p>E3ISPM+FTAXXX(31.75mm Adapter)</p>

9.6 E3CMOS Series C-mount USB3.0 CMOS Camera

9.6.1 E3CMOS Basic Characteristic

E3CMOS adopt SONY Exmor CMOS sensor as the image-picking device and USB3.0 is used as the data transfer interface.

E3CMOS hardware resolutions range from 0.4M to 20M and come with the integrated CNC aluminum alloy compact housing.

E3CMOS comes with advanced video & image processing application ToupView; Providing Windows/Linux/macOS/Android multiple platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc);

The E3CMOS can be widely used in bright field light environment and microscope image capture and analysis with higher frame rate.

The basic characteristic of E3CMOS cameras are as follows:

- SONY Exmor, Exmor R(**Back-illuminated**), Exmor RS CMOS sensor with USB3.0 interface;
- Real-time 8/12/14/16bit depth switch(depending on sensor);
- Super high sensitivity up to 1120mV(IMX185);
- Ultra low noise and low power dissipation by using column-parallel A/D conversion;
- With hardware resolution among 0.4M to 20M;
- Rolling Shutter or Global Shutter;
- Standard C-Mount camera;
- CNC aluminum alloy housing;
- USB3.0 5 Gbps interface ensuring high frame rates;
- With advanced video & image processing application ToupView;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.Net, DirectShow, Twain, LabView



9.6.2 E3CMOS Datasheet(19)

Order Code	Sensor & Size(mm)	Pixel(μ m)	G Sensitivity Dark Signal	FPS/Resolution	Binning	Exposure
E3CMOS20000KPA EP120000A(Suspended)	20M/IMX183(C) 1 "(13.06x8.76)	2.4 x2.4	462mv with 1/30s 0.21mv with 1/30s	5.5@5440x3648 16@2736x1824 21@1824x1216	1x1, 2x2, 3x3	0.1ms~15s
E3CMOS20000KMA EM120000A(New)	20M/IMX183(M) 1 "(13.06x8.76)	2.4 x2.4	776mv with 1/30s 0.21mv with 1/30s	17.5@5440x3648 40@4080x2160 48@2736x1824 60@1824x1216	1x1, 1x1, 2x2, 3x3	0.1ms~60s
E3CMOS20000KPB EP120000B(New)	20M/IMX147(C) 1/2.3 "(6.24x4.67)	1.2 x1.2	130mv with 1/30s 0.1mv with 1/30s	5.2@5200x3888 15@2592x1944 30@1728x1296	1x1, 2x2, 3x3	0.1ms~15s
E3CMOS12300KMA EM112300A (New)	12.3M/IMX304(M) 1.1 "(14.13x10.35)	3.45 x3.45	1146mv with 1/30s 0.1mv with 1/30s	23.4@4096x3000 46.3@2048x1500	1x1, 1x1,	0.244ms~15s
E3CMOS12000KPA EP112000A	12M/IMX226(C) 1/1.7"(7.40x5.55)	1.85x1.85	280mv with 1/30s 0.1mv with 1/30s	7.1@4000x3000 30@2048x1080	1x1, 2x2	0.244ms~2000ms
E3CMOS06300KPA EP106300A	6.3M/IMX178(C) 1/1.8"(7.37x4.92)	2.4x2.4	425mv with 1/30s 0.15mv with 1/30s	15@3072 x2048 26@1536x 1024	1x1, 2x2	0.244ms~2000ms
E3CMOS06300KMA EM106300A	6.3M/IMX178(M) 1/1.8"(7.37x4.92)	2.4x2.4	425mv with 1/30s 0.15mv with 1/30s	30@3072 x2048 50@1536x 1024	1x1, 2x2	0.244ms~2000ms
E3CMOS05000KPA EP105000A(Suspended)	5.0M/IMX264(C, GS) 2/3" (8.45x7.07)	3.45x3.45	1146mv with 1/30s 0.15mv with 1/30s	15@2448x2048 51@1224x1024	1x1	0.1ms~60s
E3CMOS05000KMA EM105000A	5.0M/IMX264(M, GS) 2/3" (8.45x7.07)	3.45x3.45	915mv with 1/30s 0.15mv with 1/30s	35@2448x2048 60@1224x1024	1x1, 2x2	0.1ms~60s
E3CMOS03100KPA EP103100A(Suspended)	3.1M/IMX036(C) 1/2.8" ((5.12x3.84)	2.5x2.5	200mv with 1/30s 0.5mv with 1/30s	28@2048x1536 28@1024x768	1x1, 2x2	0.244ms ~2000ms
E3CMOS03100KPB EP103100B	3.1M/IMX123(C) 1/2.8" (5.12x3.84)	2.5x2.5	600mv with 1/30s 0.15mv with 1/30s	25@2048x1536 30@1920x1080	1x1	0.244ms~2000ms
E3CMOS03100KMC EM103100C(New)	3.1M/IMX265(M, GS) 1/1.8" (7.07x5.30)	3.45x3.45	1146mv with 1/30s 0.15mv with 1/30s	53@2048x1536 85@1024x768	1x1 1x1	0.1ms~15s
E3CMOS02300KPA EP102300A	2.3M/IMX185(C) 1/1.9" (7.20x4.50)	3.75x3.75	1120mv with 1/30s 0.15mv with 1/30s	38@1920x1200 66@960x600	1x1, 2x2	0.244ms ~2000ms
E3CMOS02300KPB EP102300B	2.3M/IMX249(C, GS) 1/1.2" (11.25x7.03)	5.86x5.86	1016mv with 1/30s 0.15mv with 1/30s	30@1920x1200	1x1	0.244ms~2000ms
E3CMOS02300KMC EM102300C	2.3M/IMX174(M, GS) 1/1.2" (11.25x7.03)	5.86x5.86	1016mv with 1/30s 0.15mv with 1/30s	120@1920x1200	1x1	0.244ms~2000ms
E3CMOS01500KMA EM101500A(New)	1.5M/IMX273(M, GS) 1/2.9" (4.968x3.726)	3.45x3.45	1830mv with 1/30s 0.15mv with 1/30s	228@1440x1080 530@720x540	1x1 2x2	0.1ms~60s
E3CMOS01200KPA EP101200A	1.2M/IMX224(C) 1/3"(4.80x3.60)	3.75 x3.75	2040mv with 1/30s 0.15mv with 1/30s	60@1280x960 120@640x480	1x1, 2x2	0.105ms~15s
E3CMOS00400KPA EP100400A(New)	0.4M/IMX287(C, GS) 1/2.9"(4.97x3.73)	6.9x6.9	4584mv with 1/30s 0.15mv with 1/30s	520@720x540	1x1	0.244ms~15s
E3CMOS00400KMA EM100400A(New)	0.4M/IMX287(M, GS) 1/2.9"(4.97x3.73)	6.9x6.9	7469mv with 1/30s 0.15mv with 1/30s	520@720x540	1x1	0.244ms~15s

C: Color; M: Monochrome; GS: Global Shutter

For the suspended models, customer can choose the corresponding models from E3ISPM series with faster frame rate.

Other Specification for E3CMOS Camera

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	ROI White Balance/ Manual Temp Tint Adjustment/NA for Monochromatic Sensor
Color Technique	Ultra-Fine™ Color Engine/NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Natural

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH

E3CMOS Series C-mount USB3.0 CMOS Camera

Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port
Software Environment	
Operating System	Microsoft® Windows® XP / Vista / 7 / 8 /10 (32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher Memory: 2GB or More USB Port: USB3.0 High-speed Port Display: 17" or Larger CD-ROM

9.6.3 Dimension of E3CMOS

The E3CMOS body, made from tough, CNC aluminum alloy, ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT to protect the camera sensor. No moving parts included. This design ensures a rugged, robust solution with an increased lifespan when compared to other industrial camera solutions.



Dimension of E3CMOS

9.6.4 Packing Information for E3CMOS



Packing Information of E3CMOS

Standard Camera Packing List

- A Carton L:52cm W:32cm H:33cm (20pcs, 12~17Kg/ carton), not shown in the photo
- B Gift box L:15cm W:15cm H:10cm (0.58~0.6Kg/ box)
- C E3CMOS series USB3.0 C-mount CMOS camera
- D High-speed USB3.0 A male to B male gold-plated connectors cable /2.0m
- E CD (Driver & utilities software, Ø12cm)

Optional Accessory

F	Adjustable lens adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075 108004/AMA100
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075 108011/ATA100
G	Fixed lens Adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075 108008/FMA100
		C-Mount to Dia.31.75mm Eyepiece Tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075 108014/FTA100
H	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube		
I	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube		
J	108017(Dia.23.2mm to 31.75mm Ring)/ Adapter rings for 31.75mm eyepiece tube		
K	Calibration kit	106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)	

9.6.5 Extension of E3CMOS with Microscope or Telescope Adapter

Extension	Picture
C-mount Camera	 <p>Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;</p>
Microscope Camera	 <p>E3CMOS+AMAXXX(23.2mm Adapter)</p>  <p>E3CMOS+FMAXXX(23.2mm Adapter)</p>
Telescope Camera	 <p>E3CMOS+ATAXXX(31.75mm Adapter)</p>  <p>E3CMOS+FTAXXX(31.75mm Adapter)</p>

9.7 U3ISPM Series C-mount USB3.0 CMOS Camera with Hardware ISP and Video Pipeline Inside

9.7.1 U3ISPM Basic Characteristic

U3ISPM is an ultra-high performance USB3.0 CMOS camera and it adopts ultra-high performance CMOS sensor as the image-picking device and USB3.0 is used as the data transfer interface.

U3ISPM integrated with 12 bit Ultra-fine™ Hardware Image Signal Processor Video Pipeline(Ultra-fine™ HISP VP) for Demosaic, Adjustments, Automatic Exposition, Gain Adjustment, One Push White Balance, Chrominance Adjustment, Saturation Adjustment, Gamma Correction, Luminance Adjustment, Contrast Adjustment, Bayer and finally form RAW data for 8/12 bit output. This will move the heavier burden of the processing from the PC to the Ultra-fine™ HISP VP and greatly accelerating the processing speed.

U3ISPM comes with advanced video & image processing application ToupView; Providing Windows/Linux/macOS/Android multiple platform SDK (Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc);

The U3ISPM can be widely used in bright field light environment and microscope image capture and analysis with higher frame rate.

The basic characteristic of the U3ISPM cameras are as follows:

- Standard C-Mount camera with [Aptina](#) or [Panasonic](#) CMOS sensor;
- With hardware resolution among 16M to 18M;
- Ultra-fine™ HISP VP and USB3.0 5 Gbps interface ensuring high frame rates(Up to 13 frames for 18M Resolution);
- CNC aluminum alloy housing;
- USB3.0 5 Gbps interface ensuring high frame rate;
- With advanced video & image processing application ToupView;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.NET, DirectShow, Twain Control API;



9.7.2 U3ISPM Datasheet(3)

Order Code	Sensor & Size	Pixel(μm)	G Responsivity Dynamic range SNRmax	FPS/Resolution	Binning	Exposure
U3ISPM18000KPA IP118000A(New)	18M/AR1820(C) 1/2.3"(6.14x4.61)	1.25x1.25	0.62 V/lux-sec 65.8dB 36.3	13.1@4912x3684 34.3@2456x1842 54.4@1228x922	1x1, 2x2, 4x4	0.1ms~2s
U3ISPM16000KPA IP116000A(New)	16M/MN34120(C) 1/2.33"(6.18x4.67)	1.335x1.335	R: 2453LSB Gr: 2444LSB Gb: 1054LSB B: 996LSB	16@4632x3488 30@2320x1740 27@1536x1160	1x1, 2x2, 3x3	0.2ms~2s
U3ISPM16000KPB IP116000B(New)	16M/MN34230(C) 4/3"(17.60x13.30)	3.8x3.8	R: 1315LSB Gr: 2413LSB Gb: 2413LSB B: 1042LSB (Gain = 0dB)	22@4640x3506 30@3360x2526 43@2304x1750 49@1536x1168	1x1, 2x2, 3x3	0.2ms~15s

C: Color; M: Monochrome;

Other Specification for U3ISPM Camera

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	ROI White Balance/ Manual Temp Tint Adjustment/NA for Monochromatic Sensor
Color Technique	Ultra-fine™ HISP VP /NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Natural

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 10 (32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory:2GB or More
	USB Port:USB3..0 High-speed Port
	Display:17" or Larger
	CD-ROM

9.7.3 Dimension of U3ISPM

The U3ISPM body, made from tough, aluminum alloy, ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT to protect the camera sensor. No moving parts included. This design ensures a rugged, robust solution with an increased lifespan when compared to other industrial camera solutions.



Dimension of U3ISPM

9.7.4 Packing Information for U3ISPM



Packing Information of U3ISPM

Standard Camera Packing List

- A Carton L:52cm W:32cm H:33cm (20pcs, 12~17Kg/ carton), not shown in the photo
- B Gift box L:15cm W:15cm H:10cm (0.67~0.7Kg/ box)
- C U3ISPM series USB3.0 C-mount CMOS camera
- D High-speed USB3.0 A male to B male gold-plated connectors cable /2.0m
- E CD (Driver & utilities software, Ø12cm)

Optional Accessory

F	Adjustable lens adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075
G	Fixed lens Adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075
		C-Mount to Dia.31.75mm Eyepiece Tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075

H	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube
I	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube
J	108017(Dia.23.2mm to 31.75mm Ring)/ Adapter rings for 31.75mm eyepiece tube
K	Calibration kit 106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)

9.7.5 Extension of U3ISPM with Microscope or Telescope Adapter

Extension	Picture
C-mount Camera	 <p>Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;</p>
Microscope Camera	  <p>U3ISPM+AMAXXX(23.2mm Adapter) U3ISPM+FMAXXX(23.2mm Adapter)</p>
Telescope Camera	  <p>U3ISPM+ATAXXX(31.75mm Adapter) U3ISPM+FTAXXX(31.75mm Adapter)</p>

9.8 L3CMOS Series C-mount USB3.0 CMOS Camera

9.8.1 L3CMOS Basic Characteristic

L3CMOS is Luxurious USB3.0 CMOS camera with frame buffers and it adopts ultra-high performance CMOS sensor as the image-picking device, and USB3.0 is used as the data transfer interface.

L3CMOS comes with advanced video & image processing application ToupView; Providing Windows/Linux/ OSX multiple platforms SDK; Native C/C++, C#/VB.NET, DirectShow, Twain Control API;

The L3CMOS can be widely used in bright field light environment and microscope image capture and analysis.

The basic characteristic of L3COMS cameras are as follows:

- C-Mount camera has 25.4 mm or 1 inch diameter with 32 threads per inch;
- Scientific research grade camera with Aptina CMOS sensor;
- With hardware resolution among 1.2M to 14M;
- On-board memory for perfect synchronization, higher frame rate and stable performance;
- High performance cooling structure, ensures low image noise;
- USB3.0 5 Gbps interface ensuring high frame rate;
- Ultra-Fine™ color engine with perfect color reproduction capability;
- With advanced video & image processing application ToupView;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.NET, DirectShow, Twain Control API;



9.8.2 L3CMOS Datasheet(5)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Sensitivity Dynamic Range SN Ratio	FPS/Resolution	Binning	Exposure
L3CMOS14000KPA LP114000A	14M/MT9F002(C) 1/2.3“(5.73x4.60)	1.4x1.4	0.724v/lux-sec 65.3dB 35.5dB	6.2@4096x3286 20.8@2048x1644 53.3@1024x822	1x1,2x2,4x4	0.1ms~2000ms
L3CMOS10000KPA LP110000A	10M/MT9J003(C) 1/2.3“ (5.98x4.58)	1.67x1.67	0.31v/lux-sec 65.2dB 34dB	7.2@3584x2746 24.5@1792x1372	1x1,2x2,4x4	0.1ms~2000ms
L3CMOS08500KPA LP108500A	8.5M/Special(C) 1/2.4“ (5.56x4.26)	1.67x1.67	0.31v/lux-sec 65.2dB 34dB	8.3@3328x2548 26.2@1664x1272	1x1,2x2,4x4	0.1ms~2000ms
L3CMOS05100KPA LP105100A	5.1M/MT9P006(C) 1/2.5“ (5.63x4.23)	2.2x2.2	1.76v/lux-sec 67.74dB 38.5dB	14.2@2560x1922 38.3@1280x960 101.2@640x480	1x1,2x2,4x4	0.05ms~2000ms
L3CMOS03100KPA LP103100A	3.1M/AR0330(C) 1/3“ (4.51x3.37)	2.2x2.2	1.9v/lux-sec 100dB 39dB	27.3@2048x1534 53.3@1024x770	1x1, 2x2	0.1ms~2000ms

C: Color; M: Monochrome;

Other Specification for L3CMOS Camera

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	ROI White Balance/ Manual Temp Tint Adjustment/NA for Monochromatic Sensor
Color Technique	Ultra-Fine™ Color Engine/NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Natural with High Performance Cooling Structure

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 /10 (32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory:2GB or More
	USB Port:USB3.0 High-speed Port
	Display:17” or Larger
	CD-ROM

9.8.3 Dimension of L3CMOS

The L3CMOS body, made from tough, aluminum alloy, ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT to protect the camera sensor. No moving parts included. This design ensures a rugged, robust solution with an increased lifespan when compared to other industrial camera solutions.



Dimension of L3CMOS

9.8.4 Packing Information of L3CMOS



Packing Information of L3CMOS

Standard Camera Packing List

A	Carton L:40cm W:36cm H:36cm (16pcs, 12~17Kg/ carton), not shown in the photo
B	Gift box L:16.4cm W:16.4cm H:9.6cm (0.72~0.8Kg/ box)
C	L3CMOS series USB3.0 C-mount CMOS camera
D	High-speed USB3.0 A male to B male gold-plated connectors cable /2.0m
E	CD (Driver & utilities software, Ø12cm)

Optional Accessory

F	Adjustable lens adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075
G	Fixed lens Adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075

H	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube
I	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube
J	108017(Dia.23.2mm to 31.75mm Ring)/ Adapter rings for 31.75mm eyepiece tube
K	Calibration kit 106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)

9.8.5 Extension of L3CMOS with Microscope or Telescope Adapter

Extension	Picture	
C-mount Camera		Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;
Microscope Camera	 	L3CMOS+AMAXXX(23.2mm Adapter) L3CMOS+FMAXXX(23.2mm Adapter)
Telescope Camera	 	L3CMOS+ATAXXX(31.75mm Adapter) L3CMOS+FTAXXX(31.75mm Adapter)

9.9 U3CMOS Series C-mount USB3.0 CMOS Camera

9.9.1 U3CMOS Basic Characteristic

U3CMOS is an ultra-high performance USB3.0 CMOS camera and it adopts ultra-high performance CMOS sensor as the image-picking device and USB3.0 is used as the data transfer interface.

U3CMOS hardware resolutions range from 3.0M to 18M and come with the CNC aluminum alloy compact housing.

U3CMOS comes with advanced video & image processing application ToupView; Providing Windows/Linux/ OSX multiple platforms SDK; Native C/C++, C#/VB.NET, DirectShow, Twain Control API;

The U3CMOS can be widely used in bright field light environment and microscope image capture and analysis with higher frame rate.

The basic characteristic of the U3CMOS cameras are as follows:

- Standard C-Mount camera with Aptina CMOS sensor;
- With hardware resolution among 3.0M to 18M;
- CNC aluminum alloy housing;
- USB3.0 5 Gbps interface ensuring high frame rate;
- With advanced video & image processing application ToupView;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.NET, DirectShow, Twain Control API;



9.9.2 U3CMOS Datasheet(10)

Order Code	Sensor & Size	Pixel(μm)	G Responsivity Dynamic range SNRmax	FPS/Resolution	Binning	Exposure
U3CMOS18000KPA TP118000A(New)	18M/AR1820(C) 1/2.3"(6.14x4.61)	1.25x1.25	0.62 V/lux-sec 65.8dB 36.3	5.6@4912x3684 18.1@2456x1842 32.2@1228x922	1x1,2x2,4x4	0.1ms~2000ms
U3CMOS16000KPA TP116000A(New)	16M/MN34120(C) 1/2.33"(6.18x4.66)	1.335x1.335	R: 2453LSB Gr: 2444LSB Gb: 1054LSB B: 996LSB	6.0@4632x3488 15.0@2320x1740 26.0@1536x1160	1x1, 2x2,3x3	0.2ms~2000ms
U3CMOS16000KPB TP116000B(New)	16M/MN34230PLJ(C) 4/3" (17.60x13.30)	3.8x3.8	R: 1315LSB Gr: 2413LSB Gb: 2413LSB B: 1042LSB (Gain = 0dB)	6.0@4648x3506 15.0@2304x1750 30.0@1536x1168	1x1,2x2,3x3	0.06ms~15s
U3CMOS16000KMB TM116000B(New)	16M/MN34230ALJ(M) 4/3" (17.60x13.30)	3.8x3.8	A: 2650LSB B: 2650LSB C: 2650LSB D: 2650LSB (Gain = 0dB)	22@4640x3506 36@3840x2160 43@2304x1750 43@1920x1080 49@1536x1168	1x1, 1x1, 2x2, 2x2, 3x3	0.224ms~15s
U3CMOS14000KPA TP114000A	14M/MT9F002(C) 1/2.3"(5.73x4.60)	1.4x1.4	0.724v/lux-sec 65.3dB 35.5dB	6.2@4096x3286 20.8@2048x1644 53.3@1024x822	1x1, 2x2,	0.224ms~2000ms
U3CMOS10000KPA TP110000A	10M/MT9J003(C) 1/2.3" (5.98x4.58)	1.67x1.67	0.31v/lux-sec 65.2dB 34dB	7.2@3584x2746 24.5@1792x1372	1x1,2x2,4x4	0.4ms~2000ms
U3CMOS10000KMA TM110000A	10M/MT9J003(M) 1/2.3" (5.98x4.58)	1.67x1.67	0.4v/lux-sec 65.2dB 34dB	7.2@3584x2746 24.5@1792x1372	1x1,2x2,4x4	0.4ms~2000ms
U3CMOS08500KPA TP108500A	8.5M/Special(C) 1/2.4"(5.56x4.26)	1.67x1.67	0.31v/lux-sec 65.2dB 34dB	8.3@3328x2548 26.2@1664x1272	1x1,2x2,4x4	0.1ms~2000ms
U3CMOS05100KPA TP105100A	5.1M/MT9P006(C) 1/2.5" (5.70x4.28)	2.2x2.2	1.76v/lux-sec 67.74dB 38.5dB	14.2@2560x1922 38.3@1280x960 101.2@640x480	1x1,2x2,4x4	0.1ms~2000ms
U3CMOS03100KPA TP103100A	3.1M/AR0330(C) 1/3" (4.51x3.38)	2.2x2.2	1.9v/lux-sec 100dB 39dB	27.3@2048x1534 53.3@1024x770	1x1, 2x2	0.1ms~2000ms

C: Color; M: Monochrome;

Other Specification for U3CMOS Camera

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	ROI White Balance/ Manual Temp Tint Adjustment/NA for Monochromatic Sensor
Color Technique	Ultra-Fine™ Color Engine/NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Natural

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 /10 (32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory:2GB or More
	USB Port:USB3..0 High-speed Port
	Display:17" or Larger
	CD-ROM

9.9.3 Dimension of U3CMOS

The U3CMOS body, made from tough, aluminum alloy, ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT to protect the camera sensor. No moving parts included. This design ensures a rugged, robust solution with an increased lifespan when compared to other industrial camera solutions.



Dimension of U3CMOS

9.9.4 Packing Information for U3CMOS



Packing Information of U3CMOS

Standard Camera Packing List

- A Carton L:52cm W:32cm H:33cm (20pcs, 12~17Kg/ carton), not shown in the photo
- B Gift box L:15cm W:15cm H:10cm (0.67~0.7Kg/ box)
- C U3CMOS series USB3.0 C-mount CMOS camera
- D High-speed USB3.0 A male to B male gold-plated connectors cable /2.0m
- E CD (Driver & utilities software, Ø12cm)

Optional Accessory

F	Adjustable lens adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075
G	Fixed lens Adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075
		C-Mount to Dia.31.75mm Eyepiece Tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075
H	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube		
I	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube		
J	108017(Dia.23.2mm to 31.75mm Ring)/ Adapter rings for 31.75mm eyepiece tube		
K	Calibration kit	106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)	

9.9.5 Extension of U3CMOS with Microscope or Telescope Adapter

Extension	Picture
C-mount Camera	 <p>Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;</p>
Microscope Camera	 <p>U3CMOS+AMAXXX(23.2mm Adapter)</p>  <p>U3CMOS+FMAXXX(23.2mm Adapter)</p>
Telescope Camera	 <p>U3CMOS+ATAXXX(31.75mm Adapter)</p>  <p>U3CMOS+FTAXXX(31.75mm Adapter)</p>

9.10 C3CMOS Series C-mount USB3.0 CMOS Camera

C3CMOS Basic Characteristic

C3CMOS is a Compact & high performance USB3.0 CMOS camera, it adopts Sony or OnSemi CMOS sensor as the image-picking device and USB3.0 is used as the data transfer interface.

C3CMOS hardware resolutions range from 3.5M to 10M and come with the compact CNC aluminum alloy housing.

C3CMOS comes with advanced video & image processing application ToupView; Providing Windows/Linux/ OSX multiple platforms SDK; Native C/C++, C#/VB.NET, DirectShow, Twain Control API;

The C3CMOS can be widely used in bright field light environment and microscope image capture and analysis with higher frame rate.

The basic characteristic of the C3CMOS cameras are as follows:

- Standard C-Mount camera with Sony or OnSemi CMOS sensor;
- With hardware resolution among 3.5M to 10M;
- Compact CNC aluminum alloy housing;
- USB3.0 5 Gbps interface ensuring high frame rate;
- Ultra-Fine™ color engine with perfect color reproduction capability;
- With advanced video & image processing application ToupView;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.NET, DirectShow, Twain Control API;



9.10.1C3CMOS Datasheet(4)

Order Code	Sensor & Size	Pixel(μm)	G Responsivity Dynamic range SNRmax	FPS/Resolution	Binning	Exposure
C3CMOS10000KPA CP110001A 20190518	10M/MT9J003(C) 1/2.3" (5.98x4.58)	1.67x1.67	0.31v/lux-sec 65.2dB 34dB	7.2@3664x2748 23.8@1832x1374 77.4@912x686	1x1 2x2 4x4	0.1ms~2000ms
C3CMOS05100KPA CP105100A 20181030	5.1M/MT9P006(C) 1/2.5" (5.70x4.28)	2.2x2.2	1.76v/lux-sec 67.74dB 38.5dB	14.0@2592x1944 29.4@1280x960 103.1@640x480	1x1 2x2 4x4	0.1ms~2000ms
C3CMOS05100KPB CP105100B 20200118	5.1M/IMX335(C) 1/2.8" (5.18x3.89)	2.0x2.0	505mV 70dB 43dB	20@2592x1944 40@1296x972	1x1 2x2	0.1ms~2000ms
C3CMOS03500KPA CP103500A 20200118	3.5M/SC4236(C) 1/2.6" (5.76x3.84)	2.5x2.5	3.0v/lux-sec 72dB 37dB	30@2304x1536 30@1152x768	1x1	0.1ms~2000ms

C: Color; M: Monochrome;

Other Specification for C3CMOS Camera

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	ROI White Balance/ Manual Temp Tint Adjustment/NA for Monochromatic Sensor
Color Technique	Ultra-Fine™ Color Engine/NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Natural

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 10 (32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory:2GB or More
	USB Port: USB3.0 High-speed Port
	Display:17" or Larger
	CD-ROM

9.10.2 Dimension of C3CMOS

The C3CMOS body, made from tough, aluminum alloy, ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT to protect the camera sensor. No moving parts included. This design ensures a rugged, robust solution with an increased lifespan when compared to other industrial camera solutions.



Dimension of C3CMOS

9.10.3 Packing Information for C3CMOS



Packing Information of C3CMOS

Standard Camera Packing List

- A Carton L:52cm W:32cm H:33cm (20pcs, 12~17Kg/ carton), not shown in the photo
- B Gift box L:15cm W:15cm H:10cm (0.67~0.7Kg/ box)
- C C3CMOS series USB3.0 C-mount CMOS camera
- D High-speed USB3.0 A male to B male gold-plated connectors cable /2.0m
- E CD (Driver & utilities software, Ø12cm)

Optional Accessory

F	Adjustable lens adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075
G	Fixed lens Adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075
		C-Mount to Dia.31.75mm Eyepiece Tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075
H	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube		
I	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube		
J	108017(Dia.23.2mm to 31.75mm Ring)/ Adapter rings for 31.75mm eyepiece tube		
K	Calibration kit	106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)	

9.10.4 Extension of C3CMOS with Microscope or Telescope Adapter

Extension	Picture	
C-mount Camera		Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;
Microscope Camera	 C3CMOS+AMAXXX(23.2mm Adapter)	 C3CMOS+FMAXXX(23.2mm Adapter)
Telescope Camera	 C3CMOS+ATAXXX(31.75mm Adapter)	 C3CMOS+FTAXXX(31.75mm Adapter)

9.11 S3CMOS Series USB3.0 Eyepiece Camera

9.11.1 S3CMOS Characteristic

S3CMOS is an economic version with simple and compact structure USB3.0 CMOS eyepiece camera. So here, the S means simple and compact. USB3.0 is used as the data transfer interface.

Microscope eyepiece camera with 23.2 diameter and compact size;

The S3CMOS comes with high-speed USB3.0 interface and high frame rate video display keep the screen smooth without interruption;

Also the S3CMOS comes with advanced video & image processing application ToupView;

The S3CMOS can be widely used to transfer the mono or binocular student microscopes to digital microscope.

With 23.2 to 30mm or 23.2 to 30.75 convert ring, the S3CMOS camera can also change the stereo microscope to digital stereo microscope.

The basic characteristic of S3CMOS cameras are as follows:

- Microscope eyepiece camera with 23.2 diameter and compact size;
- Easy to extend to C or CS-Mount camera with high quality lens(optional);
- High-quality camera with Aptina CMOS sensor;
- Auto white balance and auto-exposure; Brightness, contrast, chroma, and saturation can be adjusted;
- High-speed USB3.0 interface and high frame rate video display keep the screen smooth without interruption;
- With advanced video & image processing application ToupView;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.NET, DirectShow, Twain Control API;



9.11.2 S3CMOS Datasheet(2)

Order Code	Sensor & Size	Pixel(μm)	G Responsivity Dynamic range SNRmax	FPS/Resolution	Binning	Exposure
S3CMOS05000KPA TP305000A	5.0M/MT9P001(C) 1/2.5"(5.70x4.28)	2.2x2.2	0.53 V/lux-sec 66.5dB 40.5dB	15@2560x1920 15@2048x1536 30@1920x1080	1x1,2x2	Auto
S3CMOS05000KPC TP305000C(New)	5.0M/SC5033(C) 1/2.7"(5.18x3.89)	2.0x2.0	2 V/lux-sec 64dB 35dB	15@2592x1944 20@2048x1536 20@1600x1200 30@800x600	1x1,2x2	Auto

C: Color; M: Monochrome;

Other Specification for S3CMOS Camera

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	Auto White Balance
Color Technique	N/A
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Natural

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB3.0 Port

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 10 (32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory:2GB or More
	USB Port:USB3.0 High-speed Port
	Display:17" or Larger
	CD-ROM

9.11.3 Dimension of S3CMOS

The S3CMOS body, made from aluminum alloy blackening, ocular housing: Dia.32 X 56mm ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT filter to filter the infrared light and protect the camera sensor. No moving parts included. This design ensures a rugged, robust solution with an increased lifespan when compared to other industrial camera solutions.



Dimension of S3CMOS

9.11.4 Packing Information for S3CMOS



Packing Information of S3CMOS

Standard Camera Packing List	
A	Carton L:52cm W:32cm H:33cm (20pcs, 12~17Kg/ carton), not shown in the photo
B	Gift box L:15cm W:15cm H:10cm (0.25~0.35Kg/ box)
C	S3CMOS series camera
D	High-Speed USB3.0 USB315-ATA USB 3.0 A Male to A Male Cable,1.5m
E	CD (Driver & utilities software, Ø8cm)
Optional Accessory	
F	C-Mount Adapter Housing:108027(HS502)
G	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube
H	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube
I	108017(Dia.23.2mm to 31.75mm Ring)/ Adapter rings for 31.75mm eyepiece tube
J	Calibration kit 106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)

10 Microscope USB2.0 CMOS Camera

10.1 ECMOS Series C-mount USB2.0 CMOS Camera

10.1.1 ECMOS Basic Characteristic

ECMOS adopt SONY Exmor CMOS sensor as the image-picking device and USB2.0 is used as the data transfer interface.

ECMOS hardware resolutions range from 1.2M to 8.3M and come with the integrated CNC aluminum alloy compact housing.

ECMOS comes with advanced video & image processing application ToupView; Providing Windows/Linux/ OSX multiple platforms SDK; Native C/C++, C#/VB.NET, DirectShow, Twain Control API;

The ECMOS can be widely used in bright field light environment and microscope image capture and analysis with higher frame rate.

The basic characteristic of ECMOS cameras are as follows:

- SONY Exmor, Exmor R(**Back-illuminated**), Exmor RS CMOS sensor with USB2.0 interface;
- Real-time 8/12/14/16bit depth switch(depending on sensor);
- Super high sensitivity up to 2040mV(IMX224);
- Ultra low noise and low power dissipation by using column-parallel A/D conversion;
- With hardware resolution among 1.2M to 8.3M;
- Rolling Shutter;
- Standard C-Mount camera;
- CNC aluminum alloy housing;
- USB2.0 interface ensuring high speed data transmission;
- With advanced video & image processing application ToupView;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.Net, DirectShow, Twain;



10.1.2 ECMOS Datasheet (7)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Sensitivity Dark Signal	FPS/Resolution	Binning	Exposure
ECMOS08300KPA EP608300A(New)	8.3M/IMX274(C) 1/2.5"(6.22x3.50)	1.62x1.62	236mv with 1/30s 0.1mv with 1/30s	4@3840x2160 16@1920x1080	1x1 2x2	0.244ms~15s
ECMOS06600KPA EP606600A(New)	6.6M/IMX326(C) 1/2.9"(4.98x3.50)	1.62x1.62	236mv with 1/30s 0.1mv with 1/30s	5@3072x2160 6@2592x1944 6@3072x1728 7@2160x2160	1x1 1x1 1x1 1x1	0.244ms~15s
ECMOS05300KPA EP605300A	5.3M/IMX178(C) 1/1.9"(7.37x4.15)	2.4x2.4	425mv with 1/30s 0.15mv with 1/30s	5.5@3072 x1728 35@1280x720	1x1, 2x2	0.105ms~15s
ECMOS05000KPA EP605000A(New)	5.0M/IMX335(C) 1/2.8"(5.18x3.89)	2.0x2.0	505mv with 1/30s 0.13mv with 1/30s	6.4@2592 x1944 26.7@1296x972	1x1, 2x2	0.1ms~15s
ECMOS03100KPA EP603100A	3.1M/IMX123(C) 1/2.8"(5.12x3.84)	2.5x2.5	600mv with 1/30s 0.15mv with 1/30s	10.5@2048x1536 15@1920x1080	1x1	0.105ms~15s
ECMOS02000KPA EP602000A	2.0M/IMX290(C) 1/2.8"(5.56x3.13)	2.9 x2.9	1300mv with 1/30s 0.15mv with 1/30s	17@1920x1080	1x1	0.105ms~15s
ECMOS01200KPA EP601200A	1.2M/IMX224(C) 1/3"(4.80x3.60)	3.75 x3.75	2040mv with 1/30s 0.15mv with 1/30s	27@1280x960 54@640x480	1x1, 2x2	0.105ms~15s

C: Color; M: Monochrome;

Other Specification for ECMOS Camera

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	ROI White Balance/ Manual Temp Tint Adjustment/NA for Monochromatic Sensor
Color Technique	Ultra-Fine™ Color Engine/NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Natural

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 10 (32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher Memory: 2GB or More USB Port: USB2.0 Port Display: 17" or Larger CD-ROM

10.1.3 Dimension of ECMOS

The ECMOS body, made from tough, CNC aluminum alloy, ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT to protect the camera sensor. No moving parts included. This design ensures a rugged, robust solution with an increased lifespan when compared to other industrial camera solutions.



Dimension of ECMOS

10.1.4 Packing Information for ECMOS



Packing Information of ECMOS

Standard Camera Packing List

- A Carton L:52cm W:32cm H:33cm (20pcs, 12~17Kg/ carton), not shown in the photo
- B Gift box L:15cm W:15cm H:10cm (0.5~0.55Kg/ box)
- C ECMOS series USB2.0 C-mount CMOS camera
- D High-speed USB2.0 A male to B male gold-plated connectors cable /2.0m
- E CD (Driver & utilities software, Ø12cm)

Optional Accessory

F	Adjustable lens adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075
G	Fixed lens Adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075
		C-Mount to Dia.31.75mm Eyepiece Tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075
H	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube		
I	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube		
J	108017(Dia.23.2mm to 31.75mm Ring)/ Adapter rings for 31.75mm eyepiece tube		
K	Calibration kit	106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)	

10.1.5 Extension of ECMOS with Microscope or Telescope Adapter

Extension	Picture	
C-mount Camera		Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;
Microscope Camera	 ECMOS+AMAXXX(23.2mm Adapter)	 ECMOS+FMAXXX(23.2mm Adapter)
Telescope Camera	 ECMOS+ATAXXX(31.75mm Adapter)	 ECMOS+FTAXXX(31.75mm Adapter)

10.2 LCMOS Series C-mount USB2.0 CMOS Camera

10.2.1 LCMOS Characteristic

LCMOS is luxurious USB2.0 CMOS camera with frame buffers and it adopts ultra-high performance CMOS sensor as the image-picking device, and USB2.0 is used as the data transfer interface.

LCMOS comes with advanced video & image processing application ToupView; Providing Windows/Linux/OSX multiple platform SDK; Native C/C++, C#/VB.NET, DirectShow, Twain Control API;

The LCMOS can be widely used in bright field environment and microscope image capture and analysis with moderate speed.

The basic characteristic of L3CMOS cameras are as follows:

- Stand C-Mount camera with Aptina CMOS sensor;
- With hardware resolution among 1.2M to 14M;
- On-board memory for perfect synchronization, higher frame rate and stable performance;
- High performance cooling structure, ensures low image noise;
- USB2.0 interface ensuring high speed data transmission;
- Ultra-Fine™ color engine with perfect color reproduction capability;
- With advanced video & image processing application ToupView;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.NET, DirectShow, Twain Control API;



10.2.2 LCMOS Datasheet (10)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Responsivity Dynamic range SNRmax	FPS/Resolution	Binning	Exposure
LCMOS14000KPA LP614000A	14M/MT9F002(C) 1/2.3"(5.73x4.60)	1.4x1.4	0.724v/lux-sec 65.3dB 35.5dB	2.7@4096x3288 10@2048x1644 35@1024 x822	1x1, 2x2, 4x4	0.4ms~2000ms
LCMOS10000KPA LP610000A	10M/MT9J003(C) 1/2.3"(5.98x4.59)	1.67x1.67	0.31v/lux-sec 65.2dB 34dB	3.7@3584x2748 13@1792x1374 35@896 x684	1x1, 2x2, 4x4	0.4ms~2000ms
LCMOS09000KPB LP609000B	9M/Special(C) 1/2.4"(5.83x4.37)	1.67x1.67	0.31v/lux-sec 65.2dB 34dB	3.9@3488x2616 15@1744x1308 47@872 x654	1x1, 2x2, 4x4	0.4ms~2000ms
LCMOS08000KPB LP608000B	8M/Special(C) 1/2.5"(5.45x4.09)	1.67x1.67	0.31v/lux-sec 65.2dB 34dB	4.4@3264x2448 17@1600x1200 55@800x600	1x1, 2x2, 4x4	0.4ms~2000ms
LCMOS05100KPA LP605100A	5.1M/MT9P001(C) 1/2.5"(5.70x4.28)	2.2x2.2	0.53 V/lux-sec 66.5dB 40.5dB	6.8@2592x1944 18@1280x960 55@640x480	1x1, 2x2, 4x4	0.294ms~2000ms
LCMOS03100KPA LP603100A	3.1M/MT9T001(C) 1/2"(6.55x4.92)	3.2x3.2	1.0 V/lux-sec 61dB 43dB	11.5@2048x1536 32@1024x768 45@680x510	1x1, 2x2, 3x3	0.244ms~2000ms
LCMOS03100KPB LP603100B	3.1M/IMX036(C) 1/2.8"(5.12x3.84)	2.5x2.5	200mv with 1/30s 0.5mv with 1/30s	12@2048x1536 48@1024x768 48@680x510	1x1, 2x2, 3x3	0.244ms~2000ms
LCMOS02000KPB LP602000B	2.0M/Special(C) 1/2.6"(5.12x3.84)	3.2x3.2	1.0 V/lux-sec 61dB 43dB	16@1600x1200 40@800x600	1x1, 2x2	0.244ms~2000ms
LCMOS01300KPA LP601300A	1.3M/MT9M111(C) 1/3"(4.60x3.70)	3.6x3.6	2.1V/lux-sec 68.2dB 45dB	15@1280x1024 26@640x512 48@320x256	1x1, 2x2, 4x4	0.14ms~2000ms
LCMOS01200KPB LP601200B	1.2M/AR0130(C) 1/3"(4.80x3.60)	3.75 x3.75	5.5v/lux-sec 85.3dB 44dB	28@1280x960 30@640x480	1x1, 2x2	0.4ms~2000ms

C: Color; M: Monochrome;

Other Specification for LCMOS Cameras

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	ROI White Balance/ Manual Temp Tint Adjustment/NA for Monochromatic Sensor
Color Technique	Ultra-Fine™ Color Engine/NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Natural with High Performance Cooling Structure

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 10 (32 & 64 bit), OSx(Mac OS X),Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory:2GB or More
	USB Port:USB2.0 High-speed Port
	Display:17" or Larger
	CD-ROM

10.2.3 Dimension of LCMOS

The LCMOS body, made from tough, aluminum alloy, ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT to protect the camera sensor. No moving parts included. This design ensures a rugged, robust solution with an increased lifespan when compared to other industrial camera solutions.



Dimension of LCMOS

10.2.4 Packing Information of LCMOS



Packing Information of LCMOS

Standard Camera Packing List

A	Carton L:40cm W:36cm H:36cm (16pcs, 12~17Kg/ carton), not shown in the photo
B	Gift box L:16.4cm W:16.4cm H:9.6cm (0.7~0.8Kg/ box)
C	LCMOS series USB2.0 C-mount CMOS camera
D	High-speed USB2.0 A male to B male gold-plated connectors cable /2.0m
E	CD (Driver & utilities software, Ø12cm)

Optional Accessory

F	Adjustable lens adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075
G	Fixed lens Adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075
H	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube		
I	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube		
J	108017(Dia.23.2mm to 31.75mm Ring)/ Adapter rings for 31.75mm eyepiece tube		
K	Calibration kit	106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)	

10.2.5 Extension of LCMOS with Microscope or Telescope Adapter

Extension	Picture	
C-mount Camera		Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;
Microscope Camera	 	  LCMOS+AMAXXX(23.2mm Adapter) LCMOS+FMAXXX(23.2mm Adapter)
Telescope Camera	 	  LCMOS+ATAXXX(31.75mm Adapter) LCMOS+FTAXXX(31.75mm Adapter)

10.3 UA Series C-mount USB2.0 CMOS Camera

10.3.1 UA's Basic Characteristic

UA is an Advanced [USB2.0 CMOS](#) camera. It adopts ultra-high performance CMOS sensor as the image-picking up device. USB2.0 is used as the data transfer interface.

UA hardware resolutions ranges from 1.3M to 16M installed in the aluminum alloy CNC compact housing. UA comes with advanced video & image processing application ToupView; Providing Windows/Linux/OSX multiple platform SDK; Native C/C++, C#/VB.NET, DirectShow, Twain Control API; The UA can be widely used in bright field light environment and microscope image capture and analysis with moderate frame rate.

The basic characteristic of UA cameras are as follows:

- Standard C-Mount with Aptina/Panasonic CMOS sensor;
- With hardware resolution among 1.3M to 16M;
- USB2.0 interface ensuring high speed data transmission;
- Ultra-Fine™ color engine with perfect color reproduction capability;
- With advanced video & image processing application ToupView;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.NET, DirectShow, Twain Control API;
- External dedicated on-board buffer to achieve maximum performance of USB2.0
- Compatible with most of the old and new CPU PC;
- Aluminum alloy CNC housing which is the same as that of UCMOS series.



10.3.2UA Datasheet(5)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Responsivity Dynamic range SNRmax	FPS/Resolution	Binning	Exposure
UA1600CA(New) UP901600A	16M/MN34120(C) 1/2.33"(6.18x4.66)	1.335x1.335	R: 2453LSB Gr: 2444LSB Gb: 1054LSB B: 996LSB	2@4632x3488 8@2320x1740 11@1536x1160	1x1 2x2 3x3	0.2ms~2000ms
UA1000CA(New) UP901000A	10M/MT9J003(C) 1/2.3"(5.98x4.59)	1.67x1.67	0.31v/lux-sec 65.2dB 34dB	3.3@3584x2748 11@1792x1374 38@896x684	1x1 2x2 4x4	0.4ms~2000ms
UA510CA(New) UP900510A	5.1M/MT9P006(C) 1/2.5"(5.70x4.28)	2.2x2.2	0.53 V/lux-sec 66.5dB 40.5dB	7@2592x1944 27@1280x960 90@640x480	1x1 2x2 4x4	0.294ms~2000ms
UA310CA(New) UP900310A	3.1M/MT9T001(C) 1/2"(6.55x4.92)	3.2x3.2	1.0 V/lux-sec 61dB 43dB	12@2048x1536 32@1024x768 45@680x510	1x1 2x2 3x3	0.244ms~2000ms
UA130CA(New) UP900130A	1.23M/SC1235(C) 1/3"(4.80x3.60)	3.75x3.75	4.5V/lux-sec 74dB 38dB	25@1280x960 25@1280x720	1x1, 1x1	0.1ms~2000ms

C: Color; M: Monochrome;

Other Specification for UA Camera

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	ROI White Balance/ Manual Temp Tint Adjustment/NA for Monochromatic Sensor
Color Technique	Ultra-Fine™ Color Engine/NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Natural

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 /10 (32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory:2GB or More
	USB Port:USB2.0 High-speed Port
	Display:17" or Larger
	CD-ROM

10.3.3 Dimension of UA

The UA body, made from CNC tough, aluminum alloy, ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT to protect the camera sensor. No moving parts included. This design ensures a rugged, robust solution with an increased lifespan when compared to other industrial camera solutions.



Dimension of UA

10.3.4 Packing Information for UA



Packing Information of UA

Standard Camera Packing List

A	Carton L:52cm W:32cm H:33cm (20pcs, 12~17Kg/ carton), not shown in the photo
B	Gift box L:15cm W:15cm H:10cm (0.5~0.55Kg/ box)
C	UA series USB2.0 C-mount CMOS camera
D	High-speed USB2.0 A male to B male gold-plated connectors cable /2.0m
E	CD (Driver & utilities software, Ø12cm)

Optional Accessory

F	Adjustable lens adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075
G	Fixed lens Adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075
H	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube		
I	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube		
J	108017(Dia.23.2mm to 31.75mm Ring)/ Adapter rings for 31.75mm eyepiece tube		
K	Calibration kit	106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)	

10.3.5 Extension of UA with Microscope or Telescope Adapter

Extension	Picture	
C-mount Camera		Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;
Microscope Camera	 UA+AMAXXX(23.2mm Adapter)	 UA+FMAXXX(23.2mm Adapter)
Telescope Camera:	 UA+ATAXXX(31.75mm Adapter)	 UA+FTAXXX(31.75mm Adapter)

10.4 C2CMOS Series C-mount USB2.0 CMOS Camera

10.4.1 C2CMOS Basic Characteristic

- Standard C-Mount camera with Sony or OnSemi CMOS sensor;
- With hardware resolution among 2.10MP to 12MP;
- USB2.0 interface ensuring high speed data transmission;
- Integrated with large capacity memory chip ensures data synchronous transmission, low latency, high frame rate and stability;
- Compatible with Microsoft USB Video Class protocol and support the third-party software development;
- Built in Ultra-fine hardware ISP engine ensures high color restoration;
 - ❖ Support automatic/manual exposure switching, accurate exposure time control, and real-time adjustment of exposure target area;
 - ❖ Support automatic/manual/ROI white balance;
 - ❖ Support color adjustment/color mode selection/image flipping;
 - ❖ Support histogram adjust/flat field correction/dark field correction/video ROI;
- High performance MJPEG compression algorithm, combined with the unique decoding method of ToupView and image restoration algorithm ensure highest frame rate of USB2.0 camera in the industry. The FPS for 5MP and 8MP can be up to 30FPS; the FPS for 12MP can be up to 15FPS;
- Comply with CE and FCC agreements;
- CNC aluminum alloy housing;
- With advanced video & image processing application ToupView;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Very competitive pricing.



10.4.2C2CMOS Datasheet(6)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Responsivity Dynamic range SNRmax	FPS/Resolution	Binning	Exposure
C2CMOS12000KPA CP212000A 2020年5月量产	12M/IMX577(C) 1/2.3" (5.95x4.71)	1.55x1.55	250LSB 70dB 43dB	15@3840x3040 15@1920x1520 15@960x760	1x1 1x1 1x1	0.1-2000 ms
C2CMOS08300KPA CP208300A 2020年4月量产	8.3M/IMX274(C) 1/2.5" (6.22x3.50)	1.62x1.62	236mV 70dB 43dB	30@3840x2160 30@1920x1080 30@1280x720 30@960x540	1x1 1x1 1x1	0.1-2000 ms
C2CMOS05100KPA CP205100A 2020年1月量产	5.1M/AR0521(C) 1/2.5" (5.70x4.28)	2.2x2.2	18.8ke-/lus 73dB 40dB	30@2592x1944 30@1280x960 30@640x480	1x1 1x1 1x1	0.1-1000 ms
C2CMOS05100KPB CP205100B 2020年3月量产	5.1M/IMX335(C) 1/2.8" (5.18x3.89)	2.0x2.0	505mV 70dB 43dB	25@2592x1944 25@1280x960 25@640x480	1x1 1x1 1x1	0.1-2000 ms
C2CMOS03100KPA CP203100A 2020年1月量产	3.1M/Aptina(C) 1/2.5" (5.73x4.3)	2.8x2.8	18.8ke-/lus 73dB 40dB	30@2048x1536 30@1024x768	1x1 1x1	0.1-1000 ms
C2CMOS02100KPA CP202100A 2020年2月量产	2.1M/IMX307(C) 1/2.8" (5.73x4.3)	2.9x2.9	1300mV 73dB 43dB	38@2048x1536 38@1024x768	1x1 1x1	0.1-2000 ms

C: Color; M: Monochrome;

Other Specification for C2CMOS Camera

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	Auto/Manual/ROI White Balance/Manual Temp Tint Adjustment/NA for Monochromatic Sensor
Color Technique	Ultra-fine hardware ISP engine /NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Natural

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 10 (32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory:2GB or More
	USB Port:USB2.0 High-speed Port
	Display:17" or Larger
	CD-ROM

10.4.3 Dimension of C2CMOS

The C2CMOS body, made from tough, aluminum alloy, ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT to protect the camera sensor. No moving parts included. This design ensures a rugged, robust solution with an increased lifespan when compared to other industrial camera solutions.



Dimension of C2CMOS

10.4.4 Packing Information for C2CMOS



Packing Information of C2CMOS

Standard Camera Packing List

A	Carton L:52cm W:32cm H:33cm (20pcs, 12~17Kg/ carton), not shown in the photo
B	Gift box L:15cm W:15cm H:10cm (0.5~0.55Kg/ box)
C	C2CMOS series USB2.0 C-mount CMOS camera
D	High-speed USB2.0 A male to B male gold-plated connectors cable /2.0m
E	CD (Driver & utilities software, Ø12cm)

Optional Accessory

F	Adjustable lens adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075
G	Fixed lens Adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075
H	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube		
I	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube		
J	108017(Dia.23.2mm to 31.75mm Ring)/ Adapter rings for 31.75mm eyepiece tube		
K	Calibration kit	106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)	

10.4.5 Extension of C2CMOS with Microscope or Telescope Adapter

Extension	Picture	Picture
C-mount Camera		Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;
Microscope Camera	 C2CMOS+AMAXXX(23.2mm Adapter)	 C2CMOS+FMAXXX(23.2mm Adapter)
Telescope Camera:	 C2CMOS+ATAXXX(31.75mm Adapter)	 C2CMOS+FTAXXX(31.75mm Adapter)

10.5 UCMOS Series C-mount USB2.0 CMOS Camera

10.5.1 UCMOS Basic Characteristic

UCMOS is an ultra-high performance [CMOS](#) camera and it adopts ultra-high performance CMOS sensor as the image-picking device. USB2.0 is used as the data transfer interface.

UCMOS hardware resolutions ranges from 0.35M to 14M and comes with the CNC aluminum alloy compact housing. UCMOS comes with advanced video & image processing application ToupView; Providing Windows/Linux/OSX multiple platform SDK; Native C/C++, C#/VB.NET, DirectShow, Twain Control API; The UCMOS can be widely used in bright field light environment and microscope image capture and analysis with moderate frame rate.

The basic characteristic of UCMOS cameras are as follows:

- Standard C-Mount with Aptina CMOS sensor;
- With hardware resolution among 0.35M to 14M;
- CNC aluminum alloy housing;
- USB2.0 interface ensuring high speed data transmission;
- Ultra-Fine™ color engine with perfect color reproduction capability;
- With advanced video & image processing application ToupView;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.NET, DirectShow, Twain Control API;



10.5.2 UCMOS Datasheet(10)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Responsivity Dynamic range SNRmax	FPS/Resolution	Binning	Exposure
UCMOS14000KPA TP614000A	14M/MT9F002(C) 1/2.3"(5.73x4.60)	1.4x1.4	0.724v/lux-sec 65.3dB 35.5dB	1.8@4096x3288 10@2048x1644 27@1024x822	1x1, 2x2, 4x4	0.4ms~2000ms
UCMOS10000KPA TP610000A	10M/MT9J003(C) 1/2.3"(5.98x4.59)	1.67x1.67	0.31v/lux-sec 65.2dB 34dB	1.9@3584x2748 8@1792x1374 27@896x684	1x1, 2x2, 4x4	0.4ms~2000ms
UCMOS09000KPB TP609000B	9M/Special(C) 1/2.4"(5.83x4.37)	1.67x1.67	0.31v/lux-sec 65.2dB 34dB	1.9@3488x2616 8@1744x1308 27@872x654	1x1, 2x2, 4x4	0.4ms~2000ms
UCMOS08000KPB TP608000B	8M/Special(C) 1/2.5"(5.45x4.09)	1.67x1.67	0.31v/lux-sec 65.2dB 34dB	1.9@3264x2448 8@1600x1200 27@800x600	1x1, 2x2, 4x4	0.4ms~2000ms
UCMOS05100KPA TP605100A	5.1M/MT9P006(C) 1/2.5"(5.70x4.28)	2.2x2.2	0.53 V/lux-sec 66.5dB 40.5dB	5@2592x1944 18@1280x960 60@640x480	1x1, 2x2, 4x4	0.294ms~2000ms
UCMOS03100KPA TP603100A	3.1M/MT9T001(C) 1/2"(6.55x4.92)	3.2x3.2	1.0 V/lux-sec 61dB 43dB	8@2048x1536 22@1024x768 43@680x510	1x1, 2x2, 3x3	0.244ms~2000ms
UCMOS02000KPB TP602000B	2.0M/Special(C) 1/2.6"(5.12x3.84)	3.2x3.2	1.0 V/lux-sec 61dB 43dB	16@1600x1200 50@800x600	1x1, 2x2	0.128ms~2000ms
UCMOS01300KPA TP601300A	1.23M/SC1235(C) 1/3"(4.80x3.60)	3.75x3.75	4.5V/lux-sec 74dB 38dB	15@1280x960 15@1280x720	1x1, 1x1	0.14ms~2000ms
UCMOS01300KMA TM601300A	1.3M/MT9M001(M) 1/2"(6.66x5.32)	5.2x5.2	2.1 V/lux-sec 68.2dB 45dB	20@1280x1024	1x1	0.14ms~500ms
UCMOS00350KPA TP600350A	0.35M/MT9V011(C) 1/4"(3.58x2.69)	5.6x5.6	1.9V/lux-sec 60dB 45dB	30@640x480 80@320x240	1x1, 2x2	0.111ms~192ms

C: Color; M: Monochrome;

Other Specification for UCMOS Camera

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	ROI White Balance/ Manual Temp Tint Adjustment/NA for Monochromatic Sensor
Color Technique	Ultra-Fine™ Color Engine/NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Natural

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 10 (32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory:2GB or More
	USB Port:USB2.0 High-speed Port
	Display:17" or Larger
	CD-ROM

10.5.3 Dimension of UCMOS

The UCMOS body, made from tough, aluminum alloy, ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT to protect the camera sensor. No moving parts included. This design ensures a rugged, robust solution with an increased lifespan when compared to other industrial camera solutions.



Dimension of UCMOS

10.5.4 Packing Information for UCMOS



Packing Information of UCMOS

Standard Camera Packing List

A	Carton L:52cm W:32cm H:33cm (20pcs, 12~17Kg/ carton), not shown in the photo
B	Gift box L:15cm W:15cm H:10cm (0.5~0.55Kg/ box)
C	UCMOS series USB2.0 C-mount CMOS camera
D	High-speed USB2.0 A male to B male gold-plated connectors cable /2.0m
E	CD (Driver & utilities software, Ø12cm)

Optional Accessory

F	Adjustable lens adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075
G	Fixed lens Adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075
H	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube		
I	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube		
J	108017(Dia.23.2mm to 31.75mm Ring)/ Adapter rings for 31.75mm eyepiece tube		
K	Calibration kit	106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)	

10.5.5 Extension of UCMOS with Microscope or Telescope Adapter

Extension	Picture	
C-mount Camera		Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;
Microscope Camera	 UCMOS+AMAXXX(23.2mm Adapter)	 UCMOS+FMAXXX(23.2mm Adapter)
Telescope Camera:	 UCMOS+ATAXXX(31.75mm Adapter)	 UCMOS+FTAXXX(31.75mm Adapter)

10.6 SPCMOS Series USB2.0 CMOS Eyepiece Camera with Reduction Lens

10.6.1 SPCMOS Basic Characteristic

SPCMOS is an extension of our SCMOS camera with fixed reduction lens to increase the field of view from the microscope eyepiece tube. The SPCMOS is still an economic version with simple and compact structure CMOS eyepiece camera. So here, the **S** means simple and compact, **P** means plus. USB2.0 is used as the data transfer interface.

The SPCMOS comes with high-speed USB2.0 interface and high frame rate video display keep the screen smooth without interruption;

Also the SPCMOS comes with advanced video & image processing application ToupView;

The SPCMOS can be widely used to transfer the mono or binocular student microscopes to digital microscope.

With 23.2 to 30mm or 23.2 to 30.75 convert ring, the SPCMOS camera can also change the stereo microscope to digital stereo microscope.

The basic characteristic of SPCMOS cameras are as follows:

- Microscope eyepiece camera with 23.2 diameter and compact size;
- An extension of SCMOS camera with fixed reduction lens to ensure the full field of view of the microscope from the eyepiece can be imaged to the CMOS sensor;
- High-quality camera with Aptina CMOS sensor;
- Auto white balance and auto-exposure; Brightness, contrast, chroma, and saturation can be adjusted;
- High-speed USB2.0 interface and high frame rate video display keep the screen smooth without interruption;
- With advanced video & image processing application ToupView;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.NET, DirectShow, Twain Control API;



SPCMOS Eyepiece Camera

10.6.2 SPCMOS Datasheet(5)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Responsivity Dynamic range SNRmax	FPS/Resolution	Binning	Exposure
SPCMOS05000KPA SP50000A	5.0M/Aptina(C) 1/2.5" (5.70x4.28)	2.2x2.2	NA	2@2592x1944 3@2048x1536 5@1600x1200 7.5@1280x1024	N/A	Auto
SPCMOS03000KPA SP503000A	3.0M/Aptina(C) 1/2.7" (4.51x3.38)	2.2x2.2	NA	3@2048x1536 5@1600x1200 7.5@1280x1024	N/A	Auto
SPCMOS02000KPA SP502000A	2.0M/Aptina(C) 1/3.2" (4.48x3.36)	2.8x2.8	NA	5@1600x1200 7.5@1280x1024 7.5@1280x960 20@800x600	N/A	Auto
SPCMOS01300KPA SP501300A	1.3M/Aptina(C) 1/3" (4.60x3.70)	3.6x3.6	NA	7.5@1280x1024 12.5@1024x768 12.5@800x600	N/A	Auto
SPCMOS00350KPA SP500350A	0.35M/Aptina(C) 1/4" (3.58x2.69)	5.6x5.6	NA	30@640x480	N/A	Auto

C: Color; M: Monochrome;

Other Specification for SPCMOS Camera

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	Auto White Balance
Color Technique	N/A
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Natural

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 10 (32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory:2GB or More
	USB Port:USB2.0 High-speed Port
	Display:17" or Larger
	CD-ROM

10.6.3 Dimension of SPCMOS

The SPCMOS body, made from aluminum alloy blackening, ocular housing: Dia.33 X 79.1mm ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT filter to filter the infrared light and protect the camera sensor. No moving parts included. This design ensures a rugged, robust solution with an increased lifespan when compared to other industrial camera solutions.



Dimension of SPCMOS

10.6.4 Packing Information for SPCMOS



Packing Information of SPCMOS

Standard Camera Packing List

A	Carton L:52cm W:32cm H:33cm (20pcs, 12~17Kg/ carton), not shown in the photo
B	Gift box L:15cm W:15cm H:10cm (0.25~0.26Kg/ box)
C	SPCMOS series eyepiece camera
D	High-Speed USB2.0 A male to mini B 5-pin male gold-plated connectors cable /1.5m
E	CD (Driver & utilities software, Ø8cm)

Optional Accessory

F	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube
G	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube
H	108017(Dia.23.2mm to 31.75mm Ring)/ Adapter rings for 31.75mm eyepiece tube
I	Calibration kit 106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)

10.7 SCMOS Series USB2.0 CMOS Eyepiece Camera

10.7.1 SCMOS Characteristic

SCMOS is an economic version with simple and compact structure CMOS eyepiece camera. So here, the S means simple and compact. USB2.0 is used as the data transfer interface.

The SCMOS comes with high-speed USB2.0 interface and high frame rate video display keep the screen smooth without interruption;

Also the SCMOS comes with advanced video & image processing application ToupView;

The SCMOS can be widely used to transfer the mono or binocular student microscopes to digital microscope.

With 23.2 to 30mm or 23.2 to 30.75 convert ring, the SCMOS camera can also change the stereo microscope to digital stereo microscope.

- Microscope eyepiece camera with 23.2 diameter and compact size;
- Easy to extend to C or CS- Mount camera with high quality lens(optional);
- High-quality camera with Aptina CMOS sensor;
- Auto white balance and auto-exposure; Brightness, contrast, chroma, and saturation can be adjusted;
- High-speed USB2.0 interface and high frame rate video display keep the screen smooth without interruption;
- With advanced video & image processing application ToupView;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.NET, DirectShow, Twain Control API;



10.7.2 SCMOS Datasheet (15)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Responsivity Dynamic range SNRmax	FPS/Resolution	Binning	Exposure
The New SCMOS after Jan. 2020						
SCMOS12000KPA TP512000A Available after Apr. 2020	12M/IMX577(C) 1/2.3“(5.95x4.71)	1.55x1.55	250LSB 70dB 43dB	15@3840x3040 15@1920x1520 15@960x760	1x1 1x1 1x1	0.1-2000 ms
SCMOS08300KPA TP508300A	8.3M/IMX274(C) 1/2.5“(6.22x3.50)	1.62x1.62	236mV 70dB 43dB	30@3840x2160 30@1920x1080 30@1280x720 30@960x540	1x1 1x1 1x1	0.1-2000 ms
SCMOS05100KPA TP505100A	5.1M/AR0521(C) 1/2.5“(5.70x4.28)	2.2x2.2	18.8ke-/lus 73dB 40dB	30@2592x1944 30@1280x960 30@640x480	1x1 1x1 1x1	0.1-1000 ms
SCMOS05100KPB TP505100B Available after Feb. 2020	5.1M/IMX335(C) 1/2.8“(5.18x3.89)	2.0x2.0	505mV 70dB 43dB	25@2592x1944 25@1280x960 25@640x480	1x1 1x1 1x1	0.1-2000 ms
SCMOS03100KPA TP503100A	3.1M/Aptina(C) 1/2.5“(5.73x4.3)	2.8x2.8	18.8ke-/lus 73dB 40dB	30@2048x1536 30@1024x768	1x1 1x1	0.1-1000 ms
SCMOS02100KPA TP502100A	2.1M/IMX307(C) 1/2.8“(5.73x4.3)	2.9x2.9	1300mV 73dB 43dB	38@2048x1536 38@1024x768	1x1 1x1	0.1-2000 ms
The SCMOS before Dec. 2019						
SCMOS05000KPA TP505000A	5.0M/Aptina(C) 1/2.5“(5.70x4.28)	2.2x2.2	NA	2@2592x1944 3@2048x1536 5@1600x1200 7.5@1280x1024	N/A	Auto
SCMOS05000KPB TP505000B(NEW)	5.0M/SC5033(C) 1/2.7“(5.18x3.89)	2.0x2.0	2.0V/lux-sec 64dB 35dB	20@2592x1944 20@2048x1536 20@1600x1200 30@800x600	N/A	Auto
SCMOS03000KPA TP503000A	3.0M/Aptina(C) 1/2.7“(4.51x3.38)	2.2x2.2	NA	3@2048x1536 5@1600x1200 7.5@1280x1024	N/A	Auto
SCMOS03000KPB TP503000B(NEW)	3.0M/SmartSens(C) 1/3“(4.10x3.07)	2.0x2.0	2.0V/lux-sec 64dB 35dB	20@2048x1536 20@1600x1200 30@800x600	N/A	Auto
SCMOS02000KPA TP502000A	2.0M/Aptina(C) 1/3.2“(4.48x3.36)	2.8x2.8	NA	5@1600x1200 7.5@1280x1024 20@800x600 22@640x480	N/A	Auto
SCMOS02000KPB TP502000B(NEW)	2.0M/OV2710(C) 1/2.7“(5.76x3.24)	3x3	3.3V/ Lux-sec 69dB 39dB	25@1920x1080 30@1280x1024 30@1280x720	N/A	Auto
SCMOS01300KPA TP501300A	1.3M/Aptina(C) 1/3“(4.60x3.70)	3.6x3.6	NA	7.5@1280x1024 12.5@1024x768 12.5@800x600	N/A	Auto
SCMOS00920KPA TP500A(NEW)	0.92M/BG0703(C) 1/2.7“(5.80x3.28)	4.5x4.5	5.8V/ Lux-sec 65dB 43dB	25@1280x720 25@640x480	N/A	Auto
SCMOS00350KPA TP500350A	0.35M/Aptina(C) 1/4“(3.58x2.69)	5.6x5.6	NA	30@640x480	N/A	Auto

SCMOS05000KPB and **SCMOS03000KPB** have fast speed than **SCMOS05000KPA** and **SCMOS03000KPA**

C: Color; M: Monochrome;

Other Specification for SCOMS Camera

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	Auto/ROI/Manual White Balance(New Model) Auto(Products before 2020)
Color Technique	N/A
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Natural

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60

SCMOS Series USB2.0 CMOS Eyepiece Camera

Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port
Software Environment	
Operating System	Microsoft® Windows® XP / Vista / 7 / 8 /10 (32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory:2GB or More
	USB Port:USB2.0 High-speed Port
	Display:17" or Larger
	CD-ROM

10.7.3 Dimension of SCOMS

The SCMOS body, made from aluminum alloy blackening, ocular housing: Dia.27.2 X 40mm ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT filter to filter the infrared light and protect the camera sensor. No moving parts included. This design ensures a rugged, robust solution with an increased lifespan when compared to other industrial camera solutions.



Dimension of SCMOS

10.7.4 Packing Information for SCMOS



Packing Information of SCMOS

Standard Camera Packing List

A	Carton L:52cm W:32cm H:33cm (50pcs, 12~17Kg/ carton), not shown in the photo
B	Gift box L:14.5cm W:9.5cm H:6.0cm (0.15~0.16Kg/ box)
C	SCMOS series USB2.0 eyepiece camera
D	High-Speed USB2.0 A male to mini B 5-pin male gold-plated connectors cable /1.5m
E	CD (Driver & utilities software, Ø8cm)

Optional Accessory

F	C-Mount Adapter Housing:108027(HS502)
G	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube
H	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube
I	108017(Dia.23.2mm to 31.75mm Ring)/ Adapter rings for 31.75mm eyepiece tube
J	Calibration kit 106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)

11 Microscope WiFi CMOS Camera

11.1 WCAM Series C-mount WiFi CMOS Camera

11.1.1 WCAM Basic Characteristic

WCAM is [WiFi camera](#) and it adopts ultra-high performance CMOS sensor as the image-picking device. WiFi is used as the data transfer interface.

When the WCAM is attached to the eyepiece of a microscope and started, it will and generates a WiFi signal for sending high-resolution images from a microscope to WiFi-enabled devices such as smartphones, tablets, and computers with iOS, Android, OS X, Linux and Windows operating systems, streaming images to up to six devices simultaneously.

The camera includes ToupView images software for quantifying, measuring, and annotating images and for using with an interactive white board. It also works with the free, downloadable Toupviewt app for viewing, capturing, and editing images.

The basic characteristic of WCAM cameras are as follows:

- C-Mount camera has 25.4 mm or 1 inch diameter with 32 threads per inch;
- Scientific research grade camera with Aptina CMOS sensor;
- Sends H.264 encodec high-resolution images from a microscope to WiFi-enabled smartphones, computers, and tablets with iOS, Android, and Windows operating systems;
- Streams images to several devices simultaneously;
- CNC aluminum alloy housing;
- Ultra-Fine™ color engine with perfect color reproduction capability;
- With advanced video & image processing application ToupView(only support simple video viewing capturing for IOS/ android system);
- Custom programmable with SDK provided(Windows/Linux/OS);



11.1.2 WCAM Datasheet (4)

Order Code	Sensor Size(mm)	Pixel(μm)	G Responsivity Dynamic range SNRmax	FPS/Resolution	Binning	Exposure(ms)
WCAM1080PA WP601080A	1080P/IMX222 (C) 1/2.8" (5.38x3.02)	2.8x2.8	510mV with 1/30s 0.15mv with 1/30s	25@1920x1080	1x1	0.059ms~1941ms
WCAM0720PA WP600720A(Suspended)	720P/MT9P001 (C) 1/2.5" (5.63x3.17)	2.2x2.2	1.0 V/lux-sec 61dB 43dB	30@1280x720	2x2	0.21ms~200ms
WCAM0720PB WP600720B	720P/MT9P001 (C) 1/2.5" (5.63x3.17))	2.2x2.2	1.0 V/lux-sec 61dB 43dB	10@1280x720	2x2	Auto Exposure
WCAM0300KPA WP600300KA	0.3M/MT9V011 (C) 1/4" (3.58 x 2.69)	5.6x5.6	1.9V/lux-sec 60dB 45dB	25@640x480	1x1	Auto Exposure

C: Color; M: Monochrome;

Other Specification for WCAM Camera

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	Whole Area White Balance/ Manual Temp Tint Adjustment/NA for Monochromatic Sensor
Color Technique	Ultra-Fine™ Color Engine/NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Natural
Maximum Connected Devices	<=3

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	USB Charger, Not Recommend PC USB Port

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 10 (32 & 64 bit) IOS IPAD or iPhone, Android PAD and Phone
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory:2GB or More
	WiFi Adapter with DHCP Enabled
	Display:17" or Larger
	CD-ROM
PAD	IPAD or PAD with Android System
Mobile Phone	IPhone or Smart Phone with Android System

11.1.3 Dimension of WCAM

The WCAM body, made from tough, aluminum alloy, ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT to protect the camera sensor. No moving parts included. This design ensures a rugged, robust solution with an increased lifespan when compared to other industrial camera solutions.



Dimension of WCAM

11.1.4 Packing Information of WCAM



Packing Information of WCAM

Standard Camera Packing List

- A Carton L:52cm W:32cm H:33cm (20pcs, 11.4~14Kg/ carton), not shown in the photo
- B Gift box L:15cm W:15cm H:10cm (0.57~0.58Kg/ box)
- C WCAM series USB2.0 C-mount CMOS camera
- D High-speed USB2.0 A male to B male gold-plated connectors cable /2.0m(for PC power only) or with USB charger
- E CD (Driver & utilities software, Ø12cm)

Optional Accessory

F	Adjustable lens adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075
G	Fixed lens Adapter	C-mount to Dia.23.2mm eyepiece Tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075
		C-mount to Dia.31.75mm eyepiece Tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075
H	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube		
I	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube		
J	108017(Dia.23.2mm to 31.75mm Ring)/ Adapter rings for 31.75mm eyepiece tube		
K	Calibration kit	106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)	

11.1.5 Extension of WCAM with Microscope or Telescope Adapter

Extension		Picture
C-mount Camera		Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;
Microscope Camera	 WCAM+AMAXXX(23.2mm Adapter)	 WCAM+FMAXXX(23.2mm Adapter)
Telescope Camera	 WCAM+ATAXXX(31.75mm Adapter)	 WCAM+FTAXXX(31.75mm Adapter)

12 Microscope WiFi+USB CMOS Camera

12.1 WUCAM Series C-mount WiFi+USB CMOS Camera

12.1.1 WUCAM's Basic Characteristic

ToupTek WUCAM is a camera that has the WiFi output and USB output. An on-camera switch is used to switch between the WiFi output and USB output.

When WiFi output is available, this camera is used as a WiFi camera and could be connected to mobile devices, such as smart phones, pads and computers. It could work with ToupView app on iOS, Android and windows platform. More than 6 users could connect the camera simultaneously by WiFi connection.

When USB output is available, this camera is used as a USB camera and could support UVC standard. The camera could be used with ToupView or other 3rd part software which could support UVC camera.

The basic characteristic of WUCAM series camera is as follows:

- C-Mount camera has 25.4 mm or 1 inch diameter with 32 threads per inch;
- Scientific research grade camera with Aptina CMOS sensor;
- Switchable USB+WiFi data interface;
- Send MJPEG encodec high-resolution images from camera to WiFi-enabled smartphones, computers, and tablets with iOS, Android, and Windows operating systems;
- Streams images to several devices simultaneously;
- Send MJPEG encodec high-resolution images from camera to USB-enabled computer with UVC standard protocol;
- Ultra-Fine color engine with perfect color reproduction capability;
- With advanced video & image processing application ToupView(only support simple video viewing capturing for IOS/ android system);
- Custom programmable with SDK provided(Windows/Linux/OS)(WiFi);



12.1.2 WUCAM Datasheet (1)

Order Code	Sensor Size(mm)	Pixel(μm)	G Responsivity Dynamic range SNRmax	FPS/Resolution	Binning	Exposure(ms)
WUCAM0720PA WU600720A	720P/MT9P001 (C) 1/2.5" (5.63x3.17)	2.2x2.2	0.53 V/lux-sec 66.5dB 40dB	30@1280x720	2x2	Auto/Manual Exposure

C: Color; M: Monochrome;

Other Specification for WCAM Camera

Output Interface	USB or WiFi(on Camera Switch)
Spectral Range	380-650nm (with IR-cut Filter)
White Balance	Whole Area White Balance/ Manual Temp Tint Adjustment/NA for Monochromatic Sensor
Color Technique	Ultra-Fine™ Color Engine/NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Natural
Maximum Connected Device	6~10

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	USB Charger USB port from PC

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 10 (32 & 64 bit) IOS IPAD or IPhone, Android PAD and Phone
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher Memory:2GB or More WiFi Adapter with DHCP Enabled Display:17" or Larger CD-ROM
PAD	IPAD or PAD with Android System
Mobile Phone	IPhone or Smart Phone with Android System

12.1.3 Dimension of WUCAM

The WUCAM body, made from tough, CNC aluminum alloy, ensures a heavy duty, workhorse solution. The camera is designed with a high-quality IR-CUT filter to protect the camera sensor. No moving parts included. This design ensures a rugged, robust solution with an increased lifespan when compared to other industrial camera solutions.



Dimension of WUCAM

12.1.4 Packing Information of WUCAM



Packing Information of WUCAM



Standard Camera Packing List

A	Carton L:52cm W:32cm H:33cm (20pcs, 11.4~14Kg/ carton, 0.045m ³), not shown in the photo
B	Gift box L:15cm W:15cm H:10cm (0.46~0.47Kg/ box)
C	WUCAM series WiFi+USB2.0 C-mount CMOS camera
D	High-speed USB2.0 A male to B male gold-plated connectors cable /2.0m(for PC power only) or with USB charger
E	CD (Driver & utilities software, Ø12cm)

Optional Accessory

F	Adjustable lens adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075
		C-mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075
G	Fixed lens Adapter	C-mount to Dia.23.2mm eyepiece Tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075
		C-mount to Dia.31.75mm eyepiece Tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075
H	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube		
I	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube		
J	108017(Dia.23.2mm to 31.75mm Ring)/ Adapter rings for 31.75mm eyepiece tube		
K	Calibration kit	106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)	

12.1.5 Extension of WUCAM with Microscope or Telescope Adapter

Extension		Picture
C-mount Camera		Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;
Microscope Camera	 WUCAM+AMAXXX(23.2mm Adapter)	 WUCAM+FMAXXX(23.2mm Adapter)
Telescope Camera	 WUCAM+ATAXXX(31.75mm Adapter)	 WUCAM+FTAXXX(31.75mm Adapter)

13 Industrial USB2.0 CMOS Camera

13.1 ICMOS Series C-mount USB2.0 CMOS Camera

13.1.1 ICMOS Basic Characteristic

ICMOS is an industrial CMOS camera and it adopts ultra-high performance CMOS sensor as the image-picking device. USB2.0 is used as the data transfer interface. Dimensions: 29x29x29 mm excluding lens holder, without optics (metal case) is realized to obey the industrial camera standard.

A 8-pin Hirose HR25-7TR-8PA GPIO connector for trigger, strobe (Optional);

Further, the ICMOS comes with advanced video & image processing application ToupView and providing Windows/Linux/OSX multiple platforms SDK;

Also, native C/C++, C#/VB.NET, DirectShow, Twain Control API are provided.

The ICMOS can be widely used in machine vision and on-line inspection.

The basic characteristic of ICMOS cameras are as follows:

- C-Mount camera with Aptina or OnSemi CMOS sensor;
- Dimensions: 29x29x29 mm excluding lens holder, without optics (metal case);
- 8-pin Hirose HR25-7TR-8PA GPIO connector for trigger, strobe (Optional);
- USB 2.0 interface with screw locks for camera control, data, and power;
- With advanced video & image processing application ToupView;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.NET, DirectShow, Twain Control API;



13.1.2 ICMOS Datasheet(4)

Order Code	Sensor & Size(mm)	Pixel(μm)	G Responsivity Dynamic range SNRmax	FPS/Resolution	Binning	Exposure(ms)
ICMOS14000KPA IP614000A	14M/MT9F002(C) 1/2.3"(5.73x4.60)	1.4x1.4	0.724v/lux-sec 65.3dB 35.5dB	2.7@4096x3288 10@2048x1644 35@1024 x822	1x1, 2x2, 4x4	0.4ms~2000ms
ICMOS10000KPA IP610000A	10M/MT9J003(C) 1/2.3" (5.98x4.59)	1.67x1.67	0.31v/lux-sec 65.2dB 34dB	3.7@3584x2748 13@1792x1374 35@896 x684	1x1, 2x2, 4x4	0.4ms~2000ms
ICMOS03100KPA IP603100A	3.1M/MT9T001(C) 1/2" (6.55x4.92)	3.2x3.2	1.0 V/lux-sec 61dB 43dB	12@2048x1536 43@1024x768 83@680x510	1x1	0.128ms~2000ms
ICMOS01300KMA IM601300A	1.3M/MT9M001(M) 1/2" (6.66x5.32)	5.2x5.2	2.1 V/lux-sec 68.2dB 45dB	30@1280x1024	1x1	0.64ms~1035.62ms

C: Color; M: Monochrome;

Other Specification for ICMOS Camera

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	ROI White Balance/ Manual Temp Tint Adjustment/NA for Monochromatic Sensor
Color Technique	Ultra-Fine™ Color Engine/NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Natural
Cable Connection	Include Locking Screws
User IO	IO with Optocoupler Isolation(Trigger and Flash)

Operating Modes

Continuous Capture Mode	Video Mode
Single Capture Mode	Hard Trigger or Soft Trigger

Operating Environment


Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 10 (32 & 64 bit) OSX(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory:2GB or More
	USB Port:USB2.0 High-speed Port
	Display:17" or Larger
	CD-ROM

13.1.3 Dimension of ICMOS

The ICMOS body, made from tough, aluminum alloy, ensures a heavy duty, workhorse solution. The camera is designed with a high quality IR-CUT to protect the camera sensor. No moving parts included. This design ensures a rugged, robust solution with an increased lifespan when compared to other industrial camera solutions.



Dimension of ICMOS

13.1.4 Packing Information for ICMOS Camera



Packing Information ICMOS

Standard Camera Packing List

A	Carton L:52cm W:32cm H:33cm (50pcs, 12~17Kg/ carton), not shown in the photo
B	Gift box L:14cm W:9.7cm H:6cm (0.17~0.18Kg/ box)
C	ICMOS series USB2.0 C-mount camera
D	High-speed USB2.0 A male to B male gold-plated connectors cable /2.0m
E	CD (Driver & utilities software, Ø12cm)

Optional Accessory

F	Adjustable lens adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108001/AMA037 108002/AMA050 108003/AMA075
		C-mount to Dia.31.75mm eyepiece Tube (Please choose 1 of them for your telescope)	108008/ATA037 108009/ATA050 108010/ATA075
G	Fixed lens Adapter	C-mount to Dia.23.2mm eyepiece tube (Please choose 1 of them for your microscope)	108005/FMA037 108006/FMA050 108007/FMA075
		C-Mount to Dia.31.75mm eyepiece tube (Please choose 1 of them for your telescope)	108011/FTA037 108012/FTA050 108013/FTA075
H	108015(Dia.23.2mm to 30.0mm Ring)/Adapter rings for 30mm eyepiece tube		
I	108016(Dia.23.2mm to 30.5mm Ring)/ Adapter rings for 30.5mm eyepiece tube		
J	108017(Dia.23.2mm to 31.75mm Ring)/ Adapter rings for 31.75mm eyepiece tube		
K	Calibration kit	106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)	

13.1.5 Extension of ICMOS with Microscope or Telescope Adapter

Extension	Picture	Picture
C-mount Camera		Machine vision; Medical imaging; Semiconductor equipment; Test instruments; Document scanners; 2D barcode readers; Web camera and security video; Microscope imaging;
Microscope Camera	 ICMOS+AMAXXX(23.2mm Adapter)	 ICMOS+FMAXXX(23.2mm Adapter)
Telescope Camera	 ICMOS+ATAXXX(31.75mm Adapter)	 ICMOS+FTAXXX(31.75mm Adapter)

14 ZOPE Series Continuous Zoom Digital Microscope

14.1 Basic Characteristic of ZOPE

- The ZOPE stays in focus when magnification/focal length is changed;
- True continuous zoom that most of the handheld USB microscopes do not have;
- Digital microscope with USB2.0 to computer or HDMI interface to HDMI display;
- Compact and professional optical performance;
- With compact inner 8 high power LEDS for the reflective illumination and uniform LED transmission illumination with battery as the power;
- Long and fixed working distance up to 70mm for all zoom positions;
- CNC mechanical body ensure smooth zooming operation;
- Wide range of resolutions from 1.2M~5M;
- Ultra-Fine™ color engine with perfect color reproduction capability;
- With advanced video & image processing application ToupView;
- Providing Windows/Linux/Mac OS multiple platforms SDK;
- Native C/C++, C#/VB.NET, DirectShow, Twain Control API;
- USB Power, no extra source required;



With transmission illumination



With EPI illumination On

14.2 ZOPE Series Digital Microscope Module List

The ZOPE series digital microscope is a combination of Zoom Lens and USB Camera. Customers can choose their interested parts and our engineers will install them into a ZOPE digital microscope.

Order Code	Zoom Lens	Camera Module
ZOPEA05100KPA ZPA605100A	ZLA 0.25X~1.6X (continues and parfocal)	X05100KPA(5M pixels CMOS camera)
ZOPEA01200KPA ZPA601200A	ZLA 0.25X~1.6X (continues and parfocal)	X01200KPA(1.2M pixels CMOS camera)
ZOPEB05100KPA ZPB605100A	ZLB 0.7X~5.6X(continues and parfocal)	X05100KPA(5M pixels CMOS camera)
ZOPEB01200KPA ZPB601200A	ZLB 0.7X~5.6X(continues and parfocal)	X01200KPA(1.2M pixels CMOS camera)

ZLA: A type zoom lens with 0.25X~1.6X magnification;

ZLB: B type zoom lens with 0.7X~5.6X magnification;

14.3 Zoom Lens for ZOPE Series Digital Microscope

Currently TouTek has 2 kinds of zoom lens for option, they are ZLA and ZLB. Customer can choose the right one according to their applications.

Model	ZLA	ZLB
Specification		
Zoom Lens	0.25X~1.6X (continues and parfocal)	0.7X~5.6X(continues and parfocal)
Working Distance	67.85mm(From lens to object surface)	31.73(from lens to object suface)
MTF	Diffraction limited	Diffraction limited
Field	Φ 28.8~4.5mm	Φ 10.85~1.36mm
Reflection illumination(USB power supply)	8 LEDs embedded illumination(adjustable)	8 LEDs embedded illumination(adjustable)
Transmission Illumination (Battery power, Optional)	Uniform illumination(3 levels switchable)	Uniform illumination(3 levels switchable)

14.4 Camera Modules for ZOPE Series Digital Microscope

Currently we has 2 kinds of camera modules for the Zoom Lens, they are X05100KPA and X01200KPA. We will continue to enrich the camera modules according to the requirements.

Order Code	Sensor & Size(mm)	Pixel(μm)	G Responsivity Dynamic range SNRmax	FPS/Resolution	Binning	Exposure(ms)
X05100KPA	5.1M/MT9P001(C) 1/2.5" (5.7x4.28)	2.2x2.2	0.53 V/lux-sec 66.5dB 40.5dB	5@2592x1944 18@1280x960 60@640x480	1x1, 2x2, 4x4	0.294ms~2000ms
X01200KPA	1.2M/AR0130(M) 1/3"(4.8x3.6)	3.75 x3.75	6.5v/lux-sec 85.3dB 44dB	28@1280x960 30@640x480	1x1, 2x2	0.4ms~2000ms

C: Color; M: Monochrome;

Other Specification for UCMOS Camera

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	ROI White Balance/ Manual Temp Tint Adjustment/NA for Monochromatic Sensor
Color Technique	Ultra-Fine™ Color Engine/NA for Monochromatic Sensor
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Natural


Operating Environment

Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 / 10 (32 & 64 bit) OSX(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher
	Memory:2GB or More
	USB Port:USB2.0 High-speed Port
	Display:17" or Larger
	CD-ROM

14.5 Dimension of ZOPE



14.6 Packing Information for ZOPE Series Digital Microscope

Standard Packing List

A	Carton L:51cm W:31.5cm H:18cm (1pcs, 2.8Kg/ carton, 0.029m ³), not shown in the photo
B	ZOPE series digital microscope
C	Solid stand
D	Hexwrench to install the stand
E	CD (Driver & utilities software, Ø12cm)

Optional Accessory

F	Uniform transmissive illumination kit(3 Battery power supply, 3 levels switchable)
G	Calibration kit 106011/TS-M1(X=0.01mm/100Div.); 106012/TS-M2(X,Y=0.01mm/100Div.); 106013/TS-M7(X=0.01mm/100Div., 0.10mm/100Div.)

15 TSCOPE Series Portable Microscope

15.1 TSCOPE Portable USB Microscope

15.1.1 PUM's Basic Characteristics

The TSCOPE portable USB microscope is an easy to use, high power scope. With continuous powers from 10x to 280x, it's ideal for viewing stamps, coins, bugs, plants, rocks, skin, gems, circuit boards, and more. With the higher power magnifications, you can even view traditional microscope slides under transmitted illumination.

Best of all, you can capture your discoveries using the built-in 2.0MP camera. Press the shutter to save images and high-resolution video directly to your PC. The LED illuminator ensures your specimens are clear and bright. An included metal stand allows for steady shots and comes in handy when viewing at higher powers, minimizing shaking and keeping your specimen in sharp focus.

For teens and adults alike, the TSCOPE portable USB microscope is a fun, educational tool. It's well suited for hobbyists, quality control inspectors, medical professionals, and scientific researchers.

The basic characteristics of PUM are:

- USB powered handheld digital microscope with **continuous** 10x to 280x magnification;
- Object distance controlled zoom property;
- Single object distance, single magnification;
- Linear rotation magnification relationship;
- Object distance from 110 to 10 mm corresponding to 10x to 280x magnification;
- 5G high grade optical glass with multi-layer anti-reflection coating;
- Built-in 2MP(1920x1080) digital camera for capturing images and videos;
- 8 LED ring illuminator with adjustable illumination;
- Use the included Windows software to capture images and videos of your discoveries. Measure your specimens with built-in measurement tool;
- Computer requirements: CD/DVD drive and USB 2.0 port. UVC plug-and-play with Microsoft® Windows® XP / Vista / 7 / 8 /10 (32 & 64 bit), OSx(Mac OS X) and Linux.





Figure 15-1TSCOPE PUM series portable USB microscope

15.1.2 PUM's Hardware Specification

Order Code	Sensor	Size(mm)	Sensitivity	FPS/Resolution	Binning	Exposure
PUM20280A	2.0M/IMX290(C) 1/2.8"(5.56x3.13)	2.9 x2.9	1300mv with 1/30s 0.15mv with 1/30s	17@1920x1080	1x1	0.105ms~15s

C: Color; M: Monochrome;

Optical Specification for PUM

Optical Lens	5G High Grade Optical Glass with Multi-layer Anti-reflection Coating
Optical Magnification	0.1x~3.3x(33x)
Working Distance	13mm~160mm
Illumination	8 LEDs Illumination
Stand	M-SD-HM5 with Ø41mm Holding Ring

Camera Function

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	Auto White Balance
Color Technique	Ultra-Fine™ Color Engine
Capture/Control SDK	Windows/Linux/macOS/Android Multiple Platform SDK(Native C/C++, C#/VB.NET, Python, Java, DirectShow, Twain, etc)
Recording System	Still Picture and Movie
Cooling System*	Natural

Operating Environment

Operating Temperature (in Centidegree)	-10~ 50
Storage Temperature (in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 /10 (32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher Memory:2GB or More USB Port: USB2.0 High-speed Port Display:17" or Larger CD-ROM

15.1.3 Accessory for PUM

M-SD-HM5 stand with Ø41mm holding ring (See Section 17.5 for details).

16 HCAM Series Portable USB2.0 Microscope

16.1 HCAM's Basic Characteristic

The intermediate-level HCAM series portable USB2.0 microscope is an easy to use, low power microscope. With powers of 10x to 200x in nonlinear mode, it's ideal for viewing stamps, coins, bugs, plants, rocks, skin, gems, circuit boards, and more. With the higher power magnifications, you can even view traditional microscope slides.

Best of all, you can capture your discoveries using the built-in 0.35MP, 1.3MP or 2.0 MP camera(KPA series) or 0.35MP,1.3MP, 2.0MP, 3.0MP or 5MP camera(KPB series). Press the shutter to save images and high-resolution video directly to your PC. The LED illuminator ensures your specimens are clear and bright. An included metal stand allows for steady shots and comes in handy when viewing at higher powers, minimizing shaking and keeping your specimen in sharp focus.

For teens and adults alike, the HINOTEK Handheld Digital Microscope is a fun, educational tool. It's well suited for hobbyists, quality control inspectors, medical professionals, and scientific researchers.

The basic characteristics of HCAM are:

- USB-powered handheld digital microscope with 10x to 200x magnification in nonlinear mode;
- Built-in 0.35MP, 1.3MP or 2MP digital camera for capturing image and video (KPA);
- Built-in 0.35MP, 1.3MP, 2MP, 3MP or 5MP digital camera for capturing image and video (KPB);
- 8 LED ring illuminator;
- Use the included Windows software to capture images and video of your discoveries. Measure your specimens with built-in measurement tool;
- Computer requirements: CD/DVD drive and USB 2.0 port. UVC plug-and-play with Windows 7/8/10, Vista, and XP (32/64 bit).



Figure 16-1HCAM KPA series portable USB microscope





Figure 16-2 HCAM KPB series portable USB microscope

16.2 Specification of HCAM Series Portable USB Microscope

16.2.1 HCAM KPA Series

Order Code	Sensor	Size(mm)	Pixel(μm)	FPS/Resolution	Binning	Exposure
HCAM02000KPA HC502000A	MI2010(C)	1/3.2"	2.8x2.8	28 @ 1920 x1080 28@1280x 720 30@640x 480	1x1	0.5ms~30ms
HCAM01300KPA HC501300A	MT9M112(C)	1/4"	2.8x2.8	15@1280x1024 30@640x512	1x1	0.5ms~30ms
HCAM00350KPA HC500350A	GC0308(C)	1/6.5"	3.4x3.4	30@640x480 30@320x240	1x1	0.5ms~30ms

C: Color; M: Monochrome;

16.2.2 HCAM KPB Series

Order Code	Sensor	Size(mm)	Pixel(μm)	FPS/Resolution	Binning	Exposure
HCAM00350KPB HC500350B	BF3A03(C)	1/6.5"	3.15x3.15	20@640x480 20@320x240	1x1	8ms-125ms
HCAM01300KPB HC501300B	PAS5130(C)	1/3	3.75x3.75	30@1280x960 30@1280x720 30@640x480	1x1	8ms-125ms
HCAM02000KPB HC502000B	PS5230(C)	1/2.7"	3.0x3.0	27@1920x1080 27@1280x720 30@640x480	1x1	8ms-125ms
HCAM03000KPB HC503000B	SC5234S(C)	1/3.2"	1.998x1.998	25@2048x1536 25@1920x1080 25@1280x960 25@1024x768	1x1	3.9ms-1000ms
HCAM05000KPB HC505000B	SC5235S(C)	1/2.7"	1.998x1.998	20@2592x1944 20@2048x1536 25@1920x1080 25@1280x960 25@1024x768	1x1	3.9ms-1000ms

C: Color; M: Monochrome;

Working Distance and Magnification for HCAM KPB Series

HCAM00300KPB Resolution 640*480																			
Magnification	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	165		
Working Distance(mm)	90	31.6	12.5	4.5	0.3	-1.8	-2.8	-3	-2.8	-2.3	-1.4	-0.5	0.6	1.7	3	4.5	5.4		
Field (X) mm	16	8	5.33	4	3.2	2.67	2.29	2	1.78	1.6	1.46	1.33	1.23	1.14	1.07	1	0.97		
Field (Y) mm	12	6	4	3	2.4	2	1.72	1.5	1.33	1.2	1.1	1	0.92	0.86	0.8	0.75	0.73		
HCAM01300KPB Resolution 1280*960																			
Magnification	17	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160			
Working Distance(mm)	33.6	24.4	9.3	2.8	-0.3	-1.5	-1.7	-1.3	-0.4	0.7	2.1	3.2	4.8	6.8	8.6	10			
Field (X) mm	18.8	16	10.7	8	6.4	5.33	4.57	4	3.56	3.2	2.9	2.67	2.46	2.29	2.13	2			
Field (Y) mm	14.1	12	8	6	4.8	4	3.43	3	2.67	2.4	2.18	2	1.85	1.72	1.6	1.5			
HCAM02000KPB Resolution 1920*1080																			
Magnification	20	30	40	50	60	70	80	90	100	120	140	160	170	180	190	195			
Working Distance(mm)	36	15.8	6.5	2.2	0	-1.5	-2	-1.9	-1.4	0.2	1.9	4.2	5.7	7.1	8.4	9.6			
Field (X) mm	24	16	12	9.6	8	6.86	6	5.33	4.8	4	3.43	3	2.82	2.67	2.53	2.46			
Field (Y) mm	13.5	9	7.75	5.4	4.5	3.86	3.38	3	2.7	2.25	1.93	1.69	1.59	1.5	1.42	1.38			
HCAM03000KPB Resolution 2048*1536																			
Magnification	24	30	40	50	60	70	80	90	100	120	140	160	180	200	220	230			
Working Distance(mm)	36	24	12	6	2.5	0.5	-0.6	-1.2	-1.3	-0.8	0.4	2.4	4.4	6.6	8.9	10			
Field (X) mm	21.2	16.8	12.6	10.1	8.4	7.2	6.3	5.6	5.05	4.2	3.6	3.15	2.8	2.53	2.3	2.2			
Field (Y) mm	15.9	12.6	9.45	7.58	6.3	5.4	4.73	4.2	3.79	3.15	2.7	2.36	2.1	1.9	1.73	1.65			
HCAM05000KPB Resolution 2592*1944																			
Magnification	33	40	50	60	70	80	90	100	120	140	160	180	200	220	230	240	260	280	290
Working Distance(mm)	30.2	21	12	7	3.4	1.3	0.2	-1	-1.8	-1.7	-0.9	0.2	1.8	3	3.9	4.6	6.4	8.5	9.4
Field (X) mm	19.4	16.2	12.8	10.8	9.3	8	7.2	6.4	5.4	4.6	4.1	3.6	3.2	2.9	2.8	2.7	2.5	2.3	2.2
Field (Y) mm	14.6	12.2	9.6	8.1	7	6	5.4	4.8	4.05	3.45	3.08	2.7	2.4	2.18	2.1	2.02	1.88	1.73	1.65

The magnifications are measured with 22"(558.8mm) display

Optical Specification for HCAM Camera

Optical Lens	5G High Grade Optical Glass with Multi-layer Anti-reflection Coating(KPB)
Optical Magnification	0.1x~3.3x(33x)
Working Distance	See table of Working Distance and Magnification for HCAM KPB Series
Illumination	8 LEDs Illumination
Stand	M-SD-HM1, M-SD-HM2 or M-SD-HM3 for KPA Series M-SD-HM4 with Ø33mm Holding Ring for KPB Series)

Other Specification for HCAM Camera

Spectral Range	380-650nm (with IR-cut Filter)
White Balance	Auto White Balance
Color Technique	N/A
Capture/Control SDK	Standard UVC for Windows(USB2.0)
Recording System	Still Picture and Movie
Cooling System*	Natural

Operating Environment

Operating Temperature(in Centidegree)	-10~ 50
Storage Temperature(in Centidegree)	-20~ 60
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V over PC USB Port

Software Environment

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 /10 (32 & 64 bit) OSx(Mac OS X) Linux
PC Requirements	CPU: Equal to Intel Core2 2.8GHz or Higher Memory:2GB or More USB Port: USB2.0 High-speed Port Display:17" or Larger CD-ROM

16.2.3 Accessory for HCAM Series Portable USB Microscope

M-SD-HM1, M-SD-HM3, M-SD-HM3 for HCAM KPA series portable USB microscope;

M-SD-HM4 for HCAM KPB series portable USB microscope;

17 Stands for the Potable Microscope

17.1 M-SD-HM1 Potable Microscope Stand

Pole stand (Metal) for portable microscope with focus mount has the following basic characteristic


- Oxidized silver aluminum alloy;
- Stable to ensure capturing the clear video and image;
- Overall dimensions: 150mmX80mmX147mm;
- Plate dimensions: 150mmX80mm;
- Pole coaxial focus with 51mm range;



17.2 M-SD-HM2 Portable Microscope Stand

The track stand (Metal) for portable microscope with focus mount has the following basic characteristic:


- Oxidized silver aluminum alloy;
- Focus knob inherited from the traditional microscope to focus at ease;
- Silicon rubber ring to protect the portable microscope;
- Holding screw to hold the microscope;
- Stable to ensure capturing the clear video and image;
- Overall dimensions: 150mmX80mmX135mm;
- Plate dimensions: 150mmX80mm;
- Rack focus with 60mm range;



17.3 M-SD-HM3 Portable Microscope Stand

Plastic stand (Plastic) for portable microscope with focus mount has the following basic characteristic


- Plastic plate with aluminum alloy pole;
- Focus knob inherited from the traditional microscope allow for precise focus;
- Bayonet mount to install the portable microscope at ease;
- Holding screw to hold the microscope;
- Stable to ensure capturing video and image;
- Overall dimensions: 175mmX120mmX180mm;
- Plate dimensions: 175mmX120mm;
- Focus range: 113mm;
- Fine focus range 19mm



17.4 M-SD-HM4 Potable Microscope Stand

The track stand (Metal) for potable microscope with focus mount has the following basic characteristic


- Oxidized silver aluminum alloy;
- Focus knob inherited from the traditional microscope to focus at ease;
- Holding screw to hold the microscope;
- Stable to ensure capturing the clear video and image;
- Overall dimensions: 150mmX80mmX135mm;
- Plate dimensions: 150mmX80mm;
- Rack focus with 60mm range;
- Holding ring diameter $\varnothing 33\text{mm}$;



17.5 M-SD-HM5 Potable Microscope Stand

The track stand (Metal) for handheld microscope with focus mount has the following basic characteristic

- Oxidized silver aluminum alloy;
- Focus knob inherited from the traditional microscope to focus at ease;
- Holding screw to hold the microscope;
- Stable to ensure capturing the clear video and image;
- Overall dimensions: 153mmX83mmX200mm;
- Plate dimensions: 153mmX83mm;
- Rack focus with 110mm range;
- Holding ring diameter $\varnothing 41\text{mm}$;



18**HDMI Displayer for XCAM Series Camera****18.1 TPHD1080PA HDMI Displayer****18.1.1 TPHD1080PA's basic characteristic**

TPHD1080PA is born with our XCAM series HDMI camera and can be used for high definition display. It adopts Panasonic IPS LCD panel(Super TFT) to guarantee the wide view angle and high contrast. Together with XCAM HDMI camera, TPHD1080PA could make the imaging & display solution simple, flexible and intuitive. Outstanding performance of TPHD1080PA helps XCAM HDMI camera reach fast frame rate and excellent color.

The TPHD1080PA's basic characteristic is as follows

- HDMI monitor;
- Panasonic IPS LCD panel;
- True 1080P;
- High contrast ratio up to 1000:1;
- LED backlight with 50000 hours long life time;
- 11.6 inch active area;

18.1.2 TPHD1080PA Datasheet

Order Code	Active Area(Inch)	Video Fomat	Resolution	Contrast	Color(Million)	View Angle
TPHD1080PA HD1080A	11.6	HDMI	1080P	1000:1	16.7	IPS Full View


TPHD1080PA Datasheet

Basic Performance	
LCD Panel	Panasonic IPS LCD Screen(Super TFT)
Input Video Format	HDMI
Native Resolution	1920 x 1080
Display Type	16:9 Ratio 11.6 Inch Active Matrix Super TFT LCD
Typical Contrast Ratio	1000:1
Colors	16.7 Million
Viewing Angle(L/R/U/D)	IPS Full View
Active Display Area	258mm(W) x 145mm(H)
Pixel Pitch	0.134(W) X 0.134(H) mm
Brightness	350 cd/ sq.m ;400cd sq.m / Optional
Backlight	LED Backlight, 50000 hours
Outline Parameter	
Color	Black
Dimension	281(L)*179(H)*15.6(W) mm
Weight	400g
Operating Environment	

TPHD Series High Definition Multimedia Interface Displayer for XCAM Series Camera

Operating Temperature	-15 Degree~55 Degree
Humidity Non Condensing	Operating:10%-90%, Storage: 5%-90%
Synchronization Range	30-80 KHz Horizontal, 55-75 Hz Vertical
Power Supply	AC110V-220V /DC12V(1A)
Power Consumption	Max 12W

18.1.3 TPHD1080PA and XCAM0720PHB/PHC Camera



Front View of TPHD1080PA



Back View of TPHD1080PA+XCAM Series Camera



Side view of TPHD1080PA+XCAM Series Camera



Front View of Leica Microscope+XCAMSeries Camera and TPHD1080PA

Side View of Leica Microscope+XCAMSeries Camera and TPHD1080PA



Front View of Nikon Microscope+XCAMSeries Camera and TPHD1080PA



Side View of Nikon Microscope+XCAMSeries Camera and TPHD1080PA



Front View of Olympus Microscope+XCAMSeries Camera and TPHD1080PA



Side View of Olympus Microscope+XCAMSeries Camera and TPHD1080PA




Front View of Zeiss Microscope+XCAMSeries Camera
and TPHD1080PA



Side View of Zeiss Microscope+XCAMSeries Camera
and TPHD1080PA

18.1.4 TPHD1080PA and XCAM1080PHA,XCAM1080PHB/PHD Camera



Front View of TPHD1080PA



Back View of TPHD1080PA+XCAM Series Camera



Side view of TPHD1080PA+XCAM Series Camera



Front View of Leica Microscope+XCAMSeries Camera and TPHD1080PA



Side View of Leica Microscope+XCAMSeries Camera and TPHD1080PA



Front View of Nikon Microscope+XCAMSeries Camera and TPHD1080PA



Side View of Nikon Microscope+XCAMSeries Camera and TPHD1080PA



Front View of Olympus Microscope+XCAMSeries Camera and TPHD1080PA



Side View of Olympus Microscope+XCAMSeries Camera and TPHD1080PA




Front View of Zeiss Microscope+XCAMSeries Camera
and TPHD1080PA



Side View of Zeiss Microscope+XCAMSeries Camera
and TPHD1080PA

18.1.5 Dimension of TPHD1080PA



Dimension of TPHD1080PA

19 Eyepiece Tube to C-Mount Adapter

19.1 23.2mm Eyepiece to C-mount Adjustable Microscope Eyepiece Adapter

AMA Specifications

Article Code	Picture	Model	Description	Bar Code
108001		AMA037	1.Available Size for 18 mm Field 18X0.37mm 2.Fit to 1/4"~1/3" Size Sensor 3.0.37X Magnification 4.Manually Focusable 5.Parfocal with the Eyepiece 6.Dia.23.2mm Eyepiece Tube to C-Mount	 108001
108002		AMA050	1.Available Size for 18 mm Field 18X0.50mm 2.Fit to 1/2"~2/3" Size Sensor 3.0.50X Magnification 4.Manually Focusable 5.Parfocal with the Eyepiece 6.Dia.23.2mm Eyepiece Tube to C-Mount	 108002
108003		AMA075	1.Available Size for 18 mm Field 18X0.75mm 2.Fit to 1/1.8"~1" Size Sensor 3.0.75X Magnification 4.Manually Focusable 5.Parfocal with the Eyepiece 6.Dia.23.2mm Eyepiece Tube to C-Mount	 108003
108004		AMA100	1.Available Size for 18 mm Field 18X1.00mm 2.Fit to 1"~1.1" Size Sensor 3.1X Magnification 4.Manually Focusable 5.Parfocal with the Eyepiece 6.Dia.23.2mm Eyepiece Tube to C-Mount	

*To cover the field, the sensor size should be smaller than the available size. Our experts will help you to select the correct Adapter for your ordered microscope camera. What you need to do is to select the right camera model.



19.2 23.2mm Eyepiece to C-mount Fixed Microscope Eyepiece Adapter

FMA Specifications

Article Code	Picture	Model	Description	Bar Code
108005		FMA037	1.Available Size for 18 mm Field 18X0.37mm 2.Fit to 1/4"~1/3" Size Sensor 3.0.37X Magnification 4.Dia.23.2mm Eyepiece Tube to C-Mount	 108005
108006		FMA050	1.Available Size for 18 mm Field 18X0.50mm 2.Fit to 1/2"~2/3" Size Sensor 3.0.50X Magnification 4.Dia.23.2mm Eyepiece Tube to C-Mount	 108006
108007		FMA075	1.Available Size for 18 mm Field 18X0.75mm 2.Fit to 1/1.8"~1" Size Sensor 3.0.75X Magnification 4.Dia.23.2mm Eyepiece Tube to C-Mount	 108007
108008		FMA100	1.Available Size for 18 mm Field 18X1.00mm 2.Fit to 1" Size Sensor 3.1.00X Magnification 4.Dia.23.2mm Eyepiece Tube to C-Mount	

*To cover the field, the sensor size should be smaller than the available size. Our experts will help you to select the correct Adapter for your ordered microscope camera. What you need to do is to select the right camera model.



19.3 31.75mm Eyepiece to C-mount Adjustable Telescope Eyepiece Adapter

ATA Specifications

Article Code	Picture	Model	Description	Bar Code
108008		ATA037	1.Fit to 1/4" ~ 1/3" Size Sensor 2.0.37X Magnification 3.Manually Focusable 4.Parfocal with the Eyepiece 5.C-Mount to Dia.31.75mm Eyepiece Tube	 108008
108009		ATA050	1.Fit to 1/2" ~ 2/3" Size Sensor 2.0.50X Magnification 3.Manually Focusable 4.Parfocal with the Eyepiece 5.C-Mount to Dia.31.75mm Eyepiece Tube	 108009
108010		ATA075	1.Fit to 1/1.8" ~ 1" Size Sensor 2.0.75X Magnification 3.Manually Focusable 4.Parfocal with the Eyepiece 5.C-Mount to Dia.31.75mm Eyepiece Tube	 108010

*To cover the field, the sensor size should be smaller than the available size. Our experts will help you to select the correct Adapter for your ordered microscope camera. What you need to do is to select the right camera model.



19.4 31.75mm Eyepiece to C-mount Fixed Telescope Eyepiece Adapter

FTA Specifications

Article Code	Picture	Model	Description	Bar Code
108011		FTA037	1.Fit to 1/4" ~ 1/3" Size Sensor 2.0.37X Magnification 3.C-Mount to Dia.31.75mm Eyepiece Tube	 108011
108012		FTA050	1.Fit to 1/2" ~ 2/3" Size Sensor 2.0.50X Magnification 3.C-Mount to Dia.31.75mm Eyepiece Tube	 108012
108013		FTA075	1.Fit to 1/1.8" ~ 1" Size Sensor 2.0.75X Magnification 3.C-Mount to Dia.31.75mm Eyepiece Tube	 108013

*To cover the field, the sensor size should be smaller than the available size. Our experts will help you to select the correct Adapter for your ordered microscope camera. What you need to do is to select the right camera model.



20 Olympus,Leica,Nikon, Zeiss Phototube to C-Mount Adapter

20.1 Olympus TV Adapter

20.1.1 Characteristic

- Convert the Olympus trinocular microscope phototube/head/port (have standard 35 mm outer diameter for the insertion end to phototube) to traditional C-Mount type(25.4 mm or 1 inch diameter with 32 threads per inch);
- With different built-in reduction lens (1.2X,1X, 0.8X,0.63X, 0.5X, 0.35X) for achieving better field of view from microscope trinocular head(suitable for 4/3" 1", 2/3", 1/1.8", 1/2", 1/2.5", 1/3" or 1/4" inch CCD or CMOS sensor chips);
- Can be installed in UIS trinocular tube such as : BX series, BX2 series, CX series, CX2 series, MX series;
- Build of material: anodized aluminum;
- Telecentric optics with low light deficiency;
- Parfocal with different microscope objective lenses;
- Diffraction limited MTF;
- Aperture totally coupled with UIS microscope objective's exit pupil;

20.1.2 Specifications

Model	Photo	Magnification	Sensor Size	Mount Type
U-TV1.2XT2(NEW)		1.2X	4/3",1"	T2-Mount
U-TV1X-2/U-CAMD3		1.0X	1", 2/3"	C-Mount
U-TV0.80XC(New)		0.80X	1",2/3"	C-Mount

Olympus, Leica, Nikon, Zeiss Phototube to C-Mount Adapter

Olympus, Leica, Nikon, Zeiss Phototube to C-Mount Adapter				
U-TV0.63XC		0.63X	2/3", 1/1.8", 1/2"	C-Mount
U-TV0.5XC-3		0.50X	1/1.8", 1/2", 1/2.5"	C-Mount
U-TV0.40XC		0.40X	1/2.5", 1/3", 1/4"	C-Mount
U-TV0.35XC-2		0.35X	1/3", 1/4", 1/5"	C-Mount
Supported Microscope	Specially designed for Olympus CX, BX, MX, STM, SZX, IX, GX(GX41) series microscopes			

20.2 Zeiss TV Adapter

20.2.1 P95 Series Zeiss Characteristic

- Convert the Zeiss trinocular microscope phototube/head/port (have standard ISO 30 mm(1.18 inch) outer diameter for the insertion end to phototube) to traditional C-Mount type(25.4 mm or 1 inch diameter with 32 threads per inch);
- With different built-in reduction lens (1.2X, 1X, 0.8X, 0.65X, 0.5X, 0.35X) for achieving better field of view from microscope trinocular head(suitable for 4/3" 1", 2/3", 1/1.8", 1/2", 1/2.5", 1/3" or 1/4" inch CCD or CMOS sensor chips);
- Can be installed in Zeiss UIS trinocular tube such as:
Zeiss PrimoStar series and Zeiss Primo vert series
- Build of material: anodized aluminum;
- Telecentric optics with low light deficiency;
- Parfocal with different microscope objective lenses;
- Diffraction limited MTF;
- Aperture totally coupled with UIS microscope objective's exit pupil;

20.2.2 Specifications for the P95 series adapter

Model	Photo	Magnification	Sensor Size	Mount Type
P95-T2 4/ P95-C 1" 1.0 x 3" 1.2x(New)		1.2X	1", 4/3"	T2-Mount
P95-C 1" 1.0x		1X	1", 2/3"	C-Mount
P95-C 1" 0.8x(New)		0.8X	1", 2/3"	C-Mount
P95-C 2/3" 0.65x		0.65X	2/3", 1/1.8", 1/2"	C-Mount

Olympus, Leica, Nikon, Zeiss Phototube to C-Mount Adapter

P95-C 1/2" 0.50x		0.5X	1/1.8", 1/2", 1/2.5"	C-Mount
P95-C 1/3" 0.35x		0.35X	1/3", 1/4", 1/5"	C-Mount
Supported Microscope	Specially designed for Zeiss Primo Star series , Zeiss Primo vert series			

20.2.3 60N-C, 60N-T2 Series TV Adapter Characteristic for Zeiss Microscope

- Convert the Zeiss trinocular microscope phototube/head/port (have standard ISO 30 mm(1.18 inch) outer diameter for the insertion end to phototube) to traditional C-Mount type(25.4 mm or 1 inch diameter with 32 threads per inch);
- With different built-in reduction lens (1.2X, 1X, 0.8X, 0.65X, 0.5X, 0.35X) for achieving better field of view from microscope trinocular head(suitable for 4/3" 1", 2/3", 1/1.8", 1/2", 1/2.5", 1/3" or 1/4" inch CCD or CMOS sensor chips);
- Can be installed in Zeiss UIS trinocular tube such as Axio series microscope;
- Build of material: anodized aluminum;
- Telecentric optics with low light deficiency;
- Parfocal with different microscope objective lenses;
- Diffraction limited MTF;
- Aperture totally coupled with UIS microscope objective's exit pupil;

20.2.4 Specifications for the 60N-C or 60N-T2 series adapter

Model	Photo	Magnification	Sensor Size	Mount Type
60N-T2 4/3" 1.2x(New)		1.20X	1", 4/3"	T2-Mount
60N-C 1" 1.0x		1.0X	1", 2/3"	C-Mount
60N-C 1" 0.8x(New)		0.80X	1", 2/3"	C-Mount
60N-C 2/3" 0.63x(New)		0.63X	2/3", 1/1.8", 1/2"	C-Mount
60N-C 1/2" 0.5x		0.50X	1/1.8", 1/2", 1/2.5"	C-Mount
Supported Microscope	Axio Examiner.A1; Axio Examiner.D1; Axio Examiner.Z1;			

	Axio Imager Vario; Axio Imager.A1; Axio Imager.A1m; Axio Imager.A2; Axio Imager.A2m; Axio Imager.D1; Axio Imager.D1 for epi-fluorescence with ApoTome equipment; Axio Imager.D1m; Axio Imager.D2; Axio Imager.D2m; Axio Imager.M1 (Axio Imager.M1 for KS ELISPOT); Axio Imager.M1m; Axio Imager.M2 ; Axio Imager.M2m; Axio Imager.Z1; Axio Imager.Z1 + ApoTome; Axio Imager.Z1m; Axio Imager.Z2; Axio Imager.Z2m; Axio Lab.A1; Axio Lab.A1 FL-LED; Axio Lab.A1 MAT; Axio Lab.A1 Pol; Axio Observer.A1; Axio Observer.A1 Entry; Axio Observer.D1; Axio Observer.D1 Entry; Axio Observer.D1 Mid Range; Axio Observer.Z1; Axio Observer.Z1 High End; Axio Scope.A1; Axio Scope.A1 Pol; Axio Scope.A1 Vario; Axio Vert.A1; Axio Vert.A1 FL; Axio Vert.A1 FL-LED; Axio Vert.A1 MAT; Axio Zoom.V16; PALM CombiSystem Rel. 4.2; PALM MicroBeam; PALM MicroBeam Rel.4.2; PALM MicroTweezers Rel.4.2; Stemi 508 doc; Stemi 508 trino; SteREO Discovery.V12; SteREO Discovery.V8; SteREO Lumar.V12;
--	---



The Primo Star and ToupCam Camera

20.3 LEICA TV Adapter

20.3.1 Characteristic

- Convert the LEICA trinocular microscope phototube/head/port (have standard 35 mm outer diameter for the insertion end to phototube) to traditional C-Mount type(25.4 mm or 1 inch diameter with 32 threads per inch);
- With different built-in reduction lens (1.2X, 1X, 0.8X, 0.7X, 0.55X, 0.35X) for achieving better field of view from microscope trinocular head(suitable for 4/3" 1", 2/3", 1/1.8", 1/2", 1/2.5", 1/3" or 1/4" inch CCD or CMOS sensor chips);
- Can be installed in UIS trinocular tube such as: specially designed for LEICA DM series biology microscopes and industrial microscopes;
- Build of material: stainless steel material;
- Telecentric optics with low light deficiency;
- Parfocal with different microscope objective lenses;
- Diffraction limited MTF;
- Aperture totally coupled with LEICA UIS microscope objective's exit pupil;

20.3.2 Specifications

Model	Photo	Magnification	Sensor Size	Mount Type
11541510-120 HT2-1.2X(New)		1.2X	4/3", 1"	T2 Mount
11541510 HC-1.0X		1.0X	1", 2/3"	C-Mount
11541510-080 HC-0.80X(New)		0.8X	1", 2/3"	C-Mount
11541543 HC 0.70X		0.7X	2/3", 1/1.8", 1/2"	C-Mount
11541544 HC-0.55X		0.55X	1/1.8", 1/2", 1/2.5"	C-Mount
11541512 HC-0.35X		0.35X	1/2.5", 1/3", 1/4"	C-Mount
Supported Microscope	Specially designed for LEICA DM series biology microscopes and industrial microscopes			

20.4 NIKON TV Adapter

20.4.1 Characteristic

- Convert the NIKON trinocular microscope phototube/head/port (have standard 38 mm(1.50 inch) outer diameter for the insertion end to phototube) to traditional C-Mount type(25.4 mm or 1 inch diameter with 32 threads per inch);
- With different built-in reduction lens (1.2X, 1X, 0.8X, 0.70X, 0.55X, 0.35X) for achieving better field of view from microscope trinocular head(suitable for 4/3" 1", 2/3", 1/1.8", 1/2", 1/2.5", 1/3" or 1/4" inch CCD or CMOS sensor chips);
- Can be installed in UIS trinocular tube such as : NIKON E100, E200, 50i, 55i, 80i, 90i, Ni series, Ti Series, SMZ800, SMZ1000, SMZ15000 biology microscopes and industrial microscopes;
- Build of material: stainless steel material for the C-Mount end and spray-painted aluminum for the phototube end ;
- Telecentric optics with low light deficiency;
- Parfocal with different microscope objective lenses;
- Diffraction limited MTF;
- Aperture totally coupled with UIS microscope objective's exit pupil;

The Adapter works for the following microscope series: NIKON microscopes UPRIGHT: Alphaphot-2, Eclipse series (requires YT-tube 92306), Labophot-2, Optiphot-2 Optiphot 100S, 150, 200, 300 Stereo: SMZ-10A, SMZ-U, SMZ-1000, SMZ-1500 METALLURGICAL: EPIPHOT 300/200 MEASURING: MM-40, MM-60 INVERTED: Diaphot 300/200 TS100-F TE2000

20.4.2 Specification

Model	Photo	Magnification	Sensor Size	Mount Type
MQD42120(New) MBB42120		1.2X	4/3", 1"	T2-Mount
MQD42000 MBB42000		1.0X	1", 2/3"	C-Mount
MQD42080(New) MBB42080		0.8X	1", 2/3"	C-Mount

Olympus, Leica, Nikon, Zeiss Phototube to C-Mount Adapter

MQD42070 MBB42070		0.7X	2/3", 1/1.8", 1/2"	C-Mount
MQD42055 MBB42055		0.55X	1/1.8", 1/2", 1/2.5"	C-Mount
MQD42035 MBB42035		0.35X	1/2.5", 1/3", 1/4"	C-Mount
Supported Microscope	Specially designed for NIKON E100, E200, 50i, 55i, 80i, 90i, Ni series, Ti Series, SMZ800, SMZ1000, SMZ15000 biology microscopes and industrial microscopes			

20.5 HUVITZ TV Adapter

20.5.1 Characteristic

- Convert the HUVITZ trinocular microscope phototube/head/port (have standard 35 mm outer diameter for the insertion end to phototube) to traditional C-Mount type(25.4 mm or 1 inch diameter with 32 threads per inch);
- With different built-in reduction lens (1.2X, 1X, 0.8X, 0.63X, 0.5X, 0.35X) for achieving better field of view from microscope trinocular head(suitable for 4/3" 1", 2/3", 1/1.8", 1/2", 1/2.5", 1/3" or 1/4" inch CCD or CMOS sensor chips);
- Can be installed in UIS trinocular tube such as : HRM series, HSZ series microscope;
- Build of material: anodized aluminum;
- Telecentric optics with low light deficiency;
- Parfocal with different microscope objective lenses;
- Diffraction limited MTF;
- Aperture totally coupled with UIS microscope objective's exit pupil;

20.5.2 Specifications

Model	Photo	Magnification	Sensor Size	Mount Type
HSZ-T2P1.2(NEW)		1.2X	4/3", 1"	T2-Mount
HSZ-CP1X		1X	1", 2/3"	C-Mount
HSZ-CP0.80X (New)		0.80X	1", 2/3"	C-Mount
HSZ-CP0.63X		0.63X	2/3", 1/1.8", 1/2"	C-Mount
HSZ-CP0.5X		0.5X	1/1.8", 1/2", 1/2.5"	C-Mount

Olympus, Leica, Nikon, Zeiss Phototube to C-Mount Adapter

HSZ-CP0.35X	 A black cylindrical adapter with a small circular logo containing a stylized letter 'G' and the text 'FOCUS LOCK+' near the top.	0.35X	1/3", 1/4", 1/5"	C-Mount
Supported Microscope	Specially designed for HUVITZ HRM series, HSZ series microscopes			

20.6 Labomed TV Adapter

20.6.1 Characteristic

- Convert the Labomed trinocular microscope phototube/head/port (have standard 35 mm outer diameter for the insertion end to phototube) to traditional C-Mount type(25.4 mm or 1 inch diameter with 32 threads per inch);
- With different built-in reduction lens (1X, 0.63X, 0.5X, 0.35X) for achieving better field of view from microscope trinocular head(suitable for 1", 2/3", 1/1.8", 1/2", 1/2.5", 1/3" or 1/4" inch CCD or CMOS sensor chips);
- Can be installed in UIS trinocular tube such as : LB series microscope;
- Build of material: anodized aluminum;
- Telecentric optics with low light deficiency;
- Parfocal with different microscope objective lenses;
- Diffraction limited MTF;
- Aperture totally coupled with UIS microscope objective's exit pupil;

20.6.2 Specifications

Model	Photo	Magnification	Sensor Size	Mount Type
LB1.0X		1X	1", 2/3"	C-Mount
LB0.75X		0.75X	2/3", 1/1.8", 1/2"	C-Mount
LB0.65X		0.65X	1/1.8", 1/2", 1/2.5"	C-Mount

Olympus, Leica, Nikon, Zeiss Phototube to C-Mount Adapter

Olympus, Leica, Nikon, Zeiss Phototube to C-Mount Adapter				
LB0.50X		0.5X	1/2.3,1/2.5",1/3"	C-Mount
LB0.35X		0.35X	1/2.5",1/3",1/4"	C-Mount
Supported Microscope	Specially designed for Labomed LB series microscopes			

21 Microscope 23.2 to 30, 30.5, 30.75 Eyepiece Converter

21.1 The Basic Characteristic of the Eyepiece Converter

- The Eyepiece converter can make the 23.2 mm camera Adapter to different size microscope and telescope eyepiece holder. The TouTek's FMA and AMA end size is 23.2mm and can be directly inserted into the 23.2mm microscope eyepiece holder;
- For 23.2 eyepiece holder, no extra converter is needed for the microscope;
- The 23.2mm to 30.0mm converter is needed to connecting the 23.2mm camera Adapter to the 30 mm eyepiece holder microscope;
- The 23.2mm to 30.5mm converter is needed to connecting the 23.2mm camera Adapter to the 30.5 mm eyepiece holder microscope;
- The 23.2mm to 31.75mm converter is needed to connecting the 23.2mm camera Adapter to the 31.75 mm eyepiece holder microscope;
- For 31.75 mm eyepiece holder, user can directly use our'31.75mm FMA and AMA for their C - mount Camera.

21.2 Specification of the Eyepiece Converter

Order Code	Picture	Model	Characteristic
108015		MET2323000	Dia.23.2mm to 30.0mm Converter
108016		MET2323050	Dia.23.2mm to 30.5mm Converter
108017		MET2323175	Dia.23.2mm to 31.75mm Converter

22 Lens for Machine Vision






22.1 TP-1632ZL5M (16mm~32mm, 1" Format)

22.1.1 Specification

Resolution:	150lp/mm
Format :	1 "
Mount :	C
Focal Length :	16 ~ 32mm
F/No:	F1.8~F16
Iris Type :	Manual Iris
Horizontal of view :	53.2° ~ 27.5°
Distortion :	±1%
Focusing range :	∞ ~ 0.3m
Coating Range:	400nm~950nm
Filter Thread:	M62 x 0.75mm
Dimension:	Φ 66 x 113.35mm
Weight:	619g

22.1.2 Drawing and Optical Performance





22.2 TPWA Series Lens with CS-mount

Model No.	Focal Length	Aperture	Mount	Format	FOV	Dimensions	M.O.D(m)	Weight(g)	Remarks
TPF-F02116	2.1mm	2.0	CS	1/3"	151°	Φ30*16.7mm	0.2	45	
TPF-F02516	2.5mm	2.0	CS	1/3"	140°	Φ30*19mm	0.2	45	
TPF-F02816	2.8mm	2.0	CS	1/3"	138°x104°x74°	Φ30*17.7mm	0.2	38	



22.3 TP3MP Series Lens with CS-mount

Model No.	Focal Length	Aperture	Mount	Format	FOV	Dimensions	M.O.D(m)	Weight(g)	Remarks
TPF-F02512IR3MP	2.5mm	1.2	CS	1/2.5"	115°x109°x90°	Φ28*23.6mm	0.2	32.6	全金属
TPF-F02812IR3MP	2.8mm	1.2	CS	1/2.5"	110°x104°x90°	Φ28*23.6mm	0.2	32.6	全金属
TPF-F0412IR3MP	4.0mm	1.2	CS	1/2.5"	76°	Φ28*30.0mm	0.2	44.6	全金属
TPF-F0612IR3MP	6.0mm	1.2	CS	1/2.5"	49.8°	Φ30*32.5mm	0.2	49.2	全金属
TPF-F0812IR3MP	8.0mm	1.2	CS	1/2.5"	35°	Φ30*32.5mm	0.2	49.2	全金属
TPF-F2512IR3MP	25mm	1.2	CS	1/2.5"	16.7°	Φ30*32.2mm	0.2	54	全金属

22.4 TP2MP Series Lens with CS-mount

Model No.	Focal Length	Aperture	Mount	Format	FOV	Dimensions	M.O.D(m)	Weight(g)	Remarks
TPF-F0411IR2MP	4mm	F1.2	CS	1/2."	80°	Φ30*30.0mm	0.2	49.5	全金属
TPF-F4080HD	4mm	F1.2	CS	1/2.7"	82.6°	Φ28*31.5mm	0.2m	48	
TPF-F0611IR2MP	6mm	1.2	CS	1/2."	54°	Φ30*30.0mm	0.2	50.5	
TPF-F6080HD	6mm	F1.2	CS	1/2.7"	54°	Φ28*31.5mm	0.2m	50.5	
TPF-F0811IR2MP	8mm	1.2	CS	1/2."	40°	Φ30*30.0mm	0.2	48.4	全金属
TPF-F1211IR2MP	12mm	1.2	CS	1/2."	28°5'	Φ30*30.0mm	0.2	49.5	全金属
TPF-F1611IR2MP	16mm	1.2	CS	1/2."	23°	Φ30*30.0mm	0.2	33.0	全金属

22.5 TP1MP Series Lens with CS-mount

Model No.	Focal Length	Aperture	Mount	Format	FOV	Dimensions	M.O.D(m)	Weight(g)	Remarks
TPF-F0412IR	4.0mm	1.2	CS	1/3"	63.8°	Φ30*35mm	0.2	49.5	全金属
TPF-F0612IR	6.0mm	1.2	CS	1/3"	45.3°	Φ30*33mm	0.2	45.5	全金属
TPF-F0812IR	8.0mm	1.2	CS	1/3"	34°12'	Φ30*34mm	0.2	48.4	全金属
TPF-F1212IR	12mm	1.2	CS	1/3"	17°42'	Φ30*32mm	0.2	33	全金属
TPF-F1612IR	16mm	1.2	CS	1/3"	17°42'	Φ30*32mm	0.2	33	全金属
TPF-F0814IR	8mm	1.4	CS	1/3"	34°42'	Φ30*26.5mm	0.2	33.5	全金属
TPF-F2514IR	25mm	1.4	CS	1/3"	13°7'	Φ30*36mm	0.2	47	全金属
TPF-F1214IR	12mm	1.4	CS	1/3"	23°30'	Φ28*25.2mm	0.2	27.6	全金属
TPF-F0414IR	4.0mm	1.4	CS	1/3"	63.8°	Φ30*30.15mm	0.2	38.5	全金属
TPF-F0614IR	6.0mm	1.4	CS	1/3"	44.5°	Φ30*32mm	0.2	36	全金属
TPF-F1614IR	16mm	1.4	CS	1/3"	17°1'	Φ30*32mm	0.3	36.5	全金属
TPF-F2514IR-C	25mm	1.4	C	1/2"	63.8°	Φ30*31mm	0.2	47	全金属

22.6 FA-A Series Machine Vision Lens (1/1.9" 6M Resolution)

22.6.1 Characteristic

- Compatible with 6M resolutions sensor
- The minimum F# is 2.8, support the maximum 1/1.9" sensor
- Super low distortion and high relative illumination
- Optimized for machine vision illumination light and sensor
- Smart structure, high seismic resistance, high and low temperature work stability
- Multilayer broadband coating ensures high transmittance and low stray light of visible and near infrared light
- Support ultra-short work distance, the different working distances are optimized to ensure the lens's optimal performance



22.6.2 Specifications (7)

Model	EFFL (mm)	F# Number	Optical Distortion	FOV			Minimum Working Distance(m)	Filter Thread	Interface
				D	H	V			
FA-A0628M-6MP	6	F2.8-F16	-1.50%	73.5°	62.8°	44.5°	0.035	~	C
FA-A0828M-6MP	8	F2.8-F16	-0.96%	58.5°	49.3°	34.0°	0.04	M27*0.5	C
FA-A1228M-6MP	12	F2.8-F16	-0.38%	41.2°	34.4°	23.4°	0.06	M27*0.5	C
FA-A1628M-6MP	16	F2.8-F16	-0.08%	31.0°	25.7°	17.5°	0.07	M27*0.5	C
FA-A2528M-6MP	25	F2.8-F16	-0.02%	19.8°	16.3°	10.9°	0.15	M25.5*0.5	C
FA-A3528M-6MP	35	F2.8-F16	-0.02%	13.8°	11.3°	7.6°	0.18	M27*0.5	C
FA-A5028M-6MP	50	F2.8-F16	0.11%	9.7°	8.0°	5.4°	0.30	M25.5*0.5	C

22.6.3 Lens Layout

22.7 FA-B Series Machine Vision lens (2/3" 6M Resolution)

22.7.1 Lens Characteristic

- Compatible with 6M resolutions sensor
- The minimum F# is 2.0, support the maximum 2/3" sensor
- Super low distortion to ensure high measurement accuracy
- Compact structure, can be integrated to compact apparatus
- High performance price ratio



22.7.2 Specifications (6)

Model	EFFL(mm)	F# Number	Optical Distortion	FOV			Minimum Working Distance(m)	Filter Thread	Interface
				D	H	V			
FA-B0824M-5MP	8	F2.4-F16	-2.06%	70.2°	58.1°	44.5°	0.03	~	C
FA-B1220M-5MP	12	F2.0-F16	-1.01%	48.8°	40.2°	30.6°	0.08	~	C
FA-B1620M-5MP	16	F2.0-F16	-0.28%	37.8°	30.8°	23.5°	0.10	M27*0.5	C
FA-B2520M-5MP	25	F2.0-F16	-0.88%	23.5°	18.8°	14.2°	0.15	M27*0.5	C
FA-B3520M-5MP	35	F2.0-F16	-0.09%	17.8°	14.3°	10.8°	0.20	M27*0.5	C
FA-B5028M-5MP	50	F2.8-F16	0.04%	12.5°	10.1°	7.5°	0.35	M27*0.5	C

22.7.3 Lens Layout

22.8 FA-C Series Machine Vision Lens(1" 10M Resolution)

22.8.1 Lens Characteristic

- Compatible with 10M resolutions sensor
- The minimum F# is 2.8, support the maximum 1" sensor
- Super low distortion and high relative illumination
- Optimized for machine vision illumination light and sensor
- Smart structure, high seismic resistance, high and low temperature work stability
- Multilayer broadband coating ensures high transmittance and low stray light of visible and near infrared light
- Support ultra-short work distance, the different working distances are optimized to ensure the lens's optimal performance



22.8.2 Specifications(5)

Model	EFFL(mm)	F# Number	Optical Distortion	FOV			Minimum Working Distance(m)	Filter Thread	Interface
				D	H	V			
FA-C1228M-12MP	12	F2.8-F16	-1.79%	70.5°	59.8°	46.2°	0.10	~	C
FA-C1628M-12MP	16	F2.8-F16	-1.30%	54.8°	44.9°	33.9°	0.08	M35.5*0.5	C
FA-C2528M-12MP	25	F2.8-F16	0.40%	36.7°	29.6°	22.1°	0.12	M35.5*0.5	C
FA-C3528M-12MP	35	F2.8-F16	-0.21%	26.7°	21.4°	15.9°	0.18	M35.5*0.5	C
FA-C5028M-12MP	50	F2.8-F16	-0.05%	18.9°	15.1°	11.2°	0.28	M35.5*0.5	C

22.8.3 Lens Layout

22.9 FA-D and FA-E Series Telecentric Lens

22.9.1 Lens Characteristic

- FA-D is compatible with 2/3" sensor, FA-E is compatible with 1/2" sensor
- Object space telecentric design
- High resolution, high contrast and high relative illumination
- Ultra low distortion and suite for high accuracy measurement and alignment
- Standard C-mount interface



22.9.2 Specifications (18)

Model	Magnification	WD (mm)	Sensor Size	DOF (mm)	Resolution (μm)	Optical Distortion	Telecentricity	F#	TTL (mm)	Max Diameter (mm)	Coaxial Illumination
FA-D-05-110	0.5	110	2/3"	2.98	12	≤0.05%	≤0.1°	9.3	120.5	35	✓
FA-D-08-65	0.8	65	2/3"	1.25	8.3	≤0.10%	≤0.1°	10	89.7	26	
FA-D-08-130	0.8	130	2/3"	1.4	9.4	≤0.10%	≤0.1°	11.2	117.1	28	✓
FA-D-1-65	1	65	2/3"	0.8	7.5	≤0.10%	≤0.1°	11	79.9	26	✓
FA-D-1-110	1	110	2/3"	0.88	7.4	≤0.05%	≤0.1°	11	128.4	30	✓
FA-D-2-65	2	65	2/3"	0.2	4.5	≤0.10%	≤0.1°	13.2	80.0	26	✓
FA-D-2-110	2	110	2/3"	0.27	4.5	≤0.05%	≤0.1°	13.6	130.4	30	✓
FA-D-4-110	4	110	2/3"	0.11	3.7	≤0.05%	≤0.1°	22	110.2	30	
FA-E-05-110	0.5	110	1/2"	2.9	25.4	≤0.50%	≤0.1°	18.8	46.2	16	
FA-E-05-65	0.5	65	1/2"	2	8.5	≤0.10%	≤0.1°	6.5	68.0	16	
FA-E-08-65	0.8	65	1/2"	2.9	20	≤0.10%	≤0.1°	23.9	76.0	16	✓
FA-E-08-130	0.8	130	1/2"	2.9	20	≤0.10%	≤0.1°	23.5	97.1	18	✓
FA-E-1-65	1	65	1/2"	1.1	10	≤0.20%	≤0.1°	14.9	80.0	16	✓
FA-E-1-110	1	110	1/2"	1.5	13.2	≤0.10%	≤0.1°	19.7	109.8	18	✓
FA-E-2-65	2	65	1/2"	0.33	5.6	≤0.10%	≤0.1°	16.7	80.1	16	
FA-E-2-110	2	110	1/2"	0.7	12.9	≤0.20%	≤0.1°	31.7	73.8	16	
FA-E-3-110	3	110	1/2"	0.3	7.65	≤0.10%	≤0.1°	34.2	117.1	16	✓
FA-E-4-110	4	110	1/2"	0.18	6.1	≤0.10%	≤0.1°	36.3	132.5	16	✓

FA-D is compatible with 2/3" sensor, FA-E is compatible with 1/2" sensor

22.9.3 Lens Layout

23 LHCCD Series Linear CCD Camera

23.1 Basic Characteristic

- Linear USB2.0 CCD camera with C-mount, f-mount, and M72x0.75 photography standards;
- 2048~3648 pixel silicon linear CCD array;
- 16-Bit A/D converter for high intensity resolution;
- External trigger capability;
- Optical integration time adjustable from 2 to 4000ms;
- Board-level camera, ideal for OEM applications;
- No external power supply required;
- High scan rate (up to 120 scans/second);
- SDK for user applications;
- Demo graphical user interface;
- Compatible to Windows XP, Vista and 7/8(32 or 64 bit);

23.2 Datasheet

Order Code	Sensor	Size(mm)	Pixel(μm)	FPS/Resolution	Binning	Exposure(ms)
LHCCD00511	ILX511 (M)	28mm	14x200	475@2048	NA	2ms~4000ms,
LHCCD00554	ILX554 (M)	28mm	14x56	475@2048	NA	2ms~4000ms
LHCCD01304	TCD1304 (M)	29.184mm	8x200	125@3648	NA	3.8ms~4000ms

OTHER HARDWARE CONFIGURATION

Capture/Control SDK	SDK and Example Code
Capture Mode	Single Camera Multiple Instance and Multiple Cameras Supported
Lens Mount(Optional)	M42
Host Interface	USB2.0

SOFTWARE ENVIRONMENT

Operating System	Microsoft® Windows® XP / Vista / 7 / 8 (32 & 64 Bit)
PC Requirements	CPU: Equal to Intel Core 2 2.8GHz or Higher
	Memory:2GB or More
	USB Port:USB2.0 High-speed Port

OPERATING ENVIRONMENT

Operating Temperature	-30~70
Storage Temperature	-40~85
Operating Humidity	30~80%RH
Storage Humidity	10~60%RH
Power Supply	DC 5V Over USB Port

24 TouVi for Cameras

TouView is professional software integrated with camera control, image capture & process, image browse, image measurement and analysis. TouView is born with the following features:


24.1 User-friendly UI design

Well-arranged menus and toolbars ensure quick operating;

The unique design of 5 sidebars -- Camera, Folders, Undo/Redo, Layer, Measurement are orderly classified;

Convenient operating method (Double click or right-click context menu) as much as possible;

Detailed help manual;



24.2 Professional Camera Control Panel

Exposure & Gain	Auto exposure (exposure target preset) and manual exposure (exposure time can be inputted manually); Up to 5 times gain;
White Balance	Advanced single-click intelligent white balance setting, temperature and tint can be manually adjusted;
Color Adjustment	Hue, saturation, brightness, contrast, gamma initialization adjustment;
Frame Rate Control	Adjustment of frame rate available for different computer configurations;
Power Frequency Setting(Anti-flicker)	Natural light/DC, AC 50 HZ, AC60 HZ switch function thoroughly eliminates video flicker;
Flip	Check the “horizontal” or “vertical” option to correct the sample direction;
Skip and bin sampling	Bin mode can obtain low noise video stream; Skip mode obtains sharper and smoother video stream. Support video stream histogram extension, Negative and positive switching, Gray calibration, Clarity factor for focusing etc.
Parameters	Load, save, overwrite, import, export self-defined parameters of camera control panel (including calibration information, exposure and color setting information);

24.3 Practical functions with good results

Video functions	Various professional functions: Video broadcast; Time lapse capture; Video record; Video watermark; Move watermark; Rotate watermark; Video stream grid; Video measurement; Video calibration, Gray calibration; Video EDF; Image stitch; Video scale bar, date and etc.;
-----------------	---

TouVi for Cameras

Image Processing and Enhancement	Control and adjust image by contrast, denoise, all kinds of filtering algorithm and mathematical morphology algorithm; image rotate, image scale, image print;
2D Measurement	Easy video or image calibration. Various video and image measurement methods like area, perimeter, angle etc.. Measurement results can be hierarchical controlled according to characteristics or preferences;
Image Stitching	Image stitching can automatically combine a sequence of relevant images into a perfect larger one. No requirement on the image order: Support video window, image window, browse window image stitching operation.
EDF(Extended Depth of Focus)	Aimed at generating a clearer image by combining a sequence of previously captured multi-focus images; Support video window, image window, browse window EDF operation. Provided with maximum contrast, weighted average, FFDSSD algorithms to meet with most applications. Consider image shift, rotation and scale in the EDF process to guarantee EDF accuracy & speed;
Professional Segmentation & Count function	Integrate the advanced 6 image segmentation and particle counting algorithm (Watershed (W), OTSU Dark, OTSU Bright, RGB Histogram, HSV Histogram and Color Cube). Manual segmentation function (Split objects) ensures the success of a complete segmentation. The count result can be exported to Microsoft Excel for further analysis;
Image Stacking	Image stacking adopts advanced image matching technology. With the recorded video, regardless of shifting, rotation, scaling, the high fidelity image can be stacked to decrease the image noise.
Color Composite	Color composite adds appropriate pseudo color to monochrome fluorescence images. Fluorescence probe and color can be chosen from the pre-defined database. Dye database can also be easily created for special fluorescence probe.





Image Stitching



EDF(Extended Depth of Focus)



24.4 Powerful compatibility

Video Interface	Support Twain, DirectShow, Labview, SDK Package (Native C++, C#)
Operating System	Compatible with Microsoft® Windows® XP / Vista / 7 / 8 /10 (32 & 64 bit), Mac OSX, Linux
Language Support	Unlimited language support, currently available in English, Catalan, French, German, Indonesian, Italian, Japanese, Korean, Polish, Russian, Simplified Chinese, Spanish, Thai, Traditional Chinese, and Turkish

24.5 Hardware Requirement

PC Requirements	CPU: Intel Core 2 2.8GHz or Higher
	Memory:2GB or more
	USB port:USB2.0 or USB3.0 port
	Display:17" or Larger
	CD-ROM